Sec 2 T 35N R 10E.

CHAINS		LINE BET. SEC. 35/2 T36NR10E T35NR10E H.C.LAWRENCE S.P.MARMES 9/28/54
EAST 1/2		FROM COR OF SEC 35-36 T36N AND SEC 1-2 T35NR10E
		I RUN S 89°-00' W. MAG. (FOR DATA AT COR. See Sec 1.)
1	80	EMIL MYERS OLD ROAD C-NE&SW.
17	15	" " " " C-E & W.
19	80	" " " " C-E & W
31	00	OFFSET 2 LKS SOUTH TO PASS BIG HARDWOOD TREE
33	00	notched into an 8" HEMLOCK TO SIGHT THROUGH
37	30	in an old Road C-NE & SW.
38	56	THE ORIG. GOV'T 1/4 COR IS 78 LKS SOUTH
		(.78 + 02 offset = 80 LKS Dep.) .80 ÷ 38.56 = .021
		.021 = 1°-12' DEFL. Δ)
		S 89°-00' W + 1°-12' = N 89°-48' W = TRUE LINE.
		AN IRON PIPE AT 1/4 COR. ALSO ORIGINAL BIRCH B.T.
1/4 S		STANDING. I SET NEW 4" CEDAR POST FROM ORIGINAL Birch
		and made new B.T. viz: HEMLOCK 14" S 28 W 61.
		I SET A 5" CEDAR POST FOR E 1/16 CORNER 40 LKS SOUTH
E 1/16		OF 19.28 chs. INTERMEDIATE. AND MADE BTS VIZ:
		(S MAPLE 10" S 70 W - 31 1/2 LKS.) (OAK 6" N 50°E - 50 LKS).
WEST 1/2		LINE BET. SEC. 35/2 (NOT RUN.)

CHAINS		EAST AND WEST 1/4 LINE SEC. 2 (EAST OF C 1/4)
		THE C 1/4 COR. OF SEC. 2 WAS SET BY B.F. DORR IN
		1896. THE STUMPS OF HIS BTS ARE HERE AND WELL
		MARKED & LEGIBLE. THEY ARE (CEDAR 12" N 8E 13 1/2 LKS)
		AND A (W. PINE 12" S 19E 25 1/4 LKS). I SET A NEW 6" CEDAR
		POST AND MADE N.BTS IN MARCH 1948. THEY ARE A
		(WHITE PINE 16" S 74 W 42) AND (WHITE PINE 14" S 75 E 25)
		ALSO (A CEDAR 8" N 2°E 27)
		FROM C 1/4 COR I RUN N 88°-30' E ON TRIAL LINE.
3	00	ENTER SPRUCE & MUSKEG SWAMP. C-NW & SE
10	00	IN JUNCTION OF SWAMP LOG ROADS.
11	00	A LOG ROAD TO HIGHLAND - C. NE.
11	70	LEAVE SWAMP FOR SOUTH POINT OF RIDGE.
13	70	OVER RIDGE & ENTER SWAMP.
14	60	A LOG ROAD C-NE & SW.
16	00	LEAVE SWAMP FOR PINE LAND.
29	57	A LOG ROAD - C-NE & SW.
38	30	INTERSECT MY RANDOM LINE BET. SEC. 1 AND 2
		AT A POINT 34.12 CHS. SOUTH OF COR ON TOWN LINE.
40	14	INTERSECT TRUE LINE 50 LKS. SOUTH OF ORIG. 1/4 COR.
		.50 ÷ 40.14 = .0125 DEP. PER CHAIN.
		.0125 = 0°-43' DEFL. Δ
		N 88°-30' E - 0°-43' = N 87°-47' E TRUE LINE.
EC 1/16		I SET A 4" CEDAR POST FOR EC 1/16 COR. 25 LKS
		NORTH OF 20.07 CHS EQUIDISTANT MEASURE.
		AND MARKED BTS VIZ: {W. PINE 10" N 35 W 42 1/2
		{W. PINE 18" S 33 W 51
		H.C. LAWRENCE & S.P. MARMES - OCT. 6 - 1954.
		EAST & WEST 1/4 LINE OF NE 1/4.
		THE NC 1/16 COR. WAS SET BY B.F. DORR IN 1896.
		FOUND STUMP OF HIS MAPLE 12" S 36 1/2 E 10 1/2 LKS. MARKS. O.K.
		SET NEW 6" CEDAR POST & MADE N.B.TS VIZ.
		HEMLOCK 7" S 28 E 32
		DEAD CEDAR 10" S 10 E 37
		I RUN N 88°-20' E MAG. ON RANDOM LINE
1	15	OLD WOODS ROAD C-NE & SW.
15	54	℄ OF NEW CONSOLIDATED ROAD
38	42	INTERSECT MY RANDOM BET 1 & 2 AT 15.13 chs. South
39	16	THE N 1/16 COR IS 22 LKS. South.
		(.22 ÷ 39.16 = .0056) .0056 = 0°-18' DEFL. Δ
		N 88°-20' + 0°-18' = N 88°-38' E TRUE LINE.
		SET A 6" CEDAR POST FOR TEMP. NE 1/16 COR. ON THE
		BASIS OF EQUIDISTANT MEASURE AT 19.58 CHS AND 11 LKS
		SOUTH OF RANDOM. {HEMLOCK 12" N 72 1/2 W 41 LKS.
		{MAPLE 17" S 56 W 37 LKS.
		DID NOT RUN N & S 1/4 LINE OF NE 1/4 AS WE OWN NE 1/4.

00017

12-28-04

12-28-04