

SEC. 3 T. 38 North R. 7 East

Chains	Chains
B.F. Dorr - 11/27/1893 N _{1/4} P. E (4) 20.02 var N 11 v. 3° 40' Lloyds 1/8 S. 3 3/4 13.91 var W. 9 v 3° 35' " 1/16 W (3° 20') 19.75 to Lake var N. 8. Nov. 27, 1893 B. SE Cor. N (4) 40.00 Hit it v 3° 35' -21' 40.04 E _{1/4} P.W. (4) 79.25 var S. 49 v 3 3/4° do aspen 7S 58W 37 $\frac{1}{2}$ +36' 40.66 + 19.67	D.H. Vaughan July 26, 1916 Ran westerly line of Village plat. Located iron mon. at SW cor. of plat and iron rod for 1/16 P. in cent. of NE _{1/4} and made Bearings (W. Pine stp. 18 S $\frac{1}{2}$ E 39 (" " 18 S 88 $\frac{1}{4}$ W 53 W. from 1/16 P. in NE _{1/4} W 22' 1986 fell 15 N. of M.C. set by Dorr Corrected line E and survey School ground as per deed of Alice Choate. Think deed will be changed and new ground surveyed farther W.
S _{1/4} P.N. 74.03 var E. 78 v 4° Cen NE _{1/4} Pine 18. S. 75 $\frac{1}{2}$ W. 31 20.11 E 1/8 on S. line N (3 3/4) 40.23 $\frac{1}{2}$ var E 13. v 4° S 1/8 on E line Pine 24S. 42 W. 10 $\frac{1}{4}$ do do W (4) 19.70 var S 1. lk 1/8 bet E _{1/4} Norway 11. N 51 W. 15 $\frac{1}{2}$ Cen SE _{1/4} Norway 19 S. 45 E 3 3/4 +35' 19.70	H.C. Hall Identified org. M.C.'s #52 & 54 on NL Sec. 3, 38-7 Orig. North $\frac{1}{4}$ S. 3-38-7 " set temp. post by record from stumps of both BT's New (Y pine 11" S 68 E 1.847 = 121.9' 0°var(W birch 8" S 31 E 1.704 = 112.5' This cor. falls in contemplated fill of Hwy 47 Store monument for this corner in Lbr. office pending road constr.
1/8 bet E _{1/4} - N. (4 $\frac{1}{2}$) 33.44 var E 32 v 4° N _{1/4} P. E. (3 3/4) 39.96 var N. 21 4 $\frac{1}{4}$ ° 19.67	Ivan Hassler - North between 4 & 3 7.50 intersect road NW-SE 24.00 enter bog 35.00 leave bog 40.00 $\frac{1}{4}$ Section corner old squared tree 42.00 intersect East bay of Tomahawk Lake over lake 43.00 48.50 intersect Tomahawk Lake old wooden post for M.C. 74.00 Section corner in lake
E _{1/4} P.N. (4° 50') 33.44 var E 1 $\frac{1}{2}$ NE Cor Pine 30 N 43 E 26 $\frac{1}{2}$ Ogl. N 1/8 on E line Pine 18 N. 74 $\frac{1}{2}$ E 29 3/4 do do W (3 $\frac{1}{2}$) 40.00 var N. 12 (20 55') 1/8 bet N. 1 $\frac{1}{2}$ Norway 22 S. 82 E. 24 E 1/8 on N line Pine 16 N. 20 E. 38	(1) NY SE 1/4 PW 22" - S 50° E - 13.8 ft (July 1917) (Jes May 1967)
D.H. Vaughan Aug 16 & 22, 1917 Began at N 1/8 P. on E line set by Dorr (W. Pine stp 16 N 20 E 38) D.H. Vaughan Sept. 28, 1915 N.E. Cor. found an iron monument set W. Allen and myself in May, 1893 when orig. trees were standing. Found a stp marked by Dorr. Runs Var 3° 30'E 1390 fell 6 lks E of 1/8 P. set by Dorr His bearing is W. Pine stp 18 N 74 $\frac{1}{2}$ E 29 3/4 Corrected N. to Cor. W. from N 1/8 P on E. line var 3° 30'E 354 to E line of Village plat of Tomahawk Lake. Angle at this point from 1/8 line plot from S. to W. is 55° 55' angle from 1/8 line to plat is 124° 05'. Course of E line of plat is N. 34 W. and is 958 ch to NE Cor. of plat. Thence S 56° W 442 ch to E line of street. W. from N.E. Cor. var 4° E 4007 fell 59 $\frac{1}{2}$ S. of $\frac{1}{4}$ P. orig. stps ok Set E 1/8 P. on N. line. W. Pine stp 20 N 75 W. 37 $\frac{1}{2}$ South from E 1/8 P. on N. line var 3° 30'E 368 to a point 150 feet northeasterly from the center of C&NW R.R. track which is northeasterly line of their right of way. Also set stakes about 100 feet apart on northeasterly line of said right of way southeasterly to the northerly line of said plat of the Village Tomahawk Lake. Set an iron monument at N 1/8 P. on E line and at E 1/8 P. on N. line. Also at a point where S. line of the NENE intersects village plat. And where W line intersects right of way. Finish in the rain Sept. 30, 1915.	(2) NY SE 1/4 - 2" BC I.P. by Lello in 1947. B6 Br PW 20" - N 82° E - 32.5 ft; Vaughan PW (ab) 28" N 75° W - 37 $\frac{1}{2}$ ft (Jes May 1967)

RETRACEMENT SURVEYS

Forest American Legion State Forest

