

RECEIVED & FILED #.....
 Oneida County Surveyor's Office
 Date OCT 17 1991
 By [Signature]
 CCS #.....

PARCEL -1-

A parcel of land in part of Government Lot 3 and in part of the NW 1/4 of the SW 1/4, Section 1, Township 38 North, Range 6 East, Hazelhurst Township, Oneida County, Wisconsin, being "PARCEL -1-" shown on Map No. 91-78 by Wilderness Surveying, Inc. dated July 29th, 1991, more particularly described as follows:

Commencing at the West Quarter Corner of said Section 1, marked by an iron pipe; thence North 89 degrees 11 minutes 20 seconds East for a distance of 94.95 feet along the north line of the NW 1/4 of the SW 1/4 to the place of beginning, marked by an iron pipe on the easterly right of way line of Sylvan Shore Drive


Thence continuing North 89 degrees 11 minutes 20 seconds East for a distance of 1234.76 feet to the northeast corner of said NW 1/4 of the SW 1/4, being the Center-West 1/16 Corner marked by an iron pipe, thence North 00 degrees 59 minutes 19 seconds West for a distance of 856.73 feet along the west line of Government Lot 3 to the Meander Corner, marked by an iron pipe near the southerly shore of Tomahawk Lake, thence meandering along the lake South 60 degrees 52 minutes 02 seconds East for a distance of 416.76 feet to the westerly line of the "OUTLOT" parcel as previously surveyed by North Country Surveyors, Inc., thence South 01 degrees 06 minutes 52 seconds East for a distance of 1404.76 feet along the westerly line of said "OUTLOT" parcel to an iron pipe on the northerly right of way line of Sylvan Shore Drive, thence North 59 degrees 23 minutes 14 seconds West for a distance of 85.68 feet along said northerly right of way line to an iron pipe, thence continuing along said right of way line, along a curve to the right, having a radius of 1593.55 feet and an arc length of 312.45 feet, being subtended by a chord of North 53 degrees 44 minutes 05 seconds West for a distance of 311.94 feet to an iron pipe, thence continuing along said right of way line North 49 degrees 04 minutes 56 seconds West for a distance of 372.01 feet to an iron pipe, thence continuing along said right of way line, along a curve to the left, having a radius of 217.09 feet and an arc length of 307.46 feet, being subtended by a chord of North 88 degrees 39 minutes 25 seconds West for a distance of 292.40 feet to an iron pipe, thence continuing along said right of way line South 50 degrees 46 minutes 07 seconds West for a distance of 68.48 feet to an iron pipe, thence continuing along said right of way line, along a curve to the right, having a radius of 189.52 feet and an arc length of 168.71 feet, being subtended by a chord of South 76 degrees 16 minutes 15 seconds West for a distance of 163.20 feet to an iron pipe, thence continuing along said right of way line North 78 degrees 13 minutes 34 seconds West for a distance of 144.58 feet to an iron pipe, thence continuing along said right of way line, along a curve to the right, having a radius of 385.39 feet and an arc length of 162.61 feet, being subtended by a chord of North 66 degrees 08 minutes 21 seconds West for a distance of 161.40 feet to an iron pipe, thence continuing along said right of way line North 54 degrees 03 minutes 07 seconds West for a distance of 204.72 feet to an iron pipe, thence continuing along said right of way line, along a curve to the right, having a radius of 146.20 feet and an arc length of 136.64 feet, being subtended by a chord of North 27 degrees 16 minutes 44 seconds West for a distance of 131.72 feet to the place of beginning

The above lateral lot lines extend to the lake, including all riparian rights thereto

Together with and subject to covenants, easements, and restrictions of record.

Said property contains 19.53 acres more or less

Bearing base assumed, referenced to the north line of the NW 1/4 of the SW 1/4 bearing N89°11'20"E



LEGEND

- = 3/4" dia. iron pipe found in place
 - ⊗ = 3/4" dia. iron rod found in place
 - ⊕ = 1 1/4" dia. iron pipe found in place
 - ⊙ = 1 1/2" dia. iron pipe found in place
 - = 2" dia. iron pipe found in place
 - = Iron pipe set, 1" dia. x 24" long
- Other corner monuments are as noted

PLAT OF SYLVAN ESTATES

1" dia. iron pipe found in place
 See U.S. Public Land Survey Map Record for reference ties


Part of
 GOV'T. LOT 3
 and part of the
 NW 1/4 of the SW 1/4
 SECTION 1, T38N, R6E

Hazelhurst Township
 Oneida County, Wisconsin

SURVEYOR'S CERTIFICATE

I, James D. Rein, Registered Land Surveyor No. S-1234, hereby certify that I have surveyed the property shown hereon, that this map represents an accurate survey of said property to the best of my knowledge and belief, that I have performed this survey by order of Erich Schwenker, and that I have complied with the requirements of Wisconsin Administrative Code A-E 7.

WILDERNESS
 SURVEYING,
 INC.



[Signature]
 Registered Land Surveyor S-1234
 dated this 29th day of July, 1991

CURVE DATA TABLE

CURVE	RADIUS	LENGTH	DELTA	CHORD	CH BEARING
A - B	1583.55'	312.45'	11°18'18"	311.94'	N53°44'05"W
C - D	217.09'	307.46'	81°08'57"	282.40'	N88°39'25"W
E - F	189.52'	168.71'	51°00'19"	163.20'	S76°16'16"W
G - H	385.39'	162.61'	24°10'27"	161.40'	N66°08'21"W
I - J	146.20'	136.64'	53°32'47"	131.72'	N27°16'44"W

PARCEL -1-
 ±19.53 Acres

PARCEL -7-
 SEE OUR MAP No. 90-154

VOL. 260 DEEDS, PAGE 288
 VOL. 260 L.C., PAGE 316
 VOL. 283 L.C., PAGE 519
 VOL. 277 DEEDS, PAGE 263