

L 2518A

L 2518A

A. S. Burnett, C. E.

CERTIFIED MEMBER A. A. E.

DESIGNS, VALUATION AND SUPERVISION

Wausau, Wis.,

October 19" 1923

Notes of Re-Survey of the Town Line between Towns 35 & 36 North of Range 4 East.

Cor. to 3-4-33-34 identified by Orig. B.T. and wooden stake.

Orig. B.T.- W.Pine 24", N.38 E., 48 lks.

New B.T.- W.Pine Stp. 16" N.16 15 W. 21 lks.

From above Cor., E., v. 3 00 E.,

79.72 Chs had fallen 79 lks S. of a point obtained as follows,-  
Tore up planks in an old bridge over creek in the road running to the South, and found a notch in an old Pine backlog. This notch was said by old residents to mark the place where the Orig. stake stood. This point conforms to the road lines to the East, West, North and South as well as to the loop in the creek, mentioned in the Govt. field Notes; I, there-for accepted this as the point for the Cor. to Secs. 2-3-34&35, but could not set the iron monument at this point for fear that high water and ice might wash it away together with the little bridge. Consequently I set monument 19 1/2 links directly East of this point and marked bearings to the point where the monument stands,-

W.Pine Stp. 36", N.37 W. 1.55 Chs.

S.Elm (croched at stp.), S. 41 E. 1.61 Chs.

Corrected V. 3 24 E.

Set 1/4 Cor. on the North side of Sec. 3 at equi distance, but not in line, account of evidence of one Stolle ( an old resident) and Clayton Vaughan, (a surveyor of Oneida County). The distance each way to the Sec Corners is 39.86 Chs., and corner is near middle of E. and W. highway. Marked new bearings,-

North End of East wing wall of culvert over road running S.  
S. 38 E., 41 1/2 links.

North End of West wing wall, same culvert,-  
S. 38 W. 44 1/2 links.

Birch stub 36", N. 13 W. 1.47 1/2 Chs.

MAP #	L 2518A
DATE FILED	JUN 23 2008
BY	JAB
DESCRIPTION FILED	
ONEIDA CO. SURVEYOR'S OFFICE	

L 2518A

L 2518A

L 2518B

L 2518B

H. S. Burnett, C. E.

CERTIFIED MEMBER A. A. E.

DESIGNS, VALUATION AND SUPERVISION

From Cor to 2-3-34 & 35, E., V. 3 00 E.
No evidence of 1/4 Cor., ran on. Cor. of 1-2-35-36
79.55 1/2 Chs., found stake offsetted 37 1/2 links North for read
purposes. Set back into line and set monument, near middle of
E. & W. highway, and on or near the center line of N. & S.
highway. Nothing to mark for witnesses.

Went back and set 1/4 Cor. on line and at equi-distance or 39.773/4
chains each way. Marked one bearing,-
Tel. pole 12", S. 43 W. 44 1/2 lks.
Corrected V. 3 00 E.

From Cor. of 1-2-35-36, E., V. 4 45 E.
79.81 Chs., found a scribed stake offsetted 40 links South.
Set monument accordingly, which comes near the middle of the
E. & W. highway and then I ran to the South to check my
position. nothing to mark as witnesses, for Cor. to Ts 35 & 36 N.
Ranges 4 & 5 East.

Later went back and set 1/4 Cor on the North side of Sec 1 at
equi-distance or 39.90 1/2 Chs. each way and on line.
Nothing here to mark as witnesses.

From Cor of 3-4-33-34, W., V. 4 20 E.
39.64 Chs., found bearings established by D.H.Vaughan for 1/4
Cor on the North side of Sec. 4, viz.,
W. Pine Stp. 36", North 57 links
Tel. Pole S. 4 E. 35 1/4 lks.
Dug and found 2"x2"x 18" iron pin.
Set new monument in its place . nothing new to mark.

From above 1/4 Cor., W., V. 4 15 E.
39.99 Chs., found bearings all gone. Iron pin 2"x2"x 18" in
the intersection of the highways. Set monument in its place
and marked new bearings for the Cor, to 4-5-32-33
East face of North wing wall of culvert over E.& W. road
N. 86 10 W. 142 1/4 links
N.W. corner of foundation wall under main building of town
hall,-
S. 27 35 E. 1.27 Chs.

MAP # L 2518B
DATE FILED JUN 23 2008
BY
DESCRIPTION FILED
ONEIDA CO. SURVEYOR'S OFFICE

L 2518B

L 2518B

H. S. Burnett, C. E.

CERTIFIED MEMBER A. A. E.

DESIGNS, VALUATION AND SUPERVISION

From Sec. Cor of 4-5-32-33, W., V. 4 20 E.  
 39.89 Chs., found Stp. of Orig. Govt B.T., viz.,  
 Birch 10", S. 5 W. 26 lks ( Sworn to by Kavanaugh  
 and Isaacson)  
 Set monument and took bearings,- for 1/4 Cor on N. side of Sec.5  
 W.Pine Stp. 28", N.44 E. 50 1/2 links  
 Tel. Pole S. 4 E. 24 lks.  
 Pine Stp. 30", N. 25 W. 95 1/2 lks

79.95 Chs found pine stp. marked by Dorr for bearing to Sec.  
 Cor of 5-6-31 & 32, viz.,  
 Pine Stp. 24", N. 72 45 W. 1.44 Chs.  
 Set monument and took bearings to,-  
 N.W. Cor. of bridge over S. road  
 S. 45 W. 33lks  
 N.E. Cor of bridge over S. road,-  
 S. 45 15 E. 34 lks

From Cor of Secs 5-6-31 & 32, W., V. 4 45 E.  
 39.84 Chs., found wooden stake set by D.H.Vaughan for 1/4  
 Cor. on the N. side of Sec 6,  
 Set monument in its place and took bearings to,-  
 Hem. 12", S.47 W. 1.111/2 Chs.

80.84 Chs., Township Corner of Towns 35 & 36 N. , Ranges  
 3 & 4 E., found one Orig Govt B.T., viz.,  
 Birch 12", S. 20 E. 19 lks.  
 Set monument by Orig. B.T., and took one new bearing,-  
 S. Elm 36", N.-- W. 91 1/2 lks.

Re-Survey of a part of the town of Somo, began  
 Sept. 12" 1923 and finished Oct. 4" 1923.  
 ( The two North tiers of Sections)

Respectfully Submitted

*D.S. Burnett*  
 D. S. Burnett,-  
 412 Washington St.  
 Wausau, Wis..

MAP # **L 2518c**  
 DATE FILED **JUN. 23. 2008**  
 BY.....  
 DESCRIPTION FILED.....  
 ONEIDA CO. SURVEYOR'S OFFICE