U.S. PUBLIC LAND SURVEY MONUMENT RECORD


NOTE: This form is intended and designed to fulfill all requirements of Wisconsin Administrative Code, Chapter A-E 7 .08 U.S. Public Land Survey Monument Record (3)(a)(b)(c)(d)(e)(f) (g)(h)(i). An additional sheet may be added if necessary to conform with said requirements.

(a)Corner location: Township 38 North

Range_7_East

Tawa of Lake Tomahawk

County of _________



(b)(f)(g)(h) Description of monument found at this corner and if it was accepted, state all evidence (material, testimonial, occupation, plats, records, other monuments) used as a basis for accepting. If not accepted or if nothing was found, state evidence used as a basis for establishing location. If reestablished through lost corner proportionate methods, indicate all monuments, distances and directions used to establish. Indicate type of monument found or set and sign post.

RIPCO - Set Witness Corner 33.00' West of N 1/16 Corner.

May 29, 1996 — Milo E. Stefan found RIPCO'S W.C. and a 16" Red Oak BT, N41°E, 76.51' with face overgrown. He set a railroad spike in blacktop and made two new BT's. This certificate is to perpetuate this W.C. by RIPCO. Its position should be tested prior to its use.

June 27, 2008 — Due to road construction Nicolet Surveyors, Inc. was contacted by the Oneida County Land Information Office to preserve the location of this survey marker. Jonathan W. Dulin found a railroad spike 10 feet East of the centerline of Fox Road along with 3 bearing trees and a 1" Iron pipe with 2" square brass plate (RIPCO W.C.). We witnessed the corner as shown below.

(c)(d)(e) Plan view of corner with ties to at least 4 witness monuments. If in disagreement with previously established corner, show the distances between the two corners and also indicate the ties to the disputed corner.

N90W

33.07



Scale: 1" =50'

Notes:


1. All bearings taken with a compass and distances measured with a tape.

2. Corner lies 10' East of centerline.

RIPCO W.C.

Plastic sign post

lies 1' West



18" Red Oak
Found blazed with a
BT sign and Nail in
side of tree.

15" Red Pine
Found blazed with a
BT sign and Nail in
side of tree.

Legend

Set 3/4" x 24" Iron Rebar
Weighing 1.50 lbs/lin ft.
W/Yellow Ref Cap

Found 1" Iron Pipe with 2"
Square Brass Plate (RIPCO W.C.)

Found Railroad Spike

Iron rebar set 1'
North of tree and
lies S42'E, 46.70'
from corner.

14" Red Pine
Found blazed with a
BT sign and Nail in

side of tree.

(i) I, Jonathan W. Dulin, certify that the corner location on this record was determined by me under my direction and control and that this U.S. Public Land Survey Monument is correct and complete to the best of the best o

Signature

DULIN
S-2754
RHINELANTER
WISCONSIN
WISCONSIN
WISCONSIN

Daté

3807353000