

U.S. PUBLIC LAND SURVEY MONUMENT RECORD


Note: This form is intended and designed to fulfill all requirements of the Wisconsin Administrative Code, Chapter A-E 7.08 U.S. Public Land Monument Record (3)(a)(b)(c)(d)(e)(f)(g)(h)(i). An additional sheet may be added if necessary to conform with said requirements.

(a) CORNER LOCATION:

South 1/4 corner of Section 25
 Township 37 North
 Range 6 East
 Town of Cassian
 County of Oneida

O. C. COORDINATES

North: 172631.6977
 East: 194563.7431
 Control Station: O. C. 271
 Latitude: 45° 38' 41.65081" N
 Longitude: 89° 39' 36.71756" W
 Datum: NAD - 83 - (91)
 Method: Direct RTK - GPS



SECTION 25

(b) HISTORY OF ORIGINAL CORNER ESTABLISHMENT


Original Surveyor: _____ Original B.T.'S _____
 Date of Survey: Commenced _____
 Completed _____

(f)(g)(h) DESCRIPTION OF MONUMENT FOUND AT THIS CORNER AND IF IT WAS ACCEPTED, STATE ALL EVIDENCE (MATERIAL, TESTIMONIAL, OCCUPATIONAL, PLATS, RECORDS, OTHER MONUMENTS) USED AS A BASIS FOR ESTABLISHING LOCATION. IF NOT ACCEPTED OF IF NOTHING WAS FOUND, STATE EVIDENCE USED AS BASIS FOR ESTABLISHING LOCATION. IF REESTABLISHED THROUGH LOST CORNER PROPORTIONATE METHODS, INDICATE ALL MONUMENTS, DISTANCES AND DIRECTIONS USED TO ESTABLISH. INDICATE TYPE OF MONUMENT AND SIGN POST FOUND OR SET.

I find the corner monument as described in that U.S. Public Land Survey Monument Record filed by Lester J. Schmit, RLS No. 1192, dated the 10th of October, 1991. This monument record has been prepared to file the Oneida County coordinates on this corner, which I have measured, based on Direct RTK - GPS methods.

(c)(d)(e) PLAN VIEW OF CORNER WITH TIES TO AT LEAST 4 WITNESS MONUMENTS. IF IN DISAGREEMENT WITH PREVIOUSLY ESTABLISHED CORNER, SHOW THE DISTANCE BETWEEN THE TWO CORNERS AND ALSO INDICATE THE TIES TO THE DISPUTED CORNER.

MAP # L 2585 DATE FILED 04/22/2009 BY JAB DESCRIPTION FILED ONEIDA CO. SURVEYOR'S OFFICE



Recovered capped 2.4" o.d. aluminum monument flush. Corner post for fences running North - South - West is 1 foot west of the monument. A white poly stake bears North 0.8 feet of the corner monument

(i) I, JAMES D. REIN, REGISTERED LAND SURVEYOR NO. S-1234 HEREBY CERTIFY THAT THE CORNER LOCATION ON THIS RECORD WAS DETERMINED BY ME OR UNDER MY DIRECTION AND CONTROL AND THAT THIS U.S. PUBLIC LAND SURVEY MONUMENT RECORD IS CORRECT AND COMPLETE TO THE BEST OF MY KNOWLEDGE AND BELIEF

[Handwritten Signature]
 SIGNATURE

4/08/09
 DATE



L 2585

INDEX NO. L 2585

L 2585

L 2585

L 2585