29	
Œ	
0	
~7	

March Date

		D CORNER P			v		
It is the purpose of disturbed, removed					onument th	at may be	
County:	City, Village, Tow		Section:	Town:	Range:		·
ONEIDA	TOWN OF STE		14	T37N	R10E	· 3	
Describe what was fou	and its location and or	igin If known dose	oribo if the menun	most found is a 1/1/	2 Annasia		
comer or other subdivi						ate location 1/16 EAST	
survey map or plat etc					Occion <u>B</u>	7710 2222	
02/15/2012 T	odd Loftus found ma	ig. nail and witness	ed as shown belo	ow.			·
Mag. nail as n	oted on Oneida County Pla	t of Survey B7345			. 1		
		1					
. 00	0.7						
MAP # L 2 9 DATE FILED.	0 4				.		
	25-13		:				
DATE FILED. 7.5	CASE COLORS OF CASE		•				
BY							
U PROPERTON ET	TITO						
DESCRIPTION FI							
ONEIDA CO. SUE	RVEYOR'S OFFICE		•				
		_			2710	14100	30
						*	
				a minimum of four			
nonuments of concret	e, natural stone, meta	II, live bearing trees	or equivalent ma				
nonuments of concret	e, natural stone, meta		or equivalent ma			NORTH	out using
monuments of concret GPS. Indicate what w	e, natural stone, meta	al, live bearing trees E 1/4 d	or equivalent ma			NORTH	out using
monuments of concret GPS. Indicate what w	e, natural stone, meta	al, live bearing trees  E 1/4 c  Found 0	or equivalent ma		atum & coordin	NORTH	out using
monuments of concret GPS Indicate what w LEGEND  -I-found I" iron pipe	e, natural stone, meta	al, live bearing trees  E 1/4 c  Found 0	or equivalent ma			NORTH	out using
monuments of concret GPS Indicate what w LEGEND  -I-found I" iron pipe	e, natural stone, meta	al, live bearing trees  E 1/4 c  Found 0	or equivalent ma		atum & coordin	NORTH	out using
monuments of concret GPS Indicate what w LEGEND -1- found 1" iron pipe -2- set spike in 18" Oak	e, natural stone, meta	E 1/4 C	or equivalent ma		atum & coordin	NORTH NO	out using
monuments of concret GPS Indicate what w LEGEND  -1-found I" iron pipe  -2- set spike in 18" Oak  -3- set I" iron pipe	e, natural stone, meta as reset.	al, live bearing trees  E 1/4 c  Found 0	or equivalent ma	aterial or indicate da	2 02.55 2 02.55 2 02.55 2 2 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	NORTH	out using
monuments of concret GPS. Indicate what w LEGEND	e, natural stone, meta as reset.	II, live bearing trees  E 1/4 6  Found 0	or equivalent ma	aterial or indicate da	2 2 3 8 8 8 8 8 8 8 8 8 8 8 8 8	NORTH NO	
monuments of concret GPS Indicate what we LEGEND  -1- found I" iron pipe  -2- set spike in 18" Oak  -3- set I" iron pipe  4- set spike west side 24" In	e, natural stone, meta as reset.	II, live bearing trees  E 1/4 6  Found 0	or equivalent ma	aterial or indicate da	2 2 3 8 8 8 8 8 8 8 8 8 8 8 8 8	NORTH NO	out using
monuments of concret GPS. Indicate what we LEGEND  -1-found I" iron pipe  -2- set spike in 18" Oak  -3- set I" iron pipe  4- set spike west side 24" In	e, natural stone, meta as reset.	I, live bearing trees  E 1/4 6  Found 0	or equivalent ma	aterial or indicate da	2 2 3 8 8 8 8 8 8 8 8 8 8 8 8 8	NORTH NO	out using
monuments of concret GPS. Indicate what we LEGEND  -1-found I" iron pipe  -2- set spike in 18" Oak  -3- set I" iron pipe  4- set spike west side 24" In	e, natural stone, meta as reset.	E 1/4 C Found C	or equivalent ma	aterial or indicate da	2 2 3 8 8 8 8 8 8 8 8 8 8 8 8 8	NORTH NO	out using
nonuments of concret GPS. Indicate what we LEGEND  -1-found I" iron pipe  -2- set spike in 18" Oak  -3- set I" iron pipe  4- set spike west side 24" In	e, natural stone, meta as reset.	1. live bearing trees  E 1/40. Found 0  St-46.19"W  St-46.19"W	or equivalent ma	aterial or indicate da	2 2 3 8 8 8 8 8 8 8 8 8 8 8 8 8	NORTH NO	out using
nonuments of concret GPS. Indicate what we LEGEND  -1-found I" iron pipe  -2- set spike in 18" Oak  -3- set I" iron pipe  4- set spike west side 24" In the set spike west spike wes	e, natural stone, meta as reset.	It, live bearing trees  E 1/4 C  Found C  3.61.9.M. M.61.9.E  SE. Sexisting of existing of the sexisting of	or equivalent ma	N87°59	SPRING PAGE 5.20 . 25.	NORTH NO	out using
nonuments of concret GPS Indicate what we LEGEND  -1- found I" iron pipe  -2- set spike in 18" Oak  -3- set I" iron pipe  4- set spike west side 24" In the set spike west spike w	e, natural stone, meta as reset.	Found Co. 1207.73.  1. live bearing trees  E 1/4 Co. Found Co. 1207.73.  No. 10.19.13.  PROFESSION	or equivalent ma	N87°59	253"W 5 587% 24	NORTH NO	tusing
The monuments of concret GPS Indicate what we LEGEND  -1-found I" iron pipe  -2- set spike in 18" Oak  -3- set I" iron pipe  4- set spike west side 24" In the set spike west sp	e, natural stone, meta as reset.	E 1/4 0 Found Co. 1207.13.  E 1/4 0 Found Co. 1207.13.  SE. 1.01.01.01.01.01.01.01.01.01.01.01.01.01	or equivalent ma	N87°59  N87°59  24.3  RVEYOR CERT	SERING & coording to the series of the serie	NORTH  NORTH  NO  1  9'53"E  775"  1	ther
The monuments of concret GPS Indicate what we LEGEND  -1-found I" iron pipe  -2- set spike in 18" Oak  -3- set I" iron pipe  4- set spike west side 24" In the set spike west sp	e, natural stone, meta as reset.	E 1/4 0 Found Co. 127.721 SE. SE. Sexisting of PROFESSION. This land corner activity as an act	or equivalent macor. C.C.M.  SEC.COR. CONCRETE MONUMENT AL LAND SUF was referenced of preserving s	RVEYOR CERT I out in advance of	SS875 253"W SS875 2550 3 151CATE: of road construction monuments	NORTH  NORTH  NO  1  9'53"E  775"  1  Truction or of s. This cont	ther ner has
LEGEND  -1- found 1" iron pipe -2- set spike in 18" Oak -3- set 1" iron pipe 4- set spike west side 24" F	e, natural stone, meta as reset.	Found Corner activity as an act not been tested for the state of the s	or equivalent macor. C.C.M.  SEC.COR. CONCRETE MONUMENT WAS REFERENCED of preserving s or its accuracy of	RVEYOR CERT out in advance of during the course	S87°5  24  SFICATE: of road construction monuments of this prese	NORTH  NORTH  NO  1  9'53"E  175"  3  ruction or	ther has
LEGEND  -1- found 1" iron pipe -2- set spike in 18" Oak -3- set 1" iron pipe 4- set spike west side 24" F -5- found Mag. nail	e, natural stone, meta as reset.	E 1/4 0 Found Co. 127.721 SE. SE. Sexisting of PROFESSION. This land corner activity as an act	SEC.COR. CONCRETE MONUMENT  AL LAND SUF was referenced of preserving so or its accuracy of at those using the contract of the	RVEYOR CERT out in advance of during the course	S87°5  24  SFICATE: of road construction monuments of this prese	NORTH  NORTH  NO  1  9'53"E  175"  3  ruction or	ther has s
LEGEND  -1- found 1" iron pipe -2- set spike in 18" Oak -3- set 1" iron pipe 4- set spike west side 24" F -5- found Mag. nail	e, natural stone, meta as reset.  Red Pine	PROFESSION This land corner activity as an act not been tested for recommended the use in a survey of the survey o	SEC.COR. CONCRETE MONUMENT  AL LAND SUF was referenced of preserving s or its accuracy of at those using to or other use.	RVEYOR CERT Out in advance of during the course the corner position	FICATE: of this presen evaluates a	NORTH  NO	ther ner has s it prior t
LEGEND  -1-found I" iron pipe -2- set spike in 18" Oak -3- set I" iron pipe 4- set spike west side 24" If 5-found Mag. nail  Seal:  TODD LOFTU S-1523	e, natural stone, meta as reset.	PROFESSION This land corner activity as an act not been tested for recommended the use in a survey of the property of the prop	SEC.COR. CONCRETE MONUMENT  AL LAND SUF was referenced of preserving s or its accuracy of at those using to or other use.  that I am a dul	RVEYOR CERT Out in advance of during the course the corner position.	FICATE: of road construction evaluates a sessional Lar	NORTH  NO	ther her has s it prior the
TODD LOFTU	e, natural stone, meta as reset.	PROFESSION This land corner activity as an act not been tested for recommended the use in a survey of the reby certify State of Wiscon.	SEC.COR.  CONCINCTON SECONDA  CONCINCTON SECON	RVEYOR CERT Out in advance of during the course the corner position of this Solution of this Solution and the Solution of this Solution of thi	TFICATE: of road construction evaluates a essional Larurvey or Lar	NORTH  NORTH  NO  1  9'53"E  7.75"  3  Truction or	ther ner has s it prior the
LEGEND  -1-found I" iron pipe -2- set spike in 18" Oak -3- set I" iron pipe 4- set spike west side 24" If 5-found Mag. nail  Seal:  TODD LOFTU S-1523 RHINELAN	e, natural stone, meta as reset.	PROFESSION This land corner activity as an act not been tested for recommended the use in a survey of the property of the prop	SEC.COR.  CONCINCTON C	RVEYOR CERT I out in advance of during the course the corner position of this So y direct supervises	TFICATE: of road construction monuments of this present evaluates a sessional Larurvey or Larurvey or Larurvey or Larurvey and construction an	NORTH  NORTH  NORTH  NO  1  9'53"E  7.75"  3  Truction or o  s. This contervation. It i and verifies  and verifies  and Corner on  ntrol and the	ther ner has s it prior the was nat the

Signature