

"A"

4-679

TRANSCRIPT

FIELD NOTES

OF THE SURVEY OF THE

RESURVEY OF THE

SUBDIVISIONAL AND MEANDER LINES

AND AN

EXTENSION SURVEY IN SECTION 33,

TOWNSHIP 37 NORTH, RANGE 8 EAST,

Of the FOURTH PRINCIPAL Meridian,

In the State of WISCONSIN.

EXECUTED BY

EARL G. HARRINGTON, U. S. CADASTRAL ENGINEER,

Supplemental

In the capacity of U. S. Surveyor, under Special Instructions dated August 30, 1927,

Technical Assistant to Supervisor of Surveys issued by the United States Surveyor General to govern surveys included in Group

No. 14, which were approved by the Commissioner of the General Land

Office, Sept. 7, 1927, and Assignment Instructions dated Sept. 9, 1927.

Survey commenced September 14, 1927.

Survey completed September 26, 1927.

6366
37-82

RECEIVED & FILED #	L357
Oneida County Surveyor's Office	
Date	FEB. 14 1988
By	M.H.
OCS-Area #	

Resurvey of the Subdivisional and Meander Lines and
Extension Survey in Section 33, T. 37 N., R. 8 E.,
Fourth Principal Meridian, Wisconsin.

Chains

Survey commenced Sept. 14, 1927, and executed with Buff
Solar Transit No. 16730, fully equipped and conforming
to the standard instrumental specifications adopted
by the General Land Office. See field notes of the extension survey executed in
Sec. 5, T. 38 N., R. 7 E., 4th Principal Meridian,
Wisconsin, for the test of the solar apparatus.
During the progress of this work the solar apparatus
was frequently tested upon meridian determined in
the examination in the fall of 1926.

Reestablishment of the South Boundary of Section 33, as
surveyed by Alfred Millard in the year 1860.

At the true point for the corner of secs. 3, 4, 33, and
34.

Set an iron post, 3 ft. long, 2 ins. diam., 42 ins. in
the ground, for cor. of secs. 3, 4, 33, and 34, with
brass cap mkd.

T 37 N	R 8 E
S 33	S 34
S 4	S 3
T 36 N	
1927	

The corner falls in the center of an east and west road
and the iron post is therefore, set 6 ins. below the
surface of the ground.

No trace of the original bearing tree can be found at
this time but from all available evidence it appears
that the original trees were destroyed when the road
was built and that new bearing trees were taken. I
am only able to find one tree which has been marked
since the date of the original survey;

A white pine stump, 4 feet high, 12 ins. diam., bears
N. 40° E., 58 lks. dist., mkd. T 37 N R 8 E S 34

B T.

This corner is recognized as the true corner.

Resurvey of the Subdivisional and Meander Lines and
Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

Thence N. 89° 58' W., on a true line, bet. secs. 4 and 33.
Over slightly rolling land, along the center of a road.
40.00 The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, which is a wooden
stake, 4 x 4 x 24 ins. above ground, mkd. $\frac{1}{4}$ S on
north face.

In place of wooden stake

Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in
the ground, surrounded by a small circular mound of
stone, for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33, with
brass cap mkd.

$\frac{1}{4}$ S 33
S 4
1927

No evidence of the original bearing trees can be found
at this time but from all available evidence it
appears that the wooden stake has always been
considered as being at the true point for the corner
and I therefore accept this stake as being the best
evidence of the point for the original corner.

From which

Trees marked since the date of the original survey.

A pine stump, 8 ins. diam., 4 feet high, bears N. 65°
W., 3 lks. dist., mkd. 4.

A pine stump, 14 ins. diam., bears S. 15° E., 48 lks.
dist., mkd. B T.

A white pine, 12 ins. diam., bears N. 8° 15' W., 129
lks. dist., mkd. $\frac{1}{4}$ S B T.

Thence

S. 89° 57' W., continuing bet. secs. 4 and 33, beginning
new measurement, through small poplar timber.

4.20 Enter a marsh, bears N. and S.

5.40 Leave marsh, bears N. and S.

25.00 North end of small lake.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

40.09 The cor. of secs. 4, 5, 32, and 33, which is a wooden stake, 4 x 4 x 36 ins. above ground, with scribe marks on the four faces.

In place of wooden stake.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the cor. of secs. 4, 5, 32, and 33, with brass cap mkd.

T 37 N R 8 E
S 32 | S 33
S 5 | S 4
T 36 N
1927

No evidence of the original bearing trees can be found at this time but from all available information at

appears that the wooden stake has always been

considered at the true point for the corner and, I

therefore accept the stake as being the best

evidence of the point for the original corner.

The cor. is set at the south side of State Highway and no new bearing trees are taken.

A small mound of stone is built around the corner.

Land, gently rolling.

Soil, sandy; 3rd rate.

Timber, second growth poplar, birch and pine.

Undergrowth, poplar and hazel.

Reestablishment of a Portion of the Subdivisional Lines
as surveyed by Wm. E. Daugherty in the year, 1863.

From the cor. of secs. 3, 4, 33, and 34, on the south
boundary of the township, previously described.

N. 1° 21' E., on a true line, bet. secs. 33 and 34.

Over gently rolling land, through timber and brush.

8.50 Enter a cedar and tamarack swamp, bears E. and W.

13.00 Leave swamp, bears E. and W.

14.00 Enter a spruce and tamarack swamp, bears E. and W.

24.00 Leave swamp, bears E. and W.


Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

41.31 The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, which is a wooden stake, 3 x 3 x 30 ins. above ground.

In place of wooden stake.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, with brass cap mkd.



From which

The remains of the original bearing trees

A yellow pine stump, 30 ins. diam., bears S. 38° W., 9 lks. dist., mkd. BT.

A yellow pine stump, 24 ins. diam., bears N. 81° E., 26 lks. dist., scribe marks obliterated.

As the large yellow pine stump will last as long or longer than the small second growth in the vicinity of the corner, no new bearing trees are taken.

Thence

N. 1° 08' W., continuing bet. secs. 33 and 34. Beginning new measurement.

17.50 Enter an open spruce swamp, bears E. and W.

21.00 Leave swamp, bears E. and W.

21.23 Proportionate distance.

Point for the N. 1/16 sec. cor. of secs. 33 and 34. No corner established.

42.46 The corner of secs. 27, 28, 33, and 34, which is an old oak stake, 3 x 3 x 30 ins. above the ground. I am unable to find any direct evidence of the original corner at this point but based upon the fact that this oak stake is properly related to an original meander corner of secs. 28 and 33, which has been identified, and which is approximately 10.00 chs. west, and from information obtained from people who had seen the original corner and bearing trees many years ago in the vicinity of where the oak stake is

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

standing, I accept said oak stake as being at the most probable position for the original corner. Also from information obtained from local surveys and from a blue print showing the location of the Chicago Northwestern Railroad, it appears that the corner of secs. 21, 22, 27, and 28 has been identified but that the distance to said corner from the oak stake marking the position for the corner of secs. 27, 28, 33, and 34 is considerable less than the record distance. If the oak stake is disregarded as being at the most probable position for the corner of secs. 27, 28, 33, and 34, it would be necessary to reestablish the corner by double proportional measurement which would place the corner at least 5.00 chs. south of said oak stake to a point, which would not be properly related to the original meander corner of secs. 28 and 33 and which would not fall in the immediate vicinity of where the original corner had been seen.

A squared wooden stake set in a recent local resurvey, bears S. 73° 09' W., 1.72 chs. dist. This stake marks the position for the cor. of secs. 27, 28, 33, and 34, as determined by this recent resurvey but as there appears to be no evidence of the original trees at this point and as the position does not check with the original meander corner of secs. 28 and 33 to the west, I can see no reason for disregarding the oak stake and accepting this stake as marking the true position for the original corner. The Supplemental Special Instructions dated August 30, 1927, provided that, where corners have been reestablished by methods which do not agree with General Land Office practice and where there is a difference of opinion relative to the correct position for the corners, in cases where there is no Public Land involved adjacent to the corners, my determinations of the true positions for the corners should not be monumented. Therefore, in

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

the case of the corner of secs. 27, 28, 33, and 34,
no iron post is set in place of the oak stake which
appears to me to be the most probable location of the
position of the original corner.

Land, gently rolling.

Soil, sandy; 3rd rate.

Timber, second growth, poplar, and birch.

Undergrowth, hazel and small timber.

Thence

N. 88° 16' W., on a true line, bet. secs. 28 and 33.

Over gently rolling land, through timber and brush.

9.91 To the shore of Flanner Lake, bears NW. and SE. and the
true point for the original meander corner of secs.
28 and 33, which is marked by a piece of iron pipe.

In place of iron pipe,

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for the original meander corner of secs.
28 and 33, with brass cap mkd.

T 37 N
S 28
M C ———
S 33
R 8 E
1927

From which

The remains of the original bearing trees

A yellow pine stump, 18 ins. diam., bears S. 77° E.,
21 lks. dist. Marks obliterated but the old ax
marks are still plain.

A fallen yellow pine, 16 ins. diam., bears N. 44° E.,
8 lks. dist. Old blaze and remains of scribe marks
are still plain.

No new bearing trees are taken as the yellow pine stumps
will last as long as the second growth timber in the
immediate vicinity of the corner.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains	
	Thence
	N. 85° 10' W., continuing bet. secs. 28 and 33, across Flanner Lake. Beginning new measurement.
7.16	Proportional point for original meander corner of secs. 28 and 33, falls in lake.
8.30	To actual shore of point of land, bears NE. and SW. Thence across point of land.
8.61	Proportional point for original meander corner of secs. 28 and 33. No evidence of original corner.
9.21	Proportional distance. Point for the E. 1/16 sec. cor. of secs. 28 and 33. No corner established.
10.05	To actual shore of lake, bears NE. and SW. Thence across lake.
19.80	To shore of point of land, bears N. and S. This point of land is not shown on the plat of the original survey.
21.60	To west shore of point of land, bears NW. and south. Thence across lake.
27.67	Proportional point for 1/4 sec. cor. falls in lake.
32.82	To shore of Flanner Lake, bears NE. and south and the true point for the original meander corner of secs. 28 and 33, which is marked by the remains of an old decayed wooden stake. In place of decayed stake. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for a meander corner of secs. 28 and 33, with brass cap mkd.
	<div style="text-align: center;"> T 37 N S 28 ————— MC S 33 R 8 E 1927 </div>
	From which
	The remains of an original bearing tree. An oak stump, badly decayed, bears N. 45° W., 18 lks. dist. No marks.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

And new bearing trees recently marked.

A white pine, 16 ins. diam., bears N. 64° 15' E., 79
lks. dist., mkd. S 28 M C B T.

A white pine, 16 ins. diam., bears S. 19° 45' W., 75
lks. dist., mkd. S 33 M C B T.

Thence

N. 89° 47' W., continuing on a true line bet. secs. 28
and 33.

Over rolling land, through young poplar timber and brush.
Beginning new measurement.

10.84 To actual shore of Dumb Bell Lake, bears NW. and S. and
true point for the original meander corner of secs.
28 and 33, which is now marked by a 3 inch squared
wooden stake, recently set and marked.

In place of wooden stake.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for the original meander corner of secs.
28 and 33, with brass cap mkd.

T 37 N
S 28
M C
S 33
R 8 E
1927

From which

The remains of the original bearing trees

A white pine stump, 24 ins. diam., bears N. 49° E.,
8 lks. dist., marks obliterated.

A fallen yellow pine, 20 ins. diam., bears S. 44° 30'
E., 25 lks. dist. Scribe marks have been destroyed
but the original blaze is very plain.

And new bearing trees recently marked.

A norway pine, 16 ins. diam., bears S. 22° 30' E., 15
lks. dist., mkd. Orig M C No 42 B T.

A norway pine, 8 ins. diam., bears S. 38° E., 13 lks.
dist., mkd. S 33 M C B T.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains	Thence
	S. $73^{\circ} 32'$ W., continuing on a true line, bet. secs. 28 and 33, across Dumb Bell Lake. Beginning new measurement.
7.23	Proportional distance and point for the original meander corner of secs. 28 and 33, falls in Dumb Bell Lake. No corner reestablished as a witness corner to this point.
11.09	To actual west shore of Dumb Bell Lake, bears N. and S. No corner set at this point.
	Thence over rolling land, through brush.
31.10	True position for the cor. of secs. 28, 29, 32, and 33, reestablished by double proportional measurement bet. the nearest identified original corners to the north, south, east, and west. The original corners used for the reestablishment are: The 1 sec. cor. of secs. 32 and 33. The meander corner of secs. 28 and 33, which according to original record was set 23.64 chs. east of the corner of secs. 28, 29, 32, and 33. The meander corner of secs. 28 and 29, which according to original record was set 33.09 chs. north of the corner of secs. 28, 29, 32, and 33. The meander corner of secs. 29 and 32, which according to original record was set 24.09 chs. west of the corner of secs. 28, 29, 32, and 33. A squared wooden stake set in a recent local resurvey, bears S. $58^{\circ} 05'$ W., 3.93 chs. dist. This stake marks the position for the corner of secs. 28, 29, 32, and 33, as determined by this local resurvey. No evidence of the original corner or bearing trees can be found at this point and it appears that the corner has been reestablished by proportional measurement, but disregarding original meander corners as fixed points for control. This practice is in accord with Wisconsin Court Decisions.

Resurvey of the Subdivisional and Meander Lines and
an Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

The Supplemental Special Instructions dated August 30, 1927, provided, where corners have been reestablished by methods which are not in accord with General Land Office Practice and where there is a difference of opinion relative to the correct position for the corners, that in cases where there is no Public Land involved adjacent to the corners, my determinations of the true positions for the corners should not be monumented. Therefore, no iron post is set to mark the position of the corner of secs. 28, 29, 32, and 33, as determined by double proportional measurement between the nearest identified corners to the north, south, east, and west.

From the true point for the corner of secs. 28, 29, 32, and 33, the point for the original meander corner of secs. 28 and 29, on the south shore of a small lake, bears N. $12^{\circ} 57'$ W., 28.02 chs. dist. This point is well marked by a 4 inch squared wooden stake, 36 ins. above the ground.

From which

The remains of the original bearing trees

A Norway pine stump, 20 ins. diam., bears S. 17° E., 23 lks. dist., mkd. B.T.

A Norway pine, 24 ins. diam., bears S. $2^{\circ} 30'$ W., 25 lks. dist., mkd. T. 37 N R 8 E S 29 M C B T.

No iron post is set at the true point for the corner on account of bed rock which is near the surface and the iron post could not be firmly set. A witness corner to the true point for the corner was not set because it appeared to me that, in a case of this kind where the original bearing trees are standing and facing the true point for the corner, a witness corner might cause confusion.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

From the true point for the corner of secs. 28, 29, 32, and 33, the point for the original meander corner of secs. 29 and 32 (original record: 24.09 chs. west of the corner of secs. 28, 29, 32, and 33), bears S. 75° 18' W., 31.42 chs. dist. This point is well marked by a 4 inch squared wooden stake, 36 ins. above the ground.

In place of wooden stake.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for meander corner of secs. 29 and 32, with brass cap mkd.

T 37 N
S 29
S 32
R 8 E
1927

From which

An original bearing tree

A pine stump, 30 ins. diam., bears S. 34° E., 32 lks. dist., marks obliterated.

This corner is accepted and recognized by the people living in this vicinity as being the original corner.

From the corner of secs. 4, 5, 32, and 33, previously described, on the south boundary of the township.

N. 4° 36' E., on a true line, bet. secs. 32 and 33, over rolling land, through timber and brush.

45.33 The true point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, which is marked by a wooden stake, 3 x 3 x 30 ins. above ground.

In place of stake.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 32 and 33, with brass cap mkd.

$\frac{1}{4}$
S 32 | S 33
1927

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

There is no positive evidence of the original bearing trees but there are numerous stumps in the immediate vicinity that check out very close to the original record although I can not positively state which stumps are or shall be considered the stumps of the original bearing trees. There is a very old blaze on a tree about 50 lks. south thus showing that this point has been recognized for many years. The corner falls in a small tamarack and spruce swamp. This checks out with the original record as the original bearing trees are noted as a spruce and a tamarack. There is no other swamp in this immediate vicinity. Until the recent local resurvey this corner has always been recognized as the true corner. The County records also show that in the year 1894, D. H. Vaughan, County Surveyor, ran the east and west center line through sec. 33 and it appears from his record that in 1894 he recognized this $\frac{1}{4}$ sec. cor. In his field notes, a small lake is noted at 33.92 chs. east of the $\frac{1}{4}$ sec. cor. According to my measurement this lake is 33.29 chs. east thus confirming the position of the wooden stake. His field notes also show that the bearing trees could be identified at that time. From all the evidence it appears that the wooden stake, which I accept, marks the true corner position.

From which

A squared wooden stake, 4 x 4 x 24 ins. above ground, set in the recent local resurvey, for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, bears S. $43^{\circ} 26'$ W., 9.84 chs. dist.

And new bearing trees to the true $\frac{1}{4}$ sec. cor.

A spruce, 6 ins. diam., bears S. 70° E., 26 lks. dist., mkd. $\frac{1}{4}$ S 33 B T.

A spruce, 5 ins. diam., bears N. $64^{\circ} 30'$ W., 11 lks. dist., mkd. $\frac{1}{4}$ S 32 B T.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains	Thence
	N. 11° 13' W., continuing on a true line, bet. secs. 32 and 33. Beginning new measurement.
33.64	The true point for the corner of secs. 28, 29, 32, and 33. Land, rolling. Soil, sandy; 3rd rate. Timber, small oak and poplar. Undergrowth, oak and poplar.
<u>Reestablishment of the Original Meander Line of Flanner Lake in Section 33.</u>	
Preliminary to the reestablishment of the original meander line, I calculated the latitudes and departures of the original meanders as returned in the field notes of the original survey, and distributed the closing error thereof, each in proportion to the lengths of the original courses, adopting new courses to the nearest minute, with lengths to the nearest link, and as far as consistent, a similar distribution was made of the small closing error of the present survey, with the resulting traverse on the ground as follows:	
<u>I commence at the meander corner of secs. 28 and 33,</u> 9.91 chs., N. 88° 16' W. of the corner of secs. 27, 28, 33, and 34.	
Thence with the reestablished meanders of Flanner Lake in sec. 33.	
Over rolling land, through second growth timber and brush. S. 29° 14' E., 2.99 chs.	
2.99	Adjusted position. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for angle point No. 14, sec. 33, with brass cap mkd.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

AP 14 T 37 N
R 8 E

S 33

1927

No trees suitable for bearing trees.

Thence

S. 1° 33' E., 15.89 chs.

15.89

Adjusted position.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for angle point No. 13, sec. 33, with
brass cap mkd.

AP 13 T 37 N
R 8 E

S 33

1927

From which

A norway pine, 6 ins. diam., bears N. 31° 30' W., 50
lks. dist., mkd. AP 13 S 33 B T.

A norway pine, 4 ins. diam., bears S. 34° 15' W., 69
lks. dist., mkd. B T.

Thence

S. 30° 49' W., 10.40 chs.

In spruce swamp.

10.40

Adjusted position.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for angle point No. 12, sec. 33, with
brass cap mkd.

AP 12 T 37 N
R 8 E

S 33

1927

From which

A poplar, 8 ins. diam., bears N. 66° 45' W., 118 lks.
dist., mkd. AP 12 S 33 B T.

A white pine stump, 24 ins. diam., bears S. 37° 45' W.,
102 lks. dist., mkd. AP 12 B T.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

Thence

S. $74^{\circ} 18' W.$, 10.40 chs.

3.75 Road, bears N. and S. Leave swamp, thence over gently
rolling land.

9.72 To actual shore of Velvet Lake, bears NW. and S.
Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for a meander corner of sec. 33, with
brass cap mkd.

T 37 N
S 33
M C
S 33
R 8 E
1927

From which

SW. corner of house, bears N. $45^{\circ} 06' E.$, 64 lks.
dist.

Well, bears S. $11^{\circ} 39' E.$, 59 lks. dist.

Thence over lake.

10.40 Adjusted position for angle point No. 11, sec. 33.

Thence

N. $80^{\circ} 30' W.$, 12.90 chs.

Over lake.

10.04 To shore of lake, bears N. and S.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for a meander corner of sec. 33, with
brass cap mkd.

T 37 N
S 33
M C
S 33
R 8 E
1927

From which

A spruce, 6 ins. diam., bears N. $2^{\circ} 30' E.$, 23 lks.
dist., mkd. S 33 M C B T.

A spruce, 5 ins. diam., bears S. $31^{\circ} 30' W.$, 25 lks.
dist., mkd. S 33 M C B T.

Thence through a spruce swamp.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

12.50 Leave swamp, bears NW. and SE. Thence over high rolling land.

12.90

Adjusted position.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for angle point No. 10, sec. 33, with brass cap mkd.

S 33 AP 10
T 37 N R 8 E
1927

From which

A birch, 3 ins. diam., bears N. $28^{\circ} 30'$ E., 13 lks.
dist., mkd. B T.

A birch, 3 ins. diam., bears S. $56^{\circ} 30'$ E., 14 lks.
dist., mkd. B T.

Thence

N. $33^{\circ} 26'$ W., 2.50 chs.

2.50

Adjusted position.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for angle point No. 9, sec. 33, with brass cap mkd.

AP 9
S 33
T 37 N R 8 E
1927

From which

A poplar, 3 ins. diam., bears S. $70^{\circ} 15'$ E., 11 lks.
dist., mkd. B T.

A birch, 3 ins. diam., bears S. $45^{\circ} 30'$ W., 23 lks.
dist., mkd. B T.

Thence

S. $47^{\circ} 04'$ W., 1.98 chs.

1.98

Adjusted position.

Set an iron post, 3 feet long, 2 ins. diam., 26 ins. in the ground, for angle point No. 8, sec. 33, with brass cap mkd.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

AP 8

S 33

T 37 N R 8 E

1927

No trees suitable for bearing trees.

Thence

N. 64° 21' W., 8.47 chs.

8.00 Enter an open swamp, bears N. and S.

8.47 Adjusted position.

Set an iron post, 3 feet long, 2 ins. diam., 26 ins. in
the ground, for angle point No. 7, sec. 33, with
brass cap mkd.

S 33

AP 7

T 37 N R 8 E

1927

From which

A norway pine, 10 ins. diam., bears N. 11° 15' E.,

228 lks. dist., mkd. AP 7 S 33 B T.

No other tree suitable for a bearing tree.

Thence

N. 16° 18' W., 6.27 chs.

5.00 Leave swamp, bears E. and W.; thence over high rolling
land.

6.27 Adjusted position.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for angle point No. 6, sec. 33, with
brass cap mkd.

AP 6

S 33

T 37 N

R 8 E

1927

From which

A norway pine, 10 ins. diam., bears S. 31° 30' E.,

203 lks. dist., mkd. AP 6 S 33 B T.

No other tree suitable for a bearing tree.

L357

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

Thence

S. 74° 11' W., 2.97 chs.

2.97

Adjusted position.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for angle point No. 5, sec. 33, with brass
cap mkd.

AP 5

S 33

T 37 N R 8 E

1927

From which

A birch, 5 ins. diam., bears N. 78° W., 217 lks.

dist., mkd. AP 5 S 33 B T.

No other tree suitable for a bearing tree.

Thence

N. 78° 27' W., 13.87 chs.

4.42

To point near foot of low ridge, bearing NW. and SE.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for a witness point of sec. 33, with
brass cap mkd.

WP

S 33

T 37 N R 8 E

1927

From which

A poplar, 5 ins. diam., bears N. 70° 45' W., 66 lks.

dist.; Mkd. WP S 33 B T.

No other tree suitable for a bearing tree.

From this point the remainder of the adjusted original
meander line follows close to the edge of an open
swamp surrounding Dumb Bell Lake and not very far
from the actual edge of the open water. Therefore,
from this point, the remainder of the line is
considered approximately correct and is not
reestablished. The west boundary of the unsurveyed
public land is determined by running a line from this
witness point along and near the foot of the low
ridge to the actual shore of Dumb Bell Lake where a
meander corner of sec. 33 is established.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains	
13.87	Adjusted position for angle point No. 4, Sec. 33. Thence N. 43° 48' E., 3.54 chs. To adjusted position for angle point No. 3, Sec. 33. N. 27° 45' W., 5.49 " To adjusted position for angle point No. 2, Sec. 33. N. 23° 00' E., 5.57 " To adjusted position for angle point No. 1, Sec. 33. N. 29° 45' E., 4.55 " To the proportional point for the original meander corner of secs. 28 and 33, which is 23.87 chs., N. 73° 32' E. of the true point for the corner of secs. 28, 29, 32, and 33.
	From the witness point of sec. 33, set 4.42 chs., N. 78° 27' W. from angle point No. 5, sec. 33. Thence N. 28° 25' W., to connect with the actual shore of Dumb Bell Lake. Through second growth timber along and near the foot of a low ridge which extends to Dumb Bell Lake.
3.04	To actual shore of Dumb Bell Lake, bears NW. and NE. Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for a meander corner of sec. 33, with brass cap mkd.

M C

S 33 S 33
T 37 N R 8 E

1927

L35 L357

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

From which

A birch, 4 ins. diam., bears N. 23° 30' E., 42 lks.

dist., mkd. M C B T.

No other tree suitable for a bearing tree.

The iron post is set 2 lks. NW. of a large surface rock.

From the original meander corner of secs. 28 and 33,

5.15 chs., N. 85° 10' W. of the proportional point
for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.Thence with the reestablished meanders of Flanner Lake
in Sec. 33.Over rolling land, through second growth timber and
brush.

S. 31° 52' W., 4.02 chs.

4.02 Adjusted position.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for angle point No. 18, sec. 33, with
brass cap mkd.

T 37 N
R 8 E
S 33 AP 18
1927

From which

A norway pine, 12 ins. diam., bears N. 33° 30' E.,
230 lks. dist., mkd. AP 18 S 33 B T.

No other tree suitable for a bearing tree.

Thence

S. 60° 49' W., 5.01 chs.

5.01 Adjusted position.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for angle point No. 17, sec. 33, with
brass cap mkd.

T 37 N R 8 E
S 33
AP 17
1927

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

From which

A spruce, 3 ins. diam., bears S. 22° 30' W., 56 lks.
dist., mkd. B T.

A spruce, 3 ins. diam., bears S. 112° 15' E., 74 lks.
dist., mkd. B T.

Thence

N. 86° 24' W., 3.50 chs.

3.50 Adjusted position.

Set an iron post, 3 feet long, 2 ins. diam., 26 ins. in
the ground, for angle point No. 16, sec. 33, with
brass cap mkd.

T 37 N
R 8 E
S 33

AP 16

1927

No trees suitable for bearing trees.

From this point the remainder of the adjusted original
meander line follows close to the actual shore of
Dumb Bell Lake and is, therefore, considered correct
and is not reestablished and monumented. The north
bdy. of the unsurveyed public land is determined by
running a line from angle point No. 16 to the nearest
point on the actual shore of Dumb Bell Lake.

Thence

N. 2° 30' W., 2.98 chs. To the adjusted position
for angle point No. 15,
sec. 33.

N. 15° 00' W., 2.78 " To the original meander
corner of secs. 28 and
33, 31.10 chs., N. 73°
32' E. of the true point
for the corner of secs.
28, 29, 32, and 33.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

From angle point No. 16, sec. 33.

Thence

N. 39° 12' W., to connect with the actual shore line of
Dumb Bell Lake.

Over rolling land, through timber and brush.

1.62 To actual shore of Dumb Bell Lake, bears N. and W.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for a meander corner of sec. 33, with
brass cap mkd.

M C
S 33 S 33
T 37 N R 8 E
1927

From which

A norway pine, 10 ins. diam., bears S. 89° 30' W.,

258 lks. dist., mkd. T 37 N R 8 E S 33 M C B T.

A norway pine, 12 ins. diam., bears N. 11° 15' E.,

52 lks. dist., mkd. T 37 N R 8 E S 33 M C B T.

Subdivision of Section 33.

From the 1 sec. cor. of secs. 33 and 34.

Thence

N. 87° 08' W., on a true center line, through sec. 33.

Over rolling land, through timber and brush.

7.00 Enter a spruce swamp, bears N. and S.

18.50 Leave swamp, bears N. and S., thence over rolling land,
through high land timber and brush.

19.86 Point for the C. E. 1/16 sec. cor.

No corner established.

23.46 To actual shore of Velvet Lake, bears NE. and SW. and
point for a special meander corner of sec. 33.

No corner established.

Thence by triangulation across Velvet Lake.

32.80 To actual shore of Velvet Lake, bears NE. and SW., and
point for a special meander corner of sec. 33.

No corner established.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains	Thence over rolling land, through high land timber and brush.
36.10	To east shore of a small lake, bears NE. and SW. Thence by triangulation across Lake.
39.72	True point for the C. $\frac{1}{4}$ sec. cor. of sec. 33, falls in lake.
44.30	To west shore of small lake, bears N. and S. Thence over rolling land, through scattered highland timber and brush.
74.50	Enter a spruce and tamarack swamp, bears NW. and SE.
77.59	The $\frac{1}{4}$ sec. cor. of secs. 32 and 33. Land, rolling. Soil, sandy; 3rd rate. Timber, scattered poplar, oak, and pine. Undergrowth, hazel, poplar, and oak.
	From the $\frac{1}{4}$ sec. cor. of secs. 4 and 33, previously described, on the south boundary of the section. Thence N. $1^{\circ} 50'$ E., on a true center line, through sec. 33. Over rolling land, through timber and brush.
1.70	Road, bears E. and W.
10.70	To south shore of small pond, bears E. and W.
14.30	To north shore of pond, bears E. and W.
27.80	Thence along west edge of Velvet Lake.
31.00	Leave west edge of Velvet Lake.
39.85	To the south shore of a small lake, bears NE. and NW. Thence across lake by triangulation.
43.35	Point of intersection with the true east and west center line through sec. 33 and true point for the C. $\frac{1}{4}$ sec. cor.
52.34	To north shore of small lake, bears SW. and NE. Thence over rolling land, through highland timber and brush.
54.45	Enter open swamp, bears E. and W.
56.60	Leave swamp, bears E. and W., thence over rolling land, through highland timber and brush.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains


57.28

Intersect the reestablished meander line of Flanner

Lake, through sec. 33, at a point from which angle
point No. 9, sec. 33, bears N. $47^{\circ} 04'$ E., 1.36 chs.
dist.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for a closing corner of sec. 33, with
brass cap mkd.



From which

A red oak, 4 ins. diam., bears N. $3^{\circ} 45'$ W., 80 lks.
dist., mkd. C C S 33 B.T.

A red oak, 4 ins. diam., bears S. $73^{\circ} 45'$ W., 37 lks.
dist., mkd. C C S 33 B T.

62.44

To actual shore of Flanner Lake, bears E. and W.

Set an iron post, 3 feet long, 2 ins. diam., 26 ins. in
the ground, for a special meander corner of sec. 33,
with brass cap mkd.

S M C

C

S

C

1927

From which

A birch, 6 ins. diam., bears N. 85° W., 35 lks. dist.,
mkd. S 33 S M C B T.

A birch, 5 ins. diam., bears N. $70^{\circ} 45'$ E., 23 lks.
dist., mkd. S 33 S M C B T.

Thence by triangulation across Flanner Lake.

86.57

The point for the sec. cor. of secs. 28 and 33, in
Flanner Lake.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains	<p>Land, rolling. S. soil good for crops.</p> <p>Soil, sandy; 3rd rate.</p> <p>Timber, oak, poplar and birch.</p> <p>Undergrowth, oak and poplar.</p>
	<p>From the point for the C. E. 1/16 sec. cor. of sec. 33.</p> <p>Thence</p> <p>N. 0° 05' W., on a true center line, through the NE. 1/4 of sec. 33.</p> <p>(Bearing is computed to intersect the point for the E. 1/16 sec. cor. of secs. 28 and 33.)</p> <p>Over rolling land, through timber and brush.</p>
7.06	<p>To actual shore of Velvet Lake, bears NE. and SW.</p> <p>Thence by triangulation across Lake.</p>
12.35 1/2	<p>To actual shore of Velvet Lake, bears E. and W.</p> <p>Thence over rolling land, through high land timber and brush.</p>
12.77	<p>Intersect the reestablished meander line of Flanner Lake, through sec. 33, at a point from which angle point No. 12, sec. 33, bears N. 74° 18' E., 5.95 chs. dist.</p> <p>At point of intersection.</p> <p>Set an iron post, 3 feet long, 2 ins. diam., 26 ins. in the ground, for a closing corner of sec. 33, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>E</p> <p>C C S 33</p> <hr style="width: 50%; margin: 0 auto;"/> <p>E</p> <p>1927</p> </div>
	<p>From which</p> <p>A norway pine, 6 ins. diam., bears N. 34° W., 45 lks. dist., mkd. C C S 33 B T.</p> <p>A birch, 5 ins. diam., bears S. 85° 30' E., 42 lks. dist., mkd. C C S 33 B T.</p>
17.15	Road, bears E. and W.
21.17 1/2	Point of intersection with the true east and west center line, through the NE. 1/4, sec. 33.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

Set an iron post, 3 feet long, 2 ins. diam., 8 ins. in the ground and in a mound of stone, for the NE. 1/16 sec. cor. of sec. 33, with brass cap mkd.

NE 1/16 S 33

1927

From which

A norway pine, 6 ins. diam., bears N. 31° 45' W., 9 lks. dist., mkd. NE 1/16 S 33 B T.

A double red oak, 8 ins. diam., bears S. 54° E., 24 lks. dist., mkd. NE 1/16 S 33 B T.

23.80½

To actual shore of Flanner Lake, bears NE. and SW.

Set an iron post, 3 feet long, 2 ins. diam., 26 ins. in the ground, for a special meander corner of sec. 33, with brass cap mkd.

S M C

E

S 33

1927

From which

A norway pine, 7 ins. diam., bears S. 70° W., 42 lks. dist., mkd. S 33 S M C B T.

A birch, 5 ins. diam., bears N. 66° 30' E., 65 lks. dist., mkd. S 33 S M C B T.

Land, rolling.

Soil, sandy, 3rd rate.

Timber, poplar, birch, pine, and oak.

Undergrowth, oak and poplar.

From the point for the N. 1/16 sec. cor. of secs. 33 and 34.

Thence

N. 87° 18' W., on a true center line, through the NE. ¼ of sec. 33.

Over nearly level land, through timber and brush.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

2.50

Enter a spruce swamp, bears NW. and SE.

9.91

Intersect the reestablished meander line of Flanner Lake,
through sec. 33, at a point from which angle point
No. 13, bears N. $30^{\circ} 49'$ E., 3.07 chs. dist.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for a closing corner of sec. 33, with
brass cap mkd.

S 33
N ——— N
C C
1927

From which

A spruce, 6 ins. diam., bears N. 76° W., $15\frac{1}{2}$ lks.
dist., mkd. C C S 33 B T.

A spruce, 5 ins. diam., bears N. 33° W., $23\frac{1}{2}$ lks.
dist., mkd. C C S 33 B T.

12.40

Leave swamp, bears N. and S., thence over rolling land,
through high land timber and brush.

19.47

The NE. $\frac{1}{16}$ sec. cor. of sec. 33.

21.19

To actual shore of Flanner Lake, bears N. and SW.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
the ground, for a special meander corner of sec. 33,
with brass cap mkd.

S M C S
N ——— N
33
1927

From which

A white pine, 8 ins. diam., bears S. 36° E., $16\frac{1}{2}$ lks.
dist., mkd. S 33 S M C B T.

A norway pine, 14 ins. diam., bears N. $47^{\circ} 15'$ E.,
56 lks. dist., mkd. S 33 S M C B T.

Land, level and rolling.

Soil, sandy; 3rd rate.

Timber, spruce, poplar, and oak.

Undergrowth, poplar and spruce.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

Survey of the South Boundary of Lot 10.

(Lot 10, claimed by H. J. Peterson, Rhinelander, Wis.)

From an iron pipe, 1 in. diam., 12 ins. above ground,
marking a point on the south bdy. of the area
claimed by H. J. Peterson.

Thence

S. 60° E., 0.29 chs. To shore of Flanner Lake,
bears N. and S. At this
point.

Set an iron pipe, $\frac{3}{4}$ ins.
diam., 30 ins. long, 20
ins. in the ground,
surrounded by a mound of
stone for the SE. cor.
of lot 10.

Returning to the iron pipe. (Place of beginning)

Thence

N. 60° W., 1.05 chs. To shore of Flanner Lake,
bears NE. and South. At
this point.

Set an iron pipe, 1 in.
diam., 24 ins. long, 16
ins. in the ground,
surrounded by a mound of
stone for the SW. corner
of lot 10.

Meanders of Flanner and Velvet Lakes.

From the meander corner of secs. 28 and 33, 9.91 chs.,
N. 88° 16' W. of the corner of secs. 27, 28, 33, and
34.

Thence with meanders of Flanner Lake in sec. 33.

Along a well defined shore line, at the edge of timber
and brush.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains		
S. 25° 33' E.,	2.60 chs.	
S. 10° 38' E.,	2.00 "	
S. 36° 07' W.,	1.70 "	
S. 14° 42' W.,	3.40 "	
S. 19° 50' W.,	1.40 "	
S. 11° 25' W.,	2.40 "	
S. 59° 21' W.,	3.30 "	
S. 44° 12' W.,	5.10 "	
N. 80° 38' W.,	0.92 "	To the NE. cor. of lot 19, Unity Point Subdivision.
S. 49° 48' W.,	0.25 1/2 "	To S. M. C. of sec. 33, on the N. and S. center line through the NE. 1/4 of sec. 33.
S. 61° 23' W.,	1.26 1/2 "	To the cor. of lots 18 and 19, Unity Point Subdivision.
S. 64° 30' W.,	0.88 1/2 "	
S. 4° 53' E.,	1.52 1/2 "	To the cor. of lots 17 and 18, Unity Point Subdivision.
S. 57° 30' E.,	0.08 "	To the S. M. C. of sec. 33, on the E. and W. center line through the NE. 1/4 of sec. 33.
S. 44° 47' W.,	0.77 "	To the cor. of lots 16 and 17, Unity Point Subdivision.
S. 54° 00' W.,	1.51 "	To cor. of lots 15 and 16, Unity Point Subdivision.
S. 76° 25' W.,	1.51 1/2 "	To cor. of lots 14 and 15, Unity Point Subdivision.
N. 89° 03' W.,	1.52 "	To cor. of lots 13 and 14, Unity Point Subdivision.
N. 87° 32' W.,	1.51 "	To cor. of lots 12 and 13, Unity Point Subdivision.
N. 62° 38' W.,	0.10 "	
N. 49° 22' W.,	0.60 "	

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains	S. 35° 29' W.,	1.41 chs.	To cor. of lots 11 and 12, Unity Point Subdivision. House, bears about S. 30° E., 140 lks. dist.
	S. 23° 51' W.,	1.51 "	To cor. of lots 10 and 11, Unity Point Subdivision.
	S. 37° 57' W.,	1.51 "	To cor. of lots 9 and 10, Unity Point Subdivision.
	S. 14° 16' W.,	0.41 "	
	S. 9° 51' E.,	0.90 "	
	S. 74° 40' E.,	0.51 "	To cor. of lots 8 and 9, Unity Point Subdivision.
	S. 84° 00' E.,	1.52 "	To cor. of lots 7 and 8, Unity Point Subdivision.
	N. 86° 00' E.,	1.51 "	To cor. of lots 6 and 7, Unity Point Subdivision.
	S. 42° 08' E.,	1.52 "	To cor. of lots 5 and 6, Unity Point Subdivision.
	S. 39° 18' E.,	1.52 "	To cor. of lots 4 and 5. House, bears north about 150 lks. dist. House, bears N. 49° E., about 150 lks. dist.
	S. 67° 03' E.,	1.51 "	To cor. of lots 3 and 4, Unity Point Subdivision.
	S. 62° 16' E.,	0.35 "	To the meander cor. of sec. 33, set on the reestablished meander line, 9.72 chs., S. 74° 18' W. of angle point No. 12. House, bears N. 45° E., 59 lks. dist.
	S. 0° 35' W.,	0.98 "	

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains		
N. 59° 55' E.,	1.28 chs.	To cor. of lots 2 and 3, Unity Point Subdivision. House, bears N. 30° E., about 130 lks. dist.
N. 66° 46' E.,	1.50 "	To cor. of lots 1 and 2, Unity Point Subdivision.
N. 73° 16' E.,	1.22 "	At 1.21 chs., intersect N. and S. center line through NE. $\frac{1}{4}$ of sec. 33, at a point 12.35 $\frac{1}{2}$ chs., N. 0° 05' W., of the true point for the C. E. 1/16 sec. cor. of sec. 33. At 1.22 chs., the cor. of lots 1 and block "B" of Unity Point Subdivision.
S. 34° 30' E.,	3.40 "	
S. 41° 13' W.,	1.00 "	
S. 35° 00' W.,	2.17 "	To a point on the true N. and S. center line, through the NE. $\frac{1}{4}$ of sec. 33, which is 7.06 chs., N. 0° 05' W. of the true point for the C. E. 1/16 sec. cor. of sec. 33.
S. 28° 41' W.,	4.10 "	
S. 25° 33' W.,	1.10 "	
S. 26° 28' W.,	2.55 "	To a point on the true E. and W. center line, through sec. 33, which is 23.46 chs., N. 87° 08' W. of the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

Land, rolling.

Soil, sandy, 3rd rate.

Timber, pine, oak, poplar, and birch.

Undergrowth, small timber.

From the meander corner of secs. 28 and 33, 5.15 chs.,

N. 85° 10' W. of the point for the $\frac{1}{4}$ sec. cor. of
secs. 28 and 33.

Thence with meanders of Flanner Lake in sec. 33.

Along a well defined shore line at the edge of timber
and brush.

S. 18° 15' W., 2.10 chs.

S. 2° 30' E., 1.20 "

S. 28° 30' E., 2.10 "

S. 30° 00' W., 4.10 "

S. 15° 30' W., 1.50 "

S. 7° 00' W., 1.20 "

S. 53° 00' E., 1.40 "

N. 74° 30' E., 1.10 "

N. 25° 30' E., 1.40 "

N. 70° 15' E., 2.00 " House, bears south about
60 lks. dist.

S. 37° 00' E., 2.90 "

S. 2° 00' W., 2.50 "

S. 53° 30' W., 6.40 "

N. 54° 00' W., 2.80 "

S. 20° 00' W., 2.20 "

S. 60° 45' E., 1.60 "

S. 49° 45' E., 4.80 "

S. 62° 00' E., 3.80 " To the S. M. C. of sec. 33,
set on the N. and S. center
line through the section.

N. 88° 33' E., 1.50 "

N. 86° 35' E., 2.10 "

N. 35° 10' E., 1.10 "

N. 9° 06' W., 0.95 "

N. 12° 14' E., 1.30 "

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

N. 32° 21' E., 1.60 chs.

N. 11° 56' E., 3.50 chs.

N. 29° 22' E., 0.37 chs. To the SW. cor. of lot 10,

S. 80° 00' E., 0.75 chs.

N. 12° 44' E., 1.90 " At 1.20 chs., house bears
east about 60 lks. dist.

N. 6° 51' W., 1.80 "

N. 42° 14' E., 0.43 "

S. 18° 45' E., 3.06 "

S. 33° 26' W., 1.92 " To the SE. cor. of lot 10,
sec. 33.

S. 14° 07' E., 3.61 "

S. 28° 48' W., 3.21 "

S. 25° 45' W., 0.86 "

S. 9° 22' W., 7.50 " To the meander corner of
sec. 33, on the
reestablished meander
line of Flanner Lake and
set 2.86 chs., S. 80° 30'
E. of angle point No. 10,
sec. 33.

S. 33° 22' E., 1.93 "

S. 1° 08' W., 2.00 "

S. 19° 27' E., 4.44 "

S. 14° 43' W., 5.04 " To a point, on the true
east and west line through
the section, which is
6.92 chs., S. 87° 08' E.
of the true point for the
C. 1/4 sec. cor.

Land, rolling.

Soil, sandy, 3rd rate.

Timber, poplar, birch, and oak.

Undergrowth, small timber.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

Meanders of Dumb Bell Lake in Sec. 33.

From the meander corner of secs. 28 and 33, on the E.
shore of Dumb Bell Lake.

Thence with the meanders of Dumb Bell Lake in sec. 33.

Along a well defined shore line.

S. 20° 30' W., 0.96 chs.

S. 12° 45' E., 3.55 " To a meander corner of
sec. 33, set 1.62 chs.,
N. 39° 12' W. of angle
point No. 16, sec. 33.

N. 78° 00' W., 2.50 "

S. 47° 30' W., 3.20 "

S. 26° 00' W., 2.90 "

S. 19° 45' E., 1.10 "

S. 42° 00' E., 6.00 "

S. 24° 15' W., 3.90 " To a meander corner of
sec. 33, set 3.04 chs.,
N. 28° 25' W of the
witness point on the
reestablished meander
line of Flanner Lake.

N. 68° 00' W., 5.05 "

N. 14° 15' W., 6.90 "

N. 22° 38' E., 3.13 "

N. 40° 00' W., 3.40 "

N. 16° 00' E., 0.58 " To a point on the line
bet. secs. 28 and 33,
which is 20.01 chs., N.
73° 32' E. of the true
point for the cor. of
secs. 28, 29, 32, and 33.

Land, rolling.

Soil, sandy; 3rd rate.

Timber, scattering poplar and pine.

Undergrowth, small timber.

General Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

In order to show the actual conditions, the shore line of that portion of Velvet Lake in the SE. $\frac{1}{4}$ of sec. 33, is determined by Stadia readings and intersections with the resulting computed traverse of the actual shore line as follows:

From a point, on the west shore of Velvet Lake, on the true east and west center line of sec. 33, which is 6.92 chs., S. $87^{\circ} 08' E.$ of the true point for the C. $\frac{1}{4}$ sec. cor. of sec. 33.

Thence with a traverse of the actual lake shore of Velvet Lake in the SE. $\frac{1}{4}$ of sec. 33.

Along a well defined shore line.

S. $25^{\circ} 30' W.$, 2.80 chs.

S. $15^{\circ} 30' E.$, 1.40 "

S. $53^{\circ} 00' W.$, 1.50 "

S. $14^{\circ} 00' W.$, 1.50 "

S. $50^{\circ} 30' W.$, 2.10 "

S. $17^{\circ} 15' W.$, 2.10 "

S. $56^{\circ} 45' W.$, 2.20 "

S. $34^{\circ} 00' W.$, 2.90 "

S. $20^{\circ} 15' E.$, 3.90 "

S. $85^{\circ} 15' E.$, 2.70 "

S. $59^{\circ} 15' E.$, 1.90 "

S. $25^{\circ} 00' E.$, 4.00 "

S. $78^{\circ} 15' E.$, 3.30 "

N. $25^{\circ} 45' E.$, 3.10 "

N. $48^{\circ} 00' E.$, 4.60 "

N. $16^{\circ} 30' W.$, 9.70 "

N. $25^{\circ} 30' E.$, 2.80 "

N. $41^{\circ} 00' E.$, 5.50 "

To a point, on the E. and W. center line through the sec. 33, which is 3.60 chs., N. $87^{\circ} 08' W.$ of the true point for the C. E. $\frac{1}{16}$ sec. cor. of sec. 33.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

For the purpose of platting and showing the actual conditions, the shore line of a small lake or pond near the center of the section is determined by stadia readings with the resulting traverse of the actual shore line as follows:

From a point on the true N. and S. center line through the section on the south shore of the lake and 3.50 chs., S. 1° 50' W. of the true point for the C. $\frac{1}{4}$ sec. cor. of sec. 33.

Thence with the traverse of the actual shore of the lake in sec. 33.

Along a well defined shore line.

N. 53° 00' E.,	2.91 chs.	
N. 41° 30' E.,	2.10 "	To a point on the true E. and W. center line of sec. 33, 3.62 chs., S. 87° 08' E. of the true point for the C. $\frac{1}{4}$ sec. cor.
N. 26° 30' E.,	2.60 "	
N. 34° 00' W.,	2.90 "	
N. 10° 15' W.,	2.50 "	
N. 20° 00' W.,	2.10 "	
S. 89° 45' W.,	1.70 "	To a point on the true N. and S. center line, 8.99 chs., N. 1° 50' E. of the true point for the C. $\frac{1}{4}$ sec. cor. of sec. 33.
S. 37° 15' W.,	2.50 "	
S. 75° 15' W.,	0.80 "	
N. 14° 45' W.,	3.00 "	
N. 1° 30' W.,	4.20 "	
S. 78° 30' W.,	2.80 "	
N. 76° 30' W.,	2.50 "	
S. 35° 15' W.,	2.60 "	
S. 28° 00' E.,	2.20 "	

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

to point on the true E. center line, 4.58
of sec. 33, T. 37 N., R. 8 E.
the true point for the
of sec.
33, T. 37 N., R. 8 E.
S. 19° 15' E., 3.30
S. 79° 45' E., 3.44 To point of beginning on
the N. and S. center line
of sec. 33, T. 37 N., R. 8 E.

General Description.

Supplemental Special Instructions, dated August 30, 1927,
issued by Donald B. Clement, Technical Assistant to
the Supervisor of Surveys, provided for the survey of
lands erroneously omitted from the original survey
adjacent to lots 2, 3, 4, 5, and 7, Sec. 33, T. 37 N.,
R. 8 E., 4th P. M., Wisconsin.

An examination of the area included in this survey was
made by the undersigned, assisted by Willis W. Bandy,
U. S. Surveyor, in the fall of 1926. The report of
this examination was submitted to the Associate
Supervisor of Surveys on January 21, 1927.

The original meander line is found to be grossly erroneous
in its representation of Flanner Lake as it existed in
1848 when Wisconsin was admitted into the Union, in
1863 when the township was surveyed and at the present
time. The tracts of land included in this survey are
shown as "water areas" on the approved plat.

There has been no material change in the elevation of
the lake since 1848 and the position for the record
meander line does not follow a contour line, which
might have been the shore line of the lake, but runs
over rolling land. The shore line of the lake is well
defined.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

The areas included in this survey are generally high, dry, and rolling and are not subject to selection by the State of Wisconsin, under the provisions of the Swamp Land Act. Soil is sandy. The areas are covered with second-growth timber consisting of poplar, pine, oak, and birch. Numerous large pine stumps were observed on the areas included in this survey. No indications of mineral deposits were observed.

The areas embraced in lots 9, 10, 12, and 13, have been claimed by John J. Remo of Rhinelander, Wisconsin, under his riparian rights as the owner of lot 4. Lots 9 and 13, are also claimed by Peter Kertzwell of Rhinelander, Wisconsin, who is the owner of lots 2 and 3. Lots 8 and 14 are also claimed by Kertzwell.

The Courts of Wisconsin held in a decision handed down during the summer of 1927, that the entire area, included in this survey east of Flanner Lake, belongs to the owner of lots 2 and 3 and that there is no unsurveyed Public Land lying between the lake and said lots 2 and 3.

The subdivision known as Unity Point was made by John J. Remo and numerous lots in this subdivision have been sold by him.

Lots 1, 7, 13, 15, 17, and 19, are claimed by John Remo of Rhinelander, Wisconsin. There are no improvements on these lots.

Lot 2, is claimed by Mrs. P. O. Means, 3154 Lake Park Ave., Chicago, Ills. A house has been built on this lot.

Lot 3, is claimed by Joseph Bertrand of Rhinelander, Wisconsin. A house has been built on this lot.

Lot 4, is claimed by Ed. Healy of Rhinelander, Wisconsin. A house has been built on this lot.

Resurvey of the Subdivisional and Meander Lines and
An Extension Survey in Section 33, T. 37 N., R. 8 E.

Chains

Lot 5, is claimed by Gilbert Forsyth of Rhinelander, Wisconsin. A house has been built on this lot.

Lot 6, is claimed by Wademar Johannsen of Dubuque, Iowa. No improvements.

Lots 8, 9, 10, and 11, are claimed by Gomer Jones of Horican, Wisconsin. A house has been built on lot 11.

Lot 12, is claimed by Mrs. H. G. Evans, of 618 Adams Street, Wausau, Wisconsin. No improvements.

Lot 14, is claimed by John O'Day, % Wisconsin Telephone Co., 418 Broadway, Milwaukee, Wisconsin. No improvements.

Lot 16, is claimed by Mrs. Wm. E. Peters of Baca St., Trinidad, Colorado. No improvements.

Lot 18, is claimed by Louis Remo of La Ren , Quebec, Canada. No improvements.

Lot 10 of this survey is claimed by H. J. Peterson of Rhinelander, Wisconsin. This piece of land was bought by Peterson from John Remo. The cabin in the eastern portion of lot 11 of this survey was built by John Remo. I do not know who is claiming the area shown as lot 11 of this survey but original lot 7 is owned by Peter Kertzwell of Rhinelander, Wisconsin, and original lot 5 is owned by E. M. Mc Vicker, Pabst Building, Milwaukee, Wisconsin. All parties interested in the areas included in this survey have been notified.

The town of Rhinelander, Wisconsin, is located approximately 4 miles east.

(Signed) Earl G. Harrington.

U. S. Cadastral Engineer.

CERTIFICATE OF UNITED STATES SURVEYOR.

I, Earl G. Harrington, U. S. Cadastral Engineer, U. S. Surveyor, hereby certify upon honor that, in pursuance of Supplemental Technical Assistant to the Supervisor of Surveys of special instructions received from the U. S. Surveyor General for

bearing date of the 30th day of August, 19 27, I have well, faithfully, and truly

in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instruc-

tions, and the laws of the United States, surveyed all those parts or portions of the resurvey of

the subdivisional and meander lines and an extension survey in Section

33, Township 37 North, Range 8 East

of the Fourth Principal Meridian, in the State of Wisconsin, which are represented in

the foregoing field notes as having been executed by me, and under my direction; and that all the corners of

said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instruc-

Supplemental Technical Assistant to the Supervisor of Surveys of special written instructions of the U. S. Surveyor General for

and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

(Signed) Earl G. Harrington,
U. S. Cadastral Engineer.

APPROVAL.

Office of the U. S. Supervisor of Surveys,
~~Office of the United States Surveyor General,~~

Denver, Colo., 1928.

The foregoing field notes of the survey of resurvey of the subdivisional and meander lines and an extension survey in Section 33, Township 37 North, Range 8 East of the Fourth Principal Meridian, in the State of Wisconsin.

executed by Earl G. Harrington, U. S. Cadastral Engineer

supplemental under his special instructions dated August 30, 1927, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

U. S. Supervisor of Surveys.

I certify that the foregoing transcript of the field notes of the above-described surveys in Group 14.

Wisconsin, has been correctly copied from the original notes on file in this office.

U. S. Supervisor of Surveys.

4-680

FIELD ASSISTANTS.

[illegible]

6-2704

L 3 5 7