

copy of Town of Somo's copy  
of D.S. Burnett's resurvey of  
Secs 1-18, T35N, R4E,  
additional road surveys in  
1923-24.

Town copy kept in Post Office @  
Tripple by Town Clerk.  
15 OCT 1973 RHEWAT

Field Notes

Town of Somo's copy of  
the original field notes  
with added comments.

RECEIVED & FILED	17284
Oneida County Surveyor's Office	
Date	MAR 1 1 1988
By	M R
OCS Area #	

Copy

of notes made in the field  
on the Re-Survey of a  
part of the Town of Somers  
(T. 35 N., R. 4 E.) begun  
September 12<sup>th</sup> 1923  
and finished Oct. 4, 1923

by

D.S. Burnett,  
Civil Engineer  
Wausau, Wis.

Wausau  
Wis.  
1923  
D.S. Burnett  
Civil Engineer  
Wausau, Wis.  
res, C.  
T. 35 N.  
R. 4 E.  
Somers, Wis.  
1923

Part of town of  
Somers, Wis.  
T. 35 N., R. 4 E.  
Somers, Wis.  
Subdivisions Surveyed  
by D.S. Burnett  
April & May 18 1923

1728

Sept. 12<sup>th</sup> P.M. Cold; wind <sup>spilling</sup>

Identified X to 3 54 33 20-1  
Town Line Bet. 35 + 36 N. 71. 1/2 W.  
by one orig. Co. B.T.

W. Pine 24 " N. 35 " E. 1/2 S.

New, W. Pine 16 " N. 13 " S.

From above X. 3., U. 5 E.

40.00 hit old iron stake set  
by some unknown person  
marks on a bed of iron  
Disregarded iron stake  
because of disparity of the  
distance from this corner  
as compared to other  
43.75, Var. West of  
stake.

Chas. (Stake said to be  
Vaughan)

9/13

57.00 chs. Come river, c.

53.00 chs. over "

83.75 turned 90° Left (East)

Continued South

85.00 chs. Sec. Cor. 34-1-10  
by stake and two birch orig. B.T.

(over)

Part of town which was  
surveyed by  
Richard S. Ward, Aug. 1865

Q. S. + St. W. township  
lines

Surveyed by  
R. S. Ward, Aug. 1865

Subdivision Survey  
by Chas. A. Palmer

April + May, 1865

Sept. 21<sup>st</sup> 1923

At Cor. bet. Sec. 11+12  
found old Gov't B.T. via.  
W. Pine 8" N. 33° E. 50 lks.

Marks very faint but by the  
use of a reading glass marks  
were easily discernible.

Set monument and made  
new bearings.

- S. Maple 14" S. 70° W. 4 lks.
- S. Maple 16" N. 45° W. 48 1/2 lks.
- S. Elm 18" S. 70° E. 51 lks.
- Orig. Pine stp. N. 33° E. 50 lks.

Sept. 21<sup>st</sup> 1923

At Sec. Cor. of 11-12-13+14 found  
Orig. Gov't B.T. via 4"x4" Cedar  
stake.

- Orig. Tam. 6" S. 61° E. 31 lks
- " Spruce 4" N. 45° W. 10 "

Also a Tam. 10" S. 30° W. 37 " which  
was apparently marked by  
Gov't but no record made.

Set iron monument and  
marked new B.T.

- Spruce 7" S. 87° W. 32 1/2 lks.
- Birch 7" N. 45° 00' W. 28 "
- Birch 7" N. 50° 00' E. 49 1/4 "

Townships No. 35 & 36 North  
between Range 2 East  
& 4th Meridian

West between Sec. 6 & 31  
Cav. 7° 15' Q.

Corner Post at;  
78.65 Intersect Range  
line 340  
North of Post & set post  
for cor. of Towns.  
24-4-26.

- North Range 446 East
- W. Pine 16" N. 62° 55' W. 55 lks.
- Lamarack 12 S. 45° 16 "
- Lamarack 16 N. 35° 45' 52 "
- Lamarack 18 S. 89° 16' 55 "

between Townships 25-26  
North Range No. 4 East,  
& 4th Meridian

West between Sect. 17 & 26  
Cav. 5° 15'

40.00 Set 4 Sec. Post.  
Lamarack 12 S. 47° 32 "

57.50 Leave Lamarack Survey  
bears NE 7 1/2 "

59.20 Stream 5 links wide  
runs north.

50.00 Set Post for corner  
Sect. 12 3 5-9 26.

- Oemlock 7 N. 32° 15' E.
- Birch 8 N. 50° 23 "
- Oemlock 10 S. 15° 22 "
- W. 9 S. 12° 25 "

Surface, level, soil 3<sup>rd</sup>  
rate Timber: Alder,  
Cedar, Oemlock, &  
Pine.

1728

Sept. 22" Clear + Warm.

At 1/4 Cor. bet. 2+3 found both Orig B.T's; Hem. 8" N. 51° W. down and badly burned but marks still visible.

Hem. 6" S. 22° E. down but mark very plain. Fixed point from these Orig. Gov't B.T's and set monument. Marked up new B.T's

- H. Maple 12" S. 82° E. 51 lbs.
- Birch Stp. 22" N. 33° W. 30 1/2 "
- Hem. Stp. 26" N. 77° W. 51 "

Sept. 22"

From Sec. Cor. 2-3-10-11, East.

V. 3° 50' E., Set stakes for correction at 20.00 + 40.00 chs. 79.41 chs. had var. S. 0.42 chs.

At 39.70 1/2 chs. set 1/4 Cor. in Cor. line and in open field; nothing to mark as bearings.

Nat. Tan. of Cor. = .00529 = 0° 18'

Cor. V. = 4° 08' E.

- 1/4 Cor. at 19.85 1/4 = Cor. 10 1/2 lbs. 1/2
- 1/4 Cor. " 39.70 1/2 = Cor. 20 1/2 " 1/2
- 1/8 " " 59.55 3/4 = Cor. 31 " 1/2

Between Townships 35 + 36 North

Line between Sect. 2 + 3

Var. S. 30° W.

into Section 2

190' block 24 ft. 50° E. 152'

D.V. 10 S. 60 W. 200'

3.24 Creek 20 links wide runs South

77.50 Same Creek

50.00 Set Post for corner to Sections 2, 3, 34, 35

W. Pine 15 ft. 50 in. 48 links

Spruce 14 ft. 70 in. 62 "

Alder 5 ft. 20 in. 5 "

Surface rolling, Soil good, timber Hemlock, Pine & Birch, Undergrowth Alder & Hazle.

Range 10 + East to West

West between Sect. 2 + 3

Var. S. 30° E.

1.29 Creek 20 runs S. 27°

40.00 Set 1/4 Sect. Corner

Hemlock 10 ft. 20 in. S.

Birch 14 ft. 30 in. 22 "

53.10 Enter Swampy

Swampy unfit for cultivation bears

N. W. & S. E.

65.00 Leave same bears N. W. S. E.

77.77 W. Pine 24 in. in dia.

80.00 Set Post for corner

Sections 3, 4, 33 + 34

7 Birch 12 ft. 30 in. 10 "

W. Pine 24 in. 38 in. 15 "

Birch 25 ft. 35 in. 17 "

4 in. 10 ft. 39 in. 18 "

Surface level, Soil good

Timber Hemlock, Birch

Spruce, Birch

L7284

Sept. 22<sup>nd</sup> 1923

Sept. 23<sup>rd</sup>

Ht 1/4 Cor. Bet. 10+11 found one  
Orig. B.T. via Hem. 11" S. 45° W.  
6 lks.

Set monument and renewed  
marks on old tree and marked  
one new bearing.

Hem. Stp. 18" O.S. 86° E. 18 lks.

Sept. 23<sup>rd</sup> (Sunday) Clear + Warm

Ht 1/4 Cor. bet. 9+16 found  
marked Stake and spruce  
stp. 7" N. 84 E. 16 lks. that  
checked with field notes  
altho no marks were visible  
as the tree had been cut very  
low.

Set monument and marked  
new bearings.

Tam. 12" N. 14° W. 96 lks.  
Spruce 4" S. 76° W. 21 1/2 "  
Tam. 5" S. 56° E. 30 1/2 "

Ht 1/4 Cor. bet. 11+14 found a  
scribed stake and the stp. of  
one of the Orig. Gov't. Trees  
viz. Spruce 6" N. 14° E. 20 lks.

Also two other trees scribed  
to which I took bearings.

Spruce 7" N. 76° W. 21 1/2 lks.  
Tam. 12" S. 56° E. 30 lks

Set monument.

Between Township  
7 N. 35 + 36 North  
West between Sec. 4 + 33  
Var. 8' East  
79.25 1/2 Pine 24 in. in dia.  
Hem. Set by Sect. Post  
Birch 10 7/2 N. 13 E.  
Hemlock 155. 45 N. 18 E.  
75.40 Creek 2 ft. wide, runs S.E.  
70.00 Set Post for corner to  
Sections 4, 5, 32 + 33  
Hemlock 15 1/2 N. 19 E.  
Do 10 N. 5-5 Q. 47 E.  
Do 9 S. 10 Q. 15 E.  
Do 9 S. 33 N. 27 E.

Surface rolling, soil  
2<sup>nd</sup> rate. Timber  
Hemlock, Pine, Birch,  
Undergrowth  
Alder & Hazle

Range 70.4 East - 70.7 West

West between Sec. 31 + 32  
Var. 5' East

Hem. Set by Sect. Post  
Sec 500 } Hemlock 15 1/2 N. 13 E.  
K. 97 } Birch 10 7/2 N. 13 E.  
76.90 Creek 2 ft. wide, runs S.E.  
40 yds. S. E.  
80.00 Set Post for corner to Sec.  
5, 6, 31 + 32.  
Hem 10 N. 19 E. 13 lks.  
Do 10 S. 81 N. 30 "  
Do 10 S. 81 N. 30 "

Surface rolling, soil  
2<sup>nd</sup> rate. Timber  
Pine, Hemlock, Birch  
& Undergrowth  
Cedar & Alder.

L7284

Sept. 23<sup>rd</sup> 1923 Cloudy, foggy  
From Sec. Cor. 2-4-33-34, W. 20<sup>th</sup>

(20°E)

Ht 39.64 chs. found bearings  
established by H. Vaughan for  
1/4 Cor. on N. Side Sec. 4  
Pine Stp. 36" North 57 lks  
Tel. Pole S. 40° E. 35 1/4 lks.  
Lug and found iron monuments  
Set new monument.  
Nothing new to mark.

From 1/4 Cor bet. 4+33 West  
N. 4° 15' E.  
39.99 chs. found bearings all done.  
but 9" x 2" x 18" iron monument  
at intersections of Highways in  
place. Set monument for Cor.  
to 4-5-32+33 and took bearings  
to the followings  
East face of North Wing wall  
of Culvert N. 86° 10' W. 1.42 1/2 chs.  
N.W. Cor of foundation under  
main building of Town Hall

Sept. 24<sup>th</sup>

S. 27° 35' E. 1.27 chs.

From Sec. Cor. of 4-5-32+33  
West along Town Line N. 4° 20' E.  
39.89 chs. found stp. of Orig. Gov't  
bearing Birch 10" S. 5° W. 26 lks  
(shown me and sworn to by  
Cavanaugh, & P. Isaacson)  
Set monument and took bearings  
to - Pine Stp. 28" N. 44° E. 50 1/2 lks.  
Tel. Pole S. 4° E. 24 "  
Pine Stp. 30" N. 25° W. 95 1/2 "

79.95 chs. found Pine Stp. marked  
by Isrr. = Pine Stp. 29" N. 72 3/4 W. 1.44 chs  
Set monument. Took bearings  
N.W. Cor of Bridge over S. Road  
S. 45° W. — 33 lks  
N.E. Cor. of Bridge over S. Road.  
S. 45° 15' E. 34 lks.

Townships 35 & 36 North  
between Range 4 East.

West between Sect. 6 & 31  
Var. 8° East  
2.04 1/2 Pine 24 in. india.  
10. Post 1/4 Sect. Post  
Hemlock 10 1/2 54 1/2 20 lks.  
Oak 10 S. 38 W. 43 "  
1.5 ad intersected Range line  
40 2/3 links  
North of Temporary Post  
and set post for corner  
of Townships 35 & 36  
North of Ranges 37 & 38  
Sugar 12 1/2 52 1/2 21 links  
Oak 12 1/2 50 1/2 25 "  
Birch 12 S. 20 W. 19 "  
Sugar 12 S. 25 W. 12 "

Surface level, Soil 3<sup>rd</sup> rate  
Timber: Pine, Hemlock,  
& Birch.  
Undergrowth: Hazel & Alder

between Ranges 35 & 36  
North. Range 4 East,  
4<sup>th</sup> Meridian.

West between Sect. 1 & 30  
Var. 31° E.  
40.00 Set = Section east  
Lamarack 9 1/2 57 1/2 15 lks  
Cedar 7 1/2 62 1/2 9 "  
50.00 Large, uncut timber  
Sugar 10 1/2 54 1/2 20 lks.  
40.00 Set Post for corner  
of Section 1, 2, 3 & 30  
Hemlock 14 1/2 65 1/2 41 "  
Oak 12 1/2 60 1/2 27 links  
Oak 12 S. 20 W. 18 "  
Oak 10 S. 54 W. 31 "

Surface low, level &  
wet. Soil 3<sup>rd</sup> rate  
Timber: Lamarack  
Alder and Hemlock

1798