

Page 153 / City
SE Cor Cemetery

4.

AFTER FIVE DAYS RETURN TO
HARRY C. HALL
Oneida County Surveyor
Rhinelander, Wis.
June 1932 to April 1933
Oneida Lake
B37

Secs 2+11 - 36, -9

for B.L. How.

Survey of two parcels of approx 1 acre each and adjoining, according to desc. in deeds.

To begin at the East N. C on line bet. 7+11

Th. Ely on Sec. line	365 lks.	
" N at 90°	291 "	Th. at 90° to lake
Thence " "	274 "	" " " "

August 8th 1932 AM

H.C. Hall + B.L.H. look over situation + identify Orig MC on E shore and H.V. Vaughan's cor to 1-2-11-12 Established 1899 (1/26-31) by double pro-portion.

A road or lane lies at rear of the 2 acre tract.

2 + 11

36-9

44

continued

August 8th PM fair 75°
H.C. Hall, Ray & Marshall 1/2 day.
H.C. chops out wood covering Vaughan's marks on his W. Pine at MC. Meas. 32 1/2 N 45° E from do + check with birch stools where Orig. B's grew. Comes on shore & about in fence line. Drive Brown

{	New Bing - W. Pine 7"	N 54° E (P.C.)	.454
	H.V. W. Pine 16"	S 55° E (P.C.)	.32 1/2

At H.V. comes to 1-2-11-12 find Bennett's post & his marks on Stip called for by Vaughan. (Must have heaved off old facing - agrees OK with H.V. notes - his birch gone - in road. This corner is in line of roadway but the travelled way passes by on N side.

Drive S.P. in place of post (rotten) next flag.

{	P.C. over	H.V. W.P. Stip 22	S 38° E	.20 ✓
		Bennett's Stip W.P. 10"	N 20° W	.648
		New Spruce 4"	S 70° W	.715
		" Y. Pine 4"	N 45° E	.783

Meas. approx dist. bet. Sec Cor + MC. (following rd. - curving)

7.69
18.08
25.77d.

traced in for true Sec. line - var 10° 20' West ±

45

2 + 11

36.9

continued.

Sec. line cuts about 2" into N. side W. Pine
just E. of MC.

Ely on line from MC. 3.65' ch + drive I.P. (P)

{ about 1.5' N. of fence W
" " E " N
" 6' E " S.

See diagram →

Observe Sun at (P) Standard time
*, 3:28 PM vert. $38^{\circ}-06\frac{1}{2}'$
← W to S off line $34^{\circ}-18'$

Makes course of Sec. line $N73^{\circ}-07'-40'' W$

2 Obs. at (4)
3:50 $\frac{1}{2}$ PM vert. $34^{\circ}-22'$
hor. $29^{\circ}-38'$

→ $N73^{\circ}-06'' W.$

3 at 6. 4:15 $\frac{3}{4}$ PM vert $30^{\circ}-00'-30''$
 $24^{\circ}-37'$
= $N73^{\circ}-05'-45''$

y	EMC	pc	Noway	12"	S89°E	.195
			Maple	5"	N30W	.01
			W. Pine	9"	S55E	.295
x	W.M.C.		W "	7"	N55E	.268

40
07
06
05
05
3/18
06' 28"

full sec line

$N73^{\circ}-06\frac{1}{2}' W.$

∴ Var. on meridian
would be $6^{\circ}34' E$

Lot 8 Sec 2.

① 14' W of fence

② 3.23 40
3.134

2577 ±
Sec. line
Var. 10°-20' W. ±

$N73^{\circ}-06\frac{1}{2}' W$
Road.

③ = 4' E. of fence

Lot 1 Sec. 11

$N16^{\circ}-53\frac{1}{2}' E$

SE x Sec 2
cut by P.H.V.

46