CERTIFIED LAND CORNER RESTORATION

Index No. R-2

State of Wisconsin
County of Oneida } ss.

I Philip T. Hansen, do hereby certify that on the 20th day of October, 19 78, I found evidence of the W 1/16 corner of Section 19 & 30 Township 35, North, Range 10 East, Fourth Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original location of this corner.

Resident witnesses:

Jim Claflin

Herb Wagoner

WISCONSIN S-498 LAND SURVEYOR

T35N R10E

S 19

W 1/16

22.942 25.578

○ = Corner monument restored.

History of original corner establishment:

Corner established by Drivas and crew, Ripco surveyors, in 1961.
Ran random line west beearing 272° 30' magnetic from S 1/4 corner section 19 & 30, 48.52 chains to close out 95.8 links south.
Set W 1/16 at 25.578 chains on corrected bearing N 86° 22' W.
Marked NBT's -
Maple 8" N43°W 32 links
Maple 10" S50°E 23 links

Description of corner evidence found:

Recovered Ripco's 3/4" iron pipe with 2" diameter alloy cap in excellent condition.
Also an old iron pipe setting beside it.

Recovered OBT's -
Maple 8" (9") N43°W, 32.0 links, our bearing N38°W.
Maple 10" (12") S56°E (S59°E), scribing grown over.
Monument projects 2½' above ground. Cap stamped: W 1/16 S 19 S 30 RIPCO

Description of monument and accessories I established to perpetuate the original location of this corner.

No additional accessories established.

Dated at Rhinelander, Wis., this 27th day of November, 19 78.

Signature Philip T. Hansen Title Registered Land Surveyor Registration No. S-498
(County Surveyor, Registered Land Surveyor, or other duly authorized official)

Office of Register of Deeds, County of Oneida, I hereby certify that the within instrument was filed in this office for record on the 4th day of December, 19 78 at 1:35 o'clock P M.

Doris Verage Kuehn
(Register of Deeds)

By ..... Deputy

FORM 985 N. G. MILLER CO., MILWAUKEE

35/0190030