

MAP #	B 5174
DATE FILED	DEC-4-3-2012
BY	SJ
DESCRIPTION FILED	
ONEIDA CO. SURVEYOR'S OFFICE	

421 C 6

Vol. 124 Pg 84



# Survey of the west 1300 feet

Govt. Lot 3 and N.W.-S.W. - Sec. 33-T. 39 N.R. 10 E.

Scale - 1 Inch = 200 feet.

# Surveyors Certificate

I, Harry C. Hall, do hereby certify that in July and August 1933, at the request of John E. McKenna I made a survey of the West 1300 feet of Govt. Lot 3 and the West 1300 feet of the N.W.-S.W. of Sec. 33-T.39N.R.10-E. That the plat hereon drawn truly represents my survey. That the three Govt. Corners on the west line of said section were identified as original corners and permanent monuments set. At southwest corner of section an iron pipe was driven and location marked by bearing trees. A west  $\frac{1}{4}$  s. and Meander Corner cement posts 6"X6"X36" with bronze caps were set at original corners. That the section line from southwest corner of section North to  $\frac{1}{4}$  s. corner was used as the Assumed Meridian and all lines were initiated therefrom.

Harry C. Hall

County Surveyor Oneida County

August 7 - 1933

## Bearings Marked

- A = Orig. Meander Corner - Hemlock Stump 16 S 13 W. 24<sup>ft</sup> - Set Cement monument  
 B = " 1/4 S. corner - Hemlock Stump 10 S. 9 E. 32<sup>ft</sup> " " " "  
 C = 1/8 S. corner - Basswood 8 N. 42 E. 43<sup>ft</sup> } 8 S. 15 W. 14" } Drove Iron Pipe  
 D = Maple 3 N 8 E. 4 ft. - Maple 14 N 65 W. 21 ft. Drove Iron Pipe  
 E = Birch 12 S. 12 E. 5.7' - Birch 12 S 37 W. 11.5' Drove Iron Pipe  
 F = Birch 10 N 60 E. 5.7' - Birch 12 S 85 W. 21' Drove Iron Pipe  
 G = Basswood - 6 N 50 E. 17.4' - Maple 13 N 35 W. 21' Drove Iron Pipe  
 H = Drove Iron Pipe - No Bgs.