

1" DIAMETER IRON PIPE
FOUND IN PLACE
SEE USPLS MONUMENT RECORD



S 88°54'37"W
1320.76'

2641.52'
1320.76'

CW 1/16 CORNER
COMPUTED POSITION

CENTER OF SECTION
SURVEY MARKER NAIL
FOUND IN PLACE

PARCEL -A-
being part of the
SE 1/4 of the SW 1/4
SECTION 21, T35N, R10E

Town of Enterprise
Oneida County, Wisconsin

SURVEYOR'S CERTIFICATE

I, Theodore G. Sommer, Registered Land Surveyor No. S-2964, hereby certify that I have surveyed the property shown hereon; that this map represents an accurate survey of said property to the best of my knowledge and belief; that I have performed this survey by order of Edward Marquard; and that I have complied with the requirements of Wisconsin Administrative Code A-E 7.


STEIGERWALDT LAND SURVEYING, LLC

Theodore G. Sommer
Registered Land Surveyor No. S-2964
Dated this November 8, 2013



Bearings Oneida County Grid
based on GPS survey data
referenced to the south line of the SW 1/4
Section 21, bearing N 89°17'23"W

MAP # **B 7702**
DATE FILED 3/21/14
BY SA
DESCRIPTION FILED
ONEIDA CO. SURVEYOR'S OFFICE



SCALE: 1" = 200'

LEGEND
○ = set iron pipe, 1.0" dia. x 24" long
▽ = computed position, not monumented
() = bearing and distance of record

Monument sizes are outside diameter.
Other corner monuments are as noted.

NOTE: Legal description provided on a separate sheet.

STEIGERWALDT LAND SURVEYING, LLC

856 NORTH 4TH STREET, TOMAHAWK, WI 54487
PHONE #: (715) 453-3274 FAX #: (715) 453-8325
www.slstomahawk.com

JOB #: 3984

DWG #: 3984

REV:

N 1°30'37"E
1303.79'

S 1/16 CORNER
COMPUTED POSITION

N 89°48'11"E
1310.30'

SW 1/16 CORNER
1.0" DIAMETER X 24" LONG
IRON PIPE SET

NE - SW

NW - SW

-A-
36.9 Acres

DOCUMENT

#565964

N 89°17'23"W
475.60'

DOCUMENT
#413018
V. 224
P. 472

W 1/16 CORNER
COMPUTED POSITION

1300.15'
N 89°17'23"W



SURVEY MARKER NAIL
FOUND IN PLACE
SEE USPLS MONUMENT RECORD

N 1°55'46"E
1124.71'

2649.42'
1324.71'

COUNTY HIGHWAY

"G"

R.O.W. POST BEARS
N 53°27'28"E, 1.09'
FROM SET IP



SURVEY MARKER NAIL
FOUND IN PLACE
SEE USPLS MONUMENT RECORD

R = 5679.58'
A = 134.65'
CB = N 89°19'08"W
LC = 134.64'

R = 5729.58'
A = 485.00'
LC = 484.86'
CB = N 88°56'07"E

WDOT R.O.W.
POST

S 03°29'23"E
50.00'