## LOCATED IN THE SOUTH FRACTIONAL 1/2 - SOUTHWEST 1/4, SECTION 30, **NOT INSPECTED** T37N, R08E, TOWN OF NEWBOLD, ONEIDA COUNTY WI. 1/16TH BY OTHERS **NOT INSPECTED** SURVEYOR'S NOTE: 835.43' (834.64') The lot line re adjustment survey is being completed as the two existing structures and the drainfield have been placed onto NE 321-3. 256.99' (258.04') PARCEL "A" TOWN OF NEWBOLD LOT DESIGN STANDARDS FOR SOO LAKE (SEE BIXBY LAND SURVEYING INC. DWG # 118) Minimum frontage = 225' THIS SURVEY = NO CHANGE SEE V.799 PG 542-543 NOT INSPECTED No. FOR EASEMENT DESCRIPTION Minimum lot area = 90,000 square feet: PROPOSED NE 321-1 = 3.90 ACRE PROPOSED NE 321-3 = 10.03 ACRE NE 321-1 and 321-3 are listed under Phillip and Joanne Frasier in which a quit claim deed is recommended per description as shown on this plat of survey. Town of Newbold C/L 20' WIDE EASEMENT ROAD AS DESCRIBED IN VOLUME 799 PAGE 543 Chapter 13 C land ordinance allows the exchange of land between adjoining land owners as SEE V.799 PG 542-543 AND EXISTING DRIVE WAY long as the remainder parcel is not designed below the minimum standard as set forth in NOT INSPECTED FOR EASEMENT DESCRIPTION The Town Of Newbold's land ordinance. Oneida County lot line/setbacks are being applied. CIL EXISTING DR.WAY PARCEL "C" +-3.90 ACRES BIXBY LAND SURVEYING INC. P.O. BOX 1532 (TO LAKE SHORE) RHINELANDER, WI. 54501 715-362-5263 (LAND) DWG # 705 **SURVEY FOR PHILLIP & JOANNA FRASIER** PARCEL "B" (N 0°43'22"E) 1325.67' N 0°34'35"E\_ (1327.15) +-10.03 ACRES TO LAKE SHORE SCALE: 1" = 100' SEE BIXBY LAND SURVEYING INC DWG # 118 SEE V.799 PG 542-543 100' NOT INSPECTED FOR EASEMENT DESCRIPTION Planning & Zoning Review PROPERTY DESCRIPTION FOR PARCEL "C" **NOT INSPECTED** UME 799 PAGE 543 A parcel of land located in The South Fractional 1/2, of the Southwest 1/4, Section 30, T37N, R08E, Town of Newbold, Oneida County, Wisconsin described as follows: Commencing at the southwest corner of said section 30; thence N00°34'35"E, a distance of 1325.67 feet SCONSIA to a capped iron pipe; thence S84°28'57"E, a distance of 835.43 feet to the point of beginning; thence S84°39'20"E, a distance of 256.99 feet to an iron pipe; thence S02°20'28"W, a distance of 903.01 feet to an iron pipe on the northerly shore of Soo Lake; thence along a meander line along the north shore of Soo Lake, S80°02'06"W, a distance of 147.72 feet to an iron pipe; thence S79°46'41"W, a distance of MAP # 37869 KEVIN P. BIXBY 2.50 feet to an iron pipe; thence leaving said shore and meander line, N02°23'30"E, a distance of 42.00 feet to an iron pipe; thence N48°17'58"W, a distance of 119.83 feet to an iron pipe; thence N23°44'48"E, S-2343 RHINELANDER, EXISTING SANITARY SYSTEM a distance of 117.99 feet to an iron pipe; thence N74°43'28"E, a distance of 52.15 feet to an iron pipe; thence N02°23'53"E, a distance of 561.18 feet to an iron pipe; thence N84°13'54"W, a distance of 160.07 feet to a pk nail; thence N22°29'08"E, a distance of 142.86 feet to the point of beginning. Said parcel contains +-3.90 acres up to the the shore of Soo Lake. Including those lands between the above described meander line and the ordinary high water mark of Soo Lake. Subject to and including easements, restrictions, ONEIDA CO. SURVEYOR'S OFFICE reservations and right-of-ways of record or in use. REVISED ON 03/10/16 TO SHOW PARCEL "A AND "B" DESCRIPTIONS A parcel of land located in the south fractional 1/2, of the southwest 1/4, section 30, T37N, R08E, Town of Newbold, Oneida County, Wisconsin described as follows: I. KEVIN P. BIXBY, PROFESSIONAL LAND SURVEYOR HEREBY CERTIFIY TO MY CLIENT, THAT I HAVE SURVEYED PARCEL "A" THE ABOVE LINE AND THAT THE ABOVE SURVEY IS A TRUE AND CORRECT REPRESENTATION OF THE LINE SURVEYED Commencing at the southwest corner of said section 30; thence N00°34'35"E, a distance of 903.35 feet to a P.K. nail and point of beginning; TO THE BEST OF MY KNOWLEDGE AND BELIEF. THAT I HAVE thence N66°44'33"E, a distance of 64.82 feet to a p.k. nail; thence S76°20'27"E, a distance of 146.07 feet to a p.k. nail; thence S89°30'12"E, a COMPLIED WITH THE MINIMUM REQUIREMENTS OF AE-7 OF distance of 156.68 feet to a p.k. nail; thence N68°42'48"E, a distance of 99.99 feet to a p.k. nail; thence N41°40'58"E, a distance of 132.85 feet THE WISCONSIN ADMINISTRATIVE CODE to a p.k. nail; thence N70°40'08"E, a distance of 255.92 feet to a spike; thence N22°29'08"E, a distance of 142.86 feet to a p.k. nail; thence N84° 28'57"W, a distance of 835.43 feet to an iron pipe; thence S00°34'35"W, a distance of 422.32 feet to the point of beginning. Said parcel contains 5.86 acres. Subject to easements, restrictions, reservations and rights-of-way of record or in use. SW CORNER SECTION 30 A parcel of land located in the south fractional 1/2, of the southwest 1/4, section 30, T37N, R08E, Town of Newbold, Oneida County, **LEGEND** Wisconsin described as follows: ● FOUND 1 1/2" CAPPED IRON PIPE NOTE: PARCEL "B" **■ FOUND P.K. NAIL** Commencing at the southwest corner of said section 30; thence N00°34'35"E, a distance of 903.35 feet to a P.K. nail and point of beginning; The subject line on this plat of survey is the only lot line that has been inspected at this time. thence N66°44'33"E, a distance of 64.82 feet to a p.k. nail; thence S76°20'27"E, a distance of 146.07 feet to a p.k. nail; thence S89°30'12"E, a Parcel's "A" and "B" descriptions and boundary lines are being shown at this time to assist

**⊗** FOUND SPIKE

FOUND 3/4" IRON PIPE

○ FOUND 1" IRON PIPE

( ) RECORDED AS

with future metes and bounds deeds within the Frasier Estate that maybe transfered. The

survey data being utilized is from previous Bixby Land Surveying Inc. data dated 6/20/01

distance of 156.68 feet to a p.k. nail; thence N68°42'48"E, a distance of 99.99 feet to a p.k. nail; thence N41°40'58"E, a distance of 132.85 feet

to a p.k. nail; thence N70°40'08"E, a distance of 255.92 feet to a spike; thence S84°13'54"E, a distance of 160.07 feet to an iron pipe; thence

S02°23'53"W, a distance of 561.18 feet to an iron pipe; thence S74°43'28"W, a distance of 52.15 feet to an iron pipe; thence S23°44'48"W a distance of 117.99 feet to an iron pipe; thence S48°17'58"E,a distance of 119.83 feet to an iron pipe; thence S02°23'30"W, a distance of 42.00

feet to an iron pipe on the northerly shore of Soo Lake; thence along a meander line of said shore, S78°59'51"W, a distance of 231.92 feet to an iron pipe; thence leaving said shore and meander line, N47°22'19"W, a distance of 184.24 feet to an iron pipe; thence N19°33'59"W, a distance

of 70.72 feet to an iron pipe; thence N37°13'14"W, a distance of 109.26 feet to an iron pipe; thence N57°26'13"W, a distance of 147.64 feet to an iron pipe; thence N47°59'52"W, a distance of 443.30 feet to the point of beginning. Said parcel contains 10.03 acres. Including those lands

between the above described meander line and the ordinary high water mark of Soo Lake. Subject to and including easements, restrictions,

reservations and rights-of-way of record or in use.

BEA

9

SSUMED

REFERENCED