


Brass capped 2" dia iron  
pipe found in place  
See U.S.P.L.S. Mon. Rec.



Bearing base assumed,  
referenced to the north line  
of Gov't Lot 2 bearing  
S88°21'54"E

Brass capped 2" dia iron  
pipe found in place  
See U.S.P.L.S. Mon. Rec.



MAP # C1201  
DATE FILED OCT 29, 1995  
BY [Signature]  
DESCRIPTION FILED  
ONEIDA CO SURVEYOR'S OFFICE

E 1/16 CORNER  
2" dia iron pipe  
found in place


KUEHNEMAN  
7.41 Acres

VOL. 774 REC., PGS. 650 & 651

Part of  
**GOV'T. LOTS 2 & 3**  
**SECTION 11, T37N, R6E**

Cassian Township  
Oneida County, Wisconsin  
SURVEYOR'S CERTIFICATE

I, James D. Rein, Registered Land Surveyor No. S-1234, hereby certify that I have surveyed the property shown hereon, that this map represents an accurate survey of said property to the best of my knowledge and belief, that I have performed this survey by order of Steven J. Kuehneman, and that I have complied with the requirements of Wisconsin Administrative Code A-E 7



WILDERNESS  
SURVEYING, INC.

[Signature]  
Registered Land Surveyor # S-1234  
Dated this 30th day of November, 1995

**KUEHNEMAN PARCEL**

A parcel of land in Government Lots 2 and 3, Section 11, Township 37 North, Range 6 East, Cassian Township, Oneida County, Wisconsin, being the "KUEHNEMAN" parcel shown on Map No. 95-170 by Wilderness Surveying, Inc., dated November 30th, 1995, more particularly described as follows:

Beginning at the quarter corner common to Sections 2 and 11, marked by a brass capped iron pipe; thence South 88 degrees 21 minutes 54 seconds East for a distance of 326.42 feet along the north line of Section 11 to an iron pipe; thence South 00 degrees 06 minutes 41 seconds West for a distance of 636.29 feet to an iron pipe on the northerly right of way line of Little Bearskin Road; thence along said northerly right of way line, along a curve to the left, having a radius of 240.95 feet and an arc length of 55.65 feet, being subtended by a chord of South 82 degrees 08 minutes 24 seconds West for a distance of 55.52 feet to an iron pipe; thence continuing along said right of way line South 75 degrees 31 minutes 26 seconds West for a distance of 144.83 feet to an iron pipe; thence continuing along said right of way line, along a curve to the right, having a radius of 140.37 feet and an arc length of 135.80 feet, being subtended by a chord of North 78 degrees 08 minutes 13 seconds West for a distance of 135.48 feet to an iron pipe; thence continuing along said right of way line North 51 degrees 47 minutes 52 seconds West for a distance of 69.13 feet to an iron pipe; thence continuing along said right of way line, along a curve to the left, having a radius of 472.53 feet and an arc length of 136.27 feet, being subtended by a chord of North 60 degrees 03 minutes 34 seconds West for a distance of 135.80 feet to an iron pipe; thence North 00 degrees 06 minutes 41 seconds East for a distance of 556.07 feet to an iron pipe on the north line of Section 11; thence South 88 degrees 19 minutes 59 seconds East for a distance of 173.75 feet along the north line of Section 11 to the place of beginning.

Together with and subject to covenants, easements, and restrictions of record.

Said property contains 7.41 acres.

SCALE 1" = 60'

LEGEND  
 ■ = 2" dia iron pipe found in place  
 ● = 1" dia iron pipe found in place  
 ⊙ = 3/4" dia iron pipe found in place  
 ○ = Iron pipe set, 3/4" dia x 24" long  
 Note: Other corner monuments are as noted

Vol. 716 Rec., Pg. 281

Vol. 718 Rec., Pg. 481

Vol. 292 Deeds, Pg. 597

1/16th line by J.H. Fisher & Associates, see map dated 10/16/79

Map No. 95-170  
File No. 2-11-376  
Drafted by M. Oestreich