C869~ RECEIVED & FILED #.. .. Oneida County Surveyor's Off Date APR 20 1992 OCS Area #. . .... Part of the NW 1/4 of the SE 1/4 SECTION 23, T39N, R6E Minocqua Township Oneida County, Wisconsin SURVEYOR'S CERTIFICATE I, James D Rein, Registered Land Surveyor No S-1234, hereby certify that I have surveyed the property shown hereon, that this map represents an accurate survey of said property to the best of my knowledge and belief, that I have performed this survey by order of Stephen C Dollard, and that I have complied with the requirements of Wisconsin Administrative Code A-E 7 WILDERNESS SURVEYING, -DOLLARD-SHELTER Registered Land Surveyor # 5-1234 | Dated this 18th day of February, 19 2.22 Acres PARKING AREA \$87°49'52''W 708 45' Rec = N86°26'E 707 I' Fleld Book = S86°45'W Note | 1/4" dla iron pipe bears N87°49'52"E 035' Wisconsin Coordinate System North Zone, based on solar observation DOLLARD PARCEL A parcel of land in the Northwest Quarter of the Southeast Quarter, Section 23, Township 39 North, Range 6 East, Minocqua Township, Oneida County, Wisconsin, being the "DOLLARD" parcel ROW Post shown on Map No. 92-06 by Wilderness Surveying, Inc., dated found in place February 18th, 1992, more particularly described as follows Commencing at the Quarter Corner common to Sections 23 and 26, marked by an iron pipe; thence North 03 degrees 23 minutes 53 seconds East (Grid bearing, Wisconsin Coordinate System North Zone) for a distance of 1352.99 feet to the southwest corner of said Northwest Quarter of the Southeast Quarter, being the Center 100' South Sixteenth Corner, marked by an iron pipe, thence continuing North 03 degrees 23 minutes 53 seconds East for a distance of 224.87 feet, along the west line of the Northwest Quarter of the Southeast Quarter to the place of beginning, marked by an iron 100' Rec = 1097' 10970' Thence continuing North 03 degrees 23 minutes 53 seconds East for a distance of 124.28 feet, along the west line of the Rec = 5473' 548 05' Northwest Quarter of the Southeast Quarter, to an iron pipe; 587°29'56''W 657 75' Rec = N86°26 E 657 0' thence North B1 degrees 55 minutes 35 seconds East for a distance of 647.08 feet to the westerly right of way line of U.S. Highway "51", marked by an iron pipe, thence along the westerly right of way line of U.S. Highway "51", along a curve to the right, having CS 1/6 CORNER l 1/2" dla iron pipe a radius of 2764.79 feet and an arc length of 197.41 feet, being found in place subtended by a chord of South 13 degrees 15 minutes 35 seconds West for a distance of 197.37 feet, to an iron pipe; thence South 87 degrees 49 minutes 52 seconds West for a distance of 603.19 feet, to the place of beginning. Together with and subject to covenants, easements and restrictions of record. Said property contains 2.22 acres more or less  $\Theta = 1 1/2$ " dlq iron pipe found in place l 3/4" dia iron pipe found in place See USPLS Mon Rec  $\boxtimes$  = | 1/4" dig iron pipe found in place  $\circ$  = Iron plpe set, 3/4" dia x 24" long  $\Delta$  = Kowalke survey adjusted corner position not monumented (See field book #18, page 45) Note Other corner monuments are as noted Map No. 92-06

File No 10-23-396 Drafted by M Oestreich