SURVEY LANDMARK PRESERVATION RECORD

It is the primary purpose of this record to preserve the location of any survey landmark subject to disturbance, removal or to be rendered inaccessible, as provided by Section 59.74(2), Perpetuation of Landmarks, Wisconsin Revised Statutes.

County:

City, Village, Town:

B 2654A

OMEIDA CO. SURVEYOR'S OFFICE

Section:

Town:

Range:

Oneida

Pine Lake

19

37 North

9 East

Describe survey landmark found or reset and origin if known, such as being a 1/16 corner, called for in a deed or shown on record land survey map or plat, also note location by Gov't. Lot, 1/4-1/4 section or other PLSS subdivisional tract.


P.K. Nail shown on Survey Map No. B4178

DATE FILED...

DESCRIPTION FILED ...

Show approximate location of survey landmark on this Section diagram:

5 1/16 Corner



3708243000

Plan view map of survey landmark location with bearing and distance ties to a minimum of four (4) described witness or reference monuments of concrete, natural stone, metal, live bearing trees or equivalent material and/or described GPS method and precision.

Scale:



See attached plan

Pre-construction

Seal:



PROFESSIONAL LAND SURVEYOR CERTIFICATE:

This survey landmark is being referenced for the express purpose of location preservation and is not intended as an attestment of the legal significance and/or positional accuracy thereof.

Therefore, this survey landmark location should be further evaluated and verified for any future land surveying or related usage purposes.

I, Michael L. Oestreich, hereby certify that I am duly licensed as a Professional Land Surveyor in the State of Wisconsin; that the location of this survey landmark was referenced by me or under my direct supervision and/or control; and that the information shown is true and correct to the best of my knowledge and belief.

signed Michael & Olestreal Date 1/30/09

Bearings Magnetic

NW Corner S19, T37N, R9E R/R spike 0.5" dia. x 24" iron rod set P.K. Nail N 1/16 Corner P.K. Nail 1.3" dia. IP P.K. Nail P.K. Nail W 1/4 Corner 19, T37N, R9E R/R spike 0.5" dia. x 24" iron rod set

SURVEY LANDMARK PRESERVATION RECORD

Date July 30th, 2009

Scale 1"= 300'