

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
DEPENDENT RESURVEY
OF A PORTION OF THE WEST BOUNDARY,
AND A PORTION OF THE SUBDIVISIONAL LINES;
A CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE WEST BOUNDARY,
AND A PORTION OF THE SUBDIVISIONAL LINES;
A CORRECTIVE RESURVEY
OF THE SUBDIVISION OF SECTION 20;
AND THE SURVEY OF THE SUBDIVISION
OF SECTIONS 15, 16, 17, 21, AND 22
OF
TOWNSHIP 35 NORTH, RANGE 12 EAST,
OF THE 4TH PRINCIPAL MERIDIAN
IN THE STATE OF WISCONSIN

EXECUTED BY

Travis M. Hand
Cadastral Surveyor

Under special instructions dated *April 4, 2007*, approved *April 5, 2007*, which provide for the surveys included under Group Number 180, and assignment instructions dated *April 5, 2007*, and supplemental special instructions dated *September 21, 2007*.

Survey commenced *April 17, 2007*
Survey completed *September 27, 2007*

INDEX DIAGRAM

Township 35 North, Range 12 East

6	5	4	3	2	1
7	8	9	10	11	12
	33	25	18		
18	32	17	23	16	16
31	30	22	14	9	14
4	19	29	20	20	21
	29	28	18	12	22
				6	23
2	30	27	29	28	27
				26	25
31	32	33	34	35	36

Adjusted Record Meanders Sec. 22 Pg. 35
 Sub. of Secs. 15 - 17 Pg. 35 - 45
 Corrective Sub. of Sec. 20 Pg. 45 - 47
 Sub. of Secs. 21 and 22 Pg. 47 - 49

TOWNSHIP 35 NORTH, RANGE 12 EAST
FOURTH PRINCIPAL MERIDIAN, WISCONSIN

CHAINS

The following field notes are those of the dependent resurvey of a portion of the west boundary, and a portion of the subdivisional lines; a corrective dependent resurvey of a portion of the west boundary, and a portion of the subdivisional lines; a corrective resurvey of the subdivision of section 20; and the survey of the subdivision of sections 15, 16, 17, 21, and 22, Township 35 North, Range 12 East, of the 4th Principal Meridian, in the State of Wisconsin.

The history of previous surveys is as follows:

Alfred Millard, Deputy Surveyor, surveyed the exterior boundaries of the township, under contract dated June 30, 1857.

James L. Nowlin and Hardin Nowlin, Deputy Surveyors, surveyed the subdivisional lines, under a joint contract dated August 11, 1864.

Scott McIntyre, Cadastral Surveyor, dependently resurveyed a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of sec. 20, under Group No. 109, Wisconsin, dated June 15, 1978.

Richard Widmar, Cadastral Surveyor, performed a corrective dependent resurvey of a portion of the subdivisional lines, under Group No. 109, Wisconsin, dated May 26, 1983.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 180, Wisconsin dated April 4, 2007, and Assignment Instructions dated April 5, 2007, and Supplemental Special Instructions dated September 21, 2007.

Preliminary to the resurvey, the lines of the original survey were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of the lines of this survey refers to the true meridian, and were determined by static observations using survey grade Global Position System (GPS) receivers or hour angle observations of the sun. The measurements of these lines were made with an electronic total

TOWNSHIP 35 NORTH, RANGE 12 EAST
FOURTH PRINCIPAL MERIDIAN, WISCONSIN

CHAINS

station with periodic solar observations taken throughout the progress of the survey, and by direct static observations with GPS receivers.

Ties to original calls of topography not directly measured as described above, were digitally scaled from color Digital Ortho Quarter Quads (DOQQ) obtained from the U.S. Department of Agriculture-Farm Service Agency-Aerial Photography Field Office. The source image date for these DOQQ's is given as 2005.

A magnetic marker, which is referred to as a "DEEP-1" in these notes, was deposited at the base of each monument, so indicated. This marker consists of a magnet, 1 in. long, 7/8 in. diam., housed in a cellulose acetate tube, 2 5/8 ins. long, 1 in. diam., with 1 in. sq. polyethylene end caps.

The geographic position of the cor. of secs. 22, 23, 26, and 27 as determined by Global Positioning System (GPS) observations, utilizing an Ashtech Locus GPS receiver positioned over the top of the monument, is as follows:

Latitude: 45°29'37.85" N.
Longitude: 88°57'50.67" W. "NAD 83"

The mean magnetic declination as determined from numerous readings throughout the survey, is 1° East.

Dependent Resurvey of a
Portion of the West Boundary
T. 35 N., R. 12 E., 4th Prin. Mer., Wisconsin

From the 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., in the center line of West County Line Rd., as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin; monumented with a spike, 1/4 in. diam., firmly set, 2 ins. below the gravel surface.

Note: the 1 in. diam., iron pipe called for in the 1978 resurvey has been obliterated, presumably by road construction.

from which the 1978 accessories

DEPENDENT RESURVEY OF A
PORTION OF THE WEST BOUNDARY
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

An aluminum post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, bears West, 70.0 lks. dist., with an aluminum cap mkd. as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin.

A maple, 11 ins. diam., bears S. 52° W., 94.0 lks. dist., mkd. with healed base and breast height blazes.

A maple, 10 ins. diam., bears N. 78° W., 56.0 lks. dist., mkd. with healed base and breast height blazes.

An embedded mound of stone, 24 ins. diam., bears West, 29.0 lks. dist. There is no remaining evidence of the 4 ins. diam. wood post called for in the 1978 dependent resurvey.

From this cor., an iron pipe, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a collar of stone, bears S. 83° 58' E., 36.1 lks. dist., with an aluminum cap mkd. WIT COR COR 23' WEST 1/4 25 30 T35N R11E R12E WFK.

Not remonumented.

N. 0° 07' W., bet. secs. 25 and 30.

40.139 Point for the cor. of secs. 19, 24, 25, and 30, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.

From this point, the point for the cor. of secs. 19, 24, 25, and 30, mistakenly established in the 1978 dependent resurvey, bears East, 12.7 lks. dist., not monumented.

From this same point, an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, bears N. 24° 02' E., 59.9 lks. dist.

Also from this same point, an iron pipe, 1 in. diam., firmly set, flush with the ground, bears S. 32° 29' W., 75.6 lks. dist.

Also from this same point, an iron pipe, 1 1/4 ins. diam., firmly set, flush with the asphalt surface of County Highway "M", bears S. 33° 01' W, 1.7 lks. dist. This cor. was mistakenly established using improper control, by James L. Will, Registered Land Surveyor No. 1410, in 1985, and was not utilized in the course of this survey.

DEPENDENT RESURVEY OF A
PORTION OF THE WEST BOUNDARY
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

Also from this same point, an iron rod, 3/4 ins. diam., firmly set, projecting 2 ins. above the ground, with a 1 in. diam. plastic cap mkd. MIKE TREML S-2197, bears N. 83°27' W., 51.2 lks. dist.

Also from this same point, an iron pipe, 1 in. diam., firmly set, projecting 1 in. above the ground, bears N. 36°55' W., 94.6 lks. dist.

N. 0°07' W., bet. secs. 19 and 24.

40.139 Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.

From this point, the 1/4 sec. cor. of secs. 19 and 24, mistakenly established in the 1978 dependent resurvey, bears East, 25.3 lks. dist., not monumented.

From this same point, an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above the ground, bears S. 82°26' E., 55.5 lks. dist.

Also from this same point, an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above the ground, bears S. 38°59' E., 63.8 lks. dist.

Also from this same point, a PK MAGNAIL, 1/4 in. diam., firmly set, flush with the asphalt surface of County Highway "M", bears S. 41°50' W., 3.0 lks. dist. This cor. was mistakenly established using improper procedures, by James L. Will, Registered Land Surveyor No. 1410, in 1985, and was not utilized in the course of this survey.

Also from this same point, an iron pipe, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with an aluminum cap mkd. T35N R11E R12E S24 S19 1/4 WIT COR 33.0' EAST S-1410, bears N. 87°43' W., 51.9 lks. dist.

Also from this same point, an iron pipe, 1 in. diam., firmly set, projecting 1 in. above the ground, bears N. 44°01' W., 77.5 lks. dist.

80.278 The cor. of secs. 13, 18, 19, and 24, determined at record bearing and dist. from the remains of a witness cor. set by I. R. Ritter, Forest County Surveyor, in 1920. This position is accepted as the best available evidence of the original cor., not monumented.

DEPENDENT RESURVEY OF A
PORTION OF THE WEST BOUNDARY
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

From this cor., the cor. of secs. 13, 18, 19, and 24., mistakenly accepted in the 1978 dependent resurvey, bears East, 38.0 lks. dist. This point was established by I. R. Ritter as a witness cor. in 1920, monumented with an embedded mound of stone, 24 ins. in diam., with remains of decayed and buried barbed wire fence extending N., S. and E. The wood post called for in the 1978 survey is no longer in existence.

From this same cor., an iron pipe, 1 3/4 ins. diam., firmly set, projecting 6 ins. above the ground, bears N. 86°45' E., 47.4 lks. dist.

Also from this same cor., an iron pipe, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with an aluminum cap mkd. REF MARK N43E 39.72 FT., bears S. 47°10' W., 61.1 lks. dist. This point was established as a reference monument by William C. Rohde, Registered Land Surveyor No. 841, in 1999, to a cor. that was improperly established by William F. Kelly, Registered Land Surveyor No. 1098, in 1984

Also from this same cor., an iron pipe, 2 1/2 ins. diam., firmly set, 3 ins. below the ground, with an aluminum cap mkd. REF MARK S45E 31.90 FT., bears N. 45°23' W., 52.1 lks. dist. This point was established as a reference monument by William C. Rohde, Registered Land Surveyor No. 841, in 1999, to a cor. that was improperly established by William F. Kelly, Registered Land Surveyor No. 1098, in 1984.

Also from this same cor., an iron rod, 3/4 ins. diam., firmly set, flush with the asphalt surface of County Highway "M", bears N. 57°46' W., 3.7 lks. dist. This cor. was mistakenly established, by William F. Kelly, Registered Land Surveyor No. 1098, in 1984, and perpetuated by William C. Rohde, Registered Land Surveyor No. 841, in 1999, and was not utilized in the course of this survey.

This cor. is located in the center line of County Highway "M", bearing N. and S., and the center line of Max Rd., bearing W.

Dependent Resurvey of a
Portion of the Subdivisional Lines
T. 35 N., R. 12 E., 4th Prin. Mer., Wisconsin

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

From the cor. of secs. 22, 23, 26, and 27, monumented with an aluminum post, 2 ½ ins. diam., firmly set, projecting 5 ins. above the ground, with an aluminum cap mkd. as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin.

This cor. was further perpetuated by Thomas R. Arnott, Registered Land Surveyor No. 887, in 1989.

from which the bearing trees not of record in the 1978 survey

A spruce stump, 9 ins. diam., bears N. 52° E., 7.0 lks. dist.

A spruce, standing dead, 5 ins. diam., bears S., 51.0 lks. dist., mkd. with a healed blaze at the base.

from which the 1978 bearing trees

A tamarack, 7 ins. diam., bears S. 35° W., 22.0 lks. dist., mkd. with a healed blaze at the base. (Record: a spruce, bears S. 24° W., 22.0 lks. dist.)

A spruce, 5 ins. diam., bears N. 50° W., 15.0 lks. dist., mkd. with healed blazes at base and breast height.

from which Arnott's bearing tree

A tamarack, 7 ins. diam., bears N. 36° E., 13.7 lks. dist., mkd. with healed blazes at base and breast height.

and a new bearing tree

A spruce, 6 ins. diam., bears S. 29° E., 18.6 lks. dist., mkd. T35N R12E S26 BT.

Not remonumented.

N. 2°27' W., bet. secs. 22 and 23.

43.777

The 1/4 sec. cor. of secs. 22 and 23, monumented with an aluminum post, 2 ½ ins. diam., firmly set, projecting 5 ins. above the ground, with an aluminum cap mkd. as described in the official record of the 1978

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

dependent resurvey, executed under Group No. 109, Wisconsin.

from which the remains of an original bearing tree

A decayed cedar stump, 20 ins. diam., bears S. 50° E., 18.0 lks. dist.

from which the 1978 bearing trees

A spruce, 7 ins. diam., bears S. 80° E., 16.0 lks. dist., mkd. 1/4 S23 BT.

A cedar, 8 ins. diam., bears N. 28° W., 18.0 lks. dist., mkd. with a healed blaze at the base.

Alongside of which, an iron pipe, 1 ½ ins. diam., firmly set, projecting 26 ins. above the ground, a wood post 5 x 5 ins. square, loosely set, projecting 7 ins. above the ground, and a wood post, 2 x 2 ins. square, loosely set, projecting 7 ins. above the ground.

Not remonumented.

N. 8° 10' E., beginning new measurement.

18.150 Leave swamp, edge bears E. and W.

19.519 Point for the N. 1/16 sec. cor. of secs. 22 and 23.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", with a brass cap mkd.

N 1/16
S 22 | S 23
2007

from which

A cedar, 9 ins. diam., bears S. 7° W., 102.3 lks. dist., mkd. N1/16 S22 BT.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A balsam, 6 ins. diam., bears S. 51° W., 98.7 lks. dist., mkd. BT at the base and X at breast height.

39.038

The cor. of secs. 14, 15, 22, and 23, monumented by persons unknown, and perpetuated by William F. Kelly, Registered Land Surveyor No. 1098, in 1983, monumented with an iron pipe, 2 ½ ins. diam., firmly set, 1 in. below the surface. This position having long been recognized as the proper cor., is judged to be the best attainable evidence of the original cor. position. Note: The aluminum cap has been knocked off and is buried alongside the 2 ½ ins. diam. iron pipe, mkd. SECT COR 15 14 22 23 T35N R12E.

from which Kelly's bearing trees

A maple stump, 19 ins. diam., bears N. 18° E., 47.0 lks. dist., mkd. with a healed blaze at the base.

A maple, 16 ins. diam., bears N. 53° W., 79.6 lks. dist., mkd. with healed base and breast height blazes.

A maple, 13 ins. diam., bears N. 45° W., 94.0 lks. dist., mkd. with healed blazes at base and breast height.

A maple, 12 ins. diam., bears N. 24° W., 87.4 lks. dist., mkd. with healed blazes at base and breast height.

Not remonumented.

This cor. is 2 lks. S. of the center line of a 20 lks. wide two track road, bearing E. and W.

Mr. Kelly recovered an iron pipe, 1 in. diam., and buried it alongside the 2 ½ ins. diam. iron pipe.

N. 0°47' W., bet. secs. 14 and 15.

28.700

Enter swamp, edge bears E. and W.

39.100

Leave swamp, edge bears E. and W.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

39.975 The 1/4 sec. cor. of secs. 14 and 15, established at proportionate dist. by Michael L. Treml, Registered Land Surveyor No. 2197, in 2005, monumented with an aluminum pipe, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with an aluminum cap mkd.

T 35 N R 12 E
1/4
S 15 | S 14
2005
S-2197

from which Treml's bearing trees

A balsam, 6 ins. diam., bears N. 29° E., 32.1 lks. dist., mkd. BT at the base and X at breast height.

A cedar, 6 ins. diam., bears S. 35° E., 33.7 lks. dist., mkd. BT at the base and X at breast height.

A spruce, 10 ins. diam., bears S. 51° W., 28.6 lks. dist., mkd. BT at the base and X at breast height.

A cedar, 8 ins. diam., bears N. 34° W., 22.5 lks. dist., mkd. BT at the base and X at breast height.

Not remonumented.

79.950 The cor. of secs. 10, 11, 14, and 15, monumented by persons unknown, and perpetuated by William F. Kelly, Registered Land Surveyor No. 1098, in 1983, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above the ground, in a collar of stone, with an aluminum cap mkd.

SECT COR
15 | 14

22 | 23
T 35 N R 12 E

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

This position having long been recognized as the proper cor., is judged to be the best attainable evidence of the original cor. position.

Note: the aluminum cap on this monument is incorrectly mkd.

from which Kelly's bearing trees

A maple, 12 ins. diam., bears N. 59° E., 51.7 lks. dist., mkd. with healed blazes at base and breast height.

A maple, 11 ins. diam., bears N. 84° E., 49.0 lks. dist., mkd. with healed blazes at base and breast height.

A maple, 18 ins. diam., bears S. 68° E., 63.6 lks. dist., mkd. with healed blazes at base and breast height.

A maple stump, 12 ins. diam., bears N. 86° W., 50.6 lks. dist., mkd. with a nail in the base.

Not remonumented.

From the cor. of secs. 21, 22, 27, and 28, monumented with an aluminum post, 2 ½ ins. diam., firmly set, projecting 10 ins. above the ground, with an aluminum cap mkd. as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin.

from which the remains of an original bearing tree

A white pine stump, bears S. 55° W., 10 lks. dist., with a wood post, 4 x 4 ins. sq., in the center of the stump, mkd. OBT.

from which the bearing trees not of record in the 1978 survey

A white pine, standing dead, 21 ins. diam., bears S. 21° E., 60.0 lks. dist., mkd. with a healed blaze at the base.

A spruce snag, 9 ins. diam., bears N. 9° W., 22.0 lks. dist.

A wood post, 4 x 4 ins. sq., bears N. 45° E., 1.0 lks. dist., loosely set, projecting 15 ins. above the ground, mkd. SC.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

from which the 1978 bearing trees

A balsam, 10 ins. diam., bears N. 47° E., 28.0 lks. dist., mkd. with a healed blaze at the base. (Record: spruce)

An aspen stump, 7 ins. diam., bears S. 89° E., 42.0 lks. dist.

An aspen stump, 10 ins. diam., bears S. 23° W., 12.0 lks. dist.

An aspen stump, 10 ins. diam., bears N. 49° W., 31.0 lks. dist., mkd. with a healed blaze at the base.

and new bearing trees

A maple, 8 ins. diam., bears S. 59° E., 18.2 lks. dist., mkd. BT at the base and X at breast height.

A maple, 11 ins. diam., bears S. 51° W., 60.7 lks. dist., mkd. T35N R12E S28 BT.

An oak, 13 ins. diam., bears N. 72° W., 57.7 lks. dist., mkd. T35N R12E S21 BT.

Not remonumented.

East, on record bearing, bet. secs. 22 and 27.

28.500 Point for the meander cor. of secs. 22 and 27, at record dist.; there is no remaining evidence of the original cor.

Set an aluminum sectional rod, 72 ins. long, 3/4 ins. diam., driven 62 ins. in the ground, with a "DEEP-1" alongside, with an aluminum cap mkd.

T 35 N	
S 22	

S 27	MC
R 12 E	
2007	

from which

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A tamarack, 7 ins. diam., bears N. 65° E., 69.8 lks. dist., mkd. BT at the base and X at breast height.

A tamarack, 7 ins. diam., bears S. 82° E., 58.4 lks. dist., mkd. BT at the base and X at breast height.

This cor. is located 85 lks. West of the westerly shore of Rice Lake.

From the cor. of secs. 21, 22, 27, and 28.

N. 1° 36' E., bet. secs. 21 and 22.

38.850 Enter swamp, edge bears SE and NW.

40.195 The 1/4 sec. cor. of secs. 21 and 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, in a collar of stone, projecting 5 ins. above the ground, with an aluminum cap mkd. as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin.

from which the remains of original bearing trees

A cedar stump, 24 ins. diam., bears N. 80° E., 12.0 lks. dist., mkd. with a scarred face.

A decayed cedar stump, bears N. 55° W., 18.0 lks. dist.

from which the 1978 bearing trees

A birch snag, 8 ins. diam., bears N. 75° E., 29.0 lks. dist., mkd. with a rotted blaze at the base with illegible scribing.
(Record: S. 53° W.)

A decayed spruce stump, bears S. 53° W., 34.0 lks. dist.
(Record: N. 75° E.)

and new bearing trees

A cedar, 9 ins. diam., bears S. 16° W., 43.6 lks. dist., mkd. 1/4 S21 BT.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A cedar, 8 ins. diam., bears N. 74° W., 33.5 lks. dist., mkd. BT at the base and X at breast height.

Not remonumented.

N. 4°21' E., beginning new measurement.

17.150 Creek, 10 lks. wide, course SE.

41.558 The cor. of secs. 15, 16, 21, and 22., perpetuated by T. Kauppinen, Surveyor for Wisconsin Conservation Department, in 1938, and further perpetuated by William F. Kelly, Registered Land Surveyor No. 1098, in 1983, monumented with an iron pipe, 2 ½ ins. diam., firmly set, projecting 18 ins. above the ground, with an aluminum cap mkd.

SEC COR	
16	15
21	22

from which the remains of original bearing trees

A decayed hemlock stump, bears N. 23° E., 25.0 lks. dist.

A decayed hemlock stump, bears N. 48° W., 15.0 lks. dist.

from which Kelly's bearing trees

A cedar, 11 ins. diam., bears N. 18° E., 67.3 lks. dist., mkd. with a healed blaze at the base, and an open breast height blaze mkd. BT.

A cedar, 20 ins. diam., bears S. 46° E., 61.0 lks. dist., mkd. with a steel washer, 1 in. diam., in an open base blaze, and an open breast height blaze mkd. BT.

A spruce, 12 ins. diam., bears N. 72° W., 41.5 lks. dist., mkd. with a steel washer, 1 in. diam., in an open base blaze, and an open breast height blaze mkd. BT.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A spruce, 15 ins. diam., bears N. 43° W., 56.5 lks. dist., mkd. with rotted blazes at base and breast height.

Not remonumented.

Recovered the wood post, 5 x 5 ins. sq., with an aluminum location tag, set by T. Kauppinen, in 1938, and buried it alongside the 2 ½ ins. diam. iron pipe.

From the cor. of secs. 14, 15, 22, and 23.

N. 89° 10' W., bet. secs. 15 and 22.

16.600 Enter swamp, edge bears N. and S.

38.750 Leave swamp, edge bears NE and SW.

39.470 The 1/4 sec. cor. of secs. 15 and 22, monumented by persons unknown, with an iron pipe, 1 ¾ ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone.

from which the remains of original bearing trees

A decayed cedar stump, bears N. 50° E., 12.0 lks. dist.

A stump hole, bears S. 52° W., 32.0 lks. dist.

At the cor. point.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

T 35 N R 12 E
S 15
1/4 —————
S 22
2007

from which

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A maple, 7 ins. diam., bears N. 28° E., 21.1 lks. dist., mkd.
1/4 S15 BT.

A cedar, 11 ins. diam., bears S. 46° E., 39.0 lks. dist., mkd.
1/4 S22 BT.

Bury the iron pipe alongside the stainless steel post.

S. 89°03' W., beginning new measurement.

19.978 Point for the W. 1/16 sec. cor. of secs. 15 and 22.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the
ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

S 15
W 1/16 —————
S 22
2007

from which

A maple, 8 ins. diam., bears S. 20° W., 26.4 lks. dist., mkd.
W1/16 S22 BT.

A maple, 9 ins. diam., bears N. 32° W., 56.6 lks. dist., mkd.
W1/16 S15 BT.

29.500 Enter swamp, edge bears NE and SW.

39.956 The cor. of secs. 15, 16, 21, and 22.


N. 0°02' E., bet. secs. 15 and 16.

33.000 Leave swamp, edge bears NE and SW.

39.362 The 1/4 sec. cor. of secs. 15 and 16, established at proportionate dist., by
William F. Kelly, Registered Land Surveyor No. 1098, in 1983,
monumented with an iron pipe, 2 ½ ins. diam., firmly set, in a collar of
stone, projecting 8 ins. above the ground, with an aluminum cap mkd.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS



from which Kelly's bearing trees

A spruce snag, 6 ins. diam., bears S. 10° E., 33.1 lks. dist., with a nail in the base.

An aspen snag, 10 ins. diam., bears S. 48° W., 10.4 lks. dist., mkd. with rotted blazes at base and breast height.

An aspen stump, 20 ins. diam., bears S. 89° W., 39.1 lks. dist.

A spruce stump, bears N. 19° W., 49.0 lks. dist., mkd. with a nail in the base.

A spruce stump, bears N. 5° W., 32.6 lks. dist., mkd. with a nail in the base.

and new bearing trees

A spruce, 7 ins. diam., bears S. 20° E., 29.2 lks. dist., mkd. 1/4 S15 BT.

A cedar, 6 ins. diam., bears S. 88° W., 51.4 lks. dist., mkd. BT at the base and X at breast height.

Not remonumented.

59.043 The N. 1/16 sec. cor. of secs. 15 and 16, established at proportionate dist., by William F. Kelly, Registered Land Surveyor No. 1098, in 1989, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 8 ins. above the ground.

At the cor. point.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

N 1/16
S 16 | S 15
2007

from which

A maple, 11 ins. diam., bears S. 69° E., 98.0 lks. dist., mkd.
N1/16 S15 BT.

A maple, 6 ins. diam., bears S. 36° E., 109.2 lks. dist., mkd. BT at
the base and X at breast height.

Bury the iron pipe alongside the stainless steel post.

78.724 The cor. of secs. 9, 10, 15, and 16, perpetuated by William F. Kelly,
Registered Land Surveyor No. 1098, in 1983, monumented with an
aluminum post, 2 ½ ins. diam., firmly set, projecting 4 ins. above the
ground, with an aluminum cap mkd.

SECT	COR
9	10
16	15
T35N	R12E

This position having long been recognized as the proper cor., is judged
to be the best attainable evidence of the original cor. position.

from which Kelly's bearing trees

A maple, 10 ins. diam., bears N. 34° E., 96.6 lks. dist., mkd. with
healed blazes at base and breast height.

A maple stump, 6 ins. diam., bears N. 78° E., 57.2 lks. dist.

A maple, 18 ins. diam., bears N. 3° W., 37.2 lks. dist., mkd. with
a healed breast height blaze.

Not remonumented.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

This cor. is located at the S. end of a dilapidated fence, with decayed wood posts, downed wire, and loose stones piled approximately 36 ins. wide, and 18 ins. high extending N.

Mr. Kelly recovered a wood post, 4 x 4 ins. sq., and buried it alongside the 2 ½ ins. diam. aluminum post.

From the cor. of secs. 10, 11, 14, and 15.

S. 89°03' W., bet. secs. 10 and 15.

18.637 From this point, an iron rod, 1 in. diam., firmly set, projecting 12 ins. above the ground, bears N., 28.8 lks. dist.

39.136 Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.

58.704 Point for the W. 1/16 sec. cor. of secs. 10 and 15, not monumented.

From this point, an iron pipe, 1 3/4 ins. diam., loosely set, projecting 9 ins. above the ground, bears S. 79°31' E., 10.5 lks. dist.

78.272 The cor. of secs. 9, 10, 15, and 16.

From the cor. of secs. 21, 22, 27, and 28.

S. 89°06' W., bet. secs. 21 and 28.

37.150 Enter swamp, edge bears N. and S.

40.256 The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 14 ins. above the ground, as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin.

from which the remains of original bearing trees

A decayed spruce stump, bears N. 27° E., 12.0 lks. dist.

A decayed spruce stump, bears S. 9°30' W., 28.0 lks. dist.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

from which the bearing trees not of record in the 1978 survey

A spruce stump, 8 ins. diam., bears N. 59° W., 9.5 lks. dist., mkd. with a rotted blaze at base.

A spruce, standing dead, 8 ins. diam., bears N. 9° W., 13.5 lks. dist., mkd. 1/4 S in a partially decayed blaze at the base.

and new bearing trees

A spruce, 7 ins. diam., bears N. 16° E., 41.5 lks. dist., mkd. 1/4 S21 BT.

A tamarack, 8 ins. diam., bears S. 34° E., 13.3 lks. dist., mkd. 1/4 S28 BT.

Not remonumented.

This cor. is located at the intersection of dilapidated fences, with decayed wood fence posts and downed wire extending S. and E.

S. 88°33' W., beginning new measurement.

39.698 The cor. of secs. 20, 21, 28, and 29, monumented with an aluminum post, 2 ½ ins. diam., firmly set, projecting 7 ins. above the ground, with an aluminum cap mkd. as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin.

from which the 1978 bearing trees

A decayed spruce stump, 10 ins. diam., bears N. 40° E., 24.0 lks. dist.

A decayed spruce stump, 8 ins. diam., bears S. 64° E., 20.0 lks. dist.

A decayed spruce stump, 6 ins. diam., bears S. 58° W., 24.0 lks. dist.

A decayed spruce stump, 4 ins. diam., bears N. 23° W., 26.0 lks. dist.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

and new bearing trees

A tamarack, 10 ins. diam., bears N. 88° E., 96.5 lks. dist., mkd.
T35N R12E S21 BT.

A cedar, 11 ins. diam., bears S. 13° E., 57.8 lks. dist., mkd.
T35N R12E S28 BT.

A spruce, 5 ins. diam., bears S. 57° W., 46.7 lks. dist., mkd. BT at
the base and X at breast height.

A cedar, 10 ins. diam., bears N. 27° W., 67.0 lks. dist., mkd.
T35N R12E S20 BT.

Not remonumented.

N. 3°38' E., bet. secs. 20 and 21.

3.000 Leave swamp, edge bears E. and W.

15.000 Enter swamp, edge bears NE and SW.

34.500 Leave swamp, edge bears NE and SW.

40.541 The 1/4 sec. cor. of secs. 20 and 21, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, in a collar of stone, projecting 9 ins. above the ground, with an aluminum cap mkd. as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin.

from which the 1978 bearing trees

An aspen, 10 ins. diam., bears S. 60° E., 14.0 lks. dist., mkd. with
healed blazes at base and breast height.

An aspen snag, 11 ins. diam., bears N. 31° W., 29.0 lks. dist.,
mkd. with a decayed blaze at the base.

and new bearing trees

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN


CHAINS

A maple, 8 ins. diam., bears N. 79° E., 73.0 lks. dist., mkd.
1/4 S21 BT.

A maple, 9 ins. diam., bears N. 49° W., 34.4 lks. dist., mkd.
1/4 S20 BT.

N. 3° 31' E., beginning new measurement.

41.375 The cor. of secs. 16, 17, 20, and 21, described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin, and perpetuated by persons unknown, monumented with an aluminum rod, 1 in. diam., firmly set, projecting 12 ins. above the ground, with an aluminum cap mkd.



from which local bearing trees not of record

An aspen, 7 ins. diam., bears S. 65° E., 24.2 lks. dist., mkd. with a nail in the center of an open blaze at the base, and with an open breast height blaze.

A balsam, 9 ins. diam., bears N. 41° W., 45.5 lks. dist., mkd. with a nail in the center of an open blaze at the base, and with an open breast height blaze.

A balsam, 14 ins. diam., bears N. 21° W., 41.5 lks. dist., mkd. with a nail in the center of an open blaze at the base, and with an open breast height blaze.

and new bearing trees

An aspen, 10 ins. diam., bears N. 72° E., 14.9 lks. dist., mkd.
T35N R12E S16 BT.

A maple, 6 ins. diam., bears S. 42° E., 135.0 lks. dist., mkd.
T35N R12E S21 BT.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A maple, 15 ins. diam., bears S. 9° W., 68.5 lks. dist., mkd. T35N R12E S20 BT.

The wood post called for in the 1978 resurvey was recovered and buried alongside the aluminum rod.

From the cor. of secs. 15, 16, 21, and 22.

S. 88°55' W., bet. secs. 16 and 21.

12.150 Leave swamp, edge bears N. and S.

19.783 From this point, an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground, bears N., 1.2 lks. dist.

39.546 Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

T 35 N R 12 E
S 16
1/4 —————
S 21
2007

from which

A yellow birch, 10 ins. diam., bears N. 72° E., 31.3 lks. dist., mkd. 1/4 S16 BT.

A maple, 14 ins. diam., bears S. 13° W., 52.0 lks. dist., mkd. 1/4 S21 BT.

From this cor., an iron pipe, 1 in. diam., firmly set, flush with the ground, bears N. 36°31' W., 4.2 lks. dist. This position was monumented by William F. Kelly, Registered Land Surveyor No. 1098, in 1989 at a point that was intended to be at midpoint from controlling cors. E. and W.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

59.305 From this point, an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above the ground, bears N., 1.7 lks. dist.

79.092 The cor. of secs. 16, 17, 20, and 21.

N. 0°47' E., bet. secs. 16 and 17.

20.165 Point for the S. 1/16 sec. cor. of secs. 16 and 17.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

S 1/16
S 17 | S 16
2007

from which

A maple, 11 ins. diam., bears S. 75° E., 27.2 lks. dist., mkd.
S1/16 S16 BT.

A maple, 10 ins. diam., bears N. 53° W., 35.3 lks. dist., mkd.
S1/16 S17 BT.

40.330 The 1/4 sec. cor. of secs. 16 and 17, monumented with the tip of a wood post, 3 in. diam., 13 ins. long, 3 ins. below the surface of an abandoned dry beaver pond.

from which the remains of an original bearing tree

A dim stump hole, with decayed wood fragments, bears
N. 52° W., 12.0 lks. dist.

At the cor. point.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

T 35 N R 12 E
1/4
S 17 | S 16
2007

from which

A spruce, 11 ins. diam., bears S. 32° W., 137.6 lks. dist., mkd.
1/4 S17 BT.

A tamarack, 5 ins. diam., bears S. 72° W., 106.7 lks. dist., mkd.
BT at the base and X at breast height.

Bury the tip of wood post alongside the stainless steel post.

This cor. is located at the intersection of dilapidated fences, with
decayed wood fence posts and downed wire extending N., S. and E.

From this cor., an iron pipe, 1 in. diam., firmly set, projecting 6 ins.
above the ground, bears S. 28°33' W., 84.5 lks. dist., alongside of which
is a wood post, 4 x 4 ins. sq., 72 ins. long, lying on the ground. This
monument was established using improper procedures and was not
utilized in the course of this survey.

N. 0°11' W., beginning new measurement.

19.408 Point for the N. 1/16 sec. cor. of secs. 16 and 17.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 24 ins. in the
ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

N 1/16
S 17 | S 16
2007

from which

A maple, 8 ins. diam., bears S. 45° E., 55.2 lks. dist., mkd. N1/16
S16 BT.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A maple, 10 ins. diam., bears S. 42° W., 31.7 lks. dist., mkd. N1/16 S17 BT.

- 38.816** The cor. of secs. 8, 9, 16, and 17, reestablished and recorded by Philip T. Hansen, Registered Land Surveyor No. 498, in 1977, and perpetuated by Jeffrey Kip Inman, Registered Land Surveyor No. 1676, in 2001. There is no remaining evidence of the original monument, however, this position is accepted as a careful and faithful reestablishment of the original cor. position.

Note: The railroad spike and accessories established by Mr. Hansen have been obliterated, presumably by road construction. This position was reestablished from found monuments of Inman's 2001 survey.

From this cor., an iron rod, 3/4 ins. diam., firmly set, projecting 14 ins. above the ground, bears S. 0°35' E., 199.9 lks. dist.

From this same cor., a concrete post, 12 ins. diam., firmly set, flush with the ground, with an aluminum disc mkd. WISCONSIN DEPT TRANS. UNLAWFUL TO DISTURB, bears N. 15°36' W., 183.7 lks. dist.

Not monumented.

From the cor. of secs. 9, 10, 15, and 16.

S. 89°13' W., bet. secs. 9 and 16.


- 19.671** Point for the E. 1/16 sec. cor. of secs. 9 and 16, not monumented.

From this cor., an iron pipe, 1 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, bears N. 23°46' W., 4.0 lks. dist.

- 39.342** The 1/4 sec. cor. of secs. 9 and 16, established at proportionate dist. by William F. Kelly, Registered Land Surveyor No. 1098, in 1983; Monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with an aluminum cap mkd.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS



from which Kelly's bearing trees

An aspen snag, 10 ins. diam., bears N. 11° E., 34.5 lks. dist., mkd. with a healed breast height blaze.

An aspen stump, 12 ins. diam., bears N. 28° E., 18.2 lks. dist.

An aspen stump, 12 ins. diam., bears S. 85° E., 9.5 lks. dist., mkd. with a healed blaze at the base.

An elm stump, 6 ins. diam., bears S. 6° E., 14.5 lks. dist.

Not remonumented.

- 59.013** The W. 1/16 sec. cor. of secs. 9 and 16, established at proportionate dist., by William F. Kelly, Registered Land Surveyor No. 1098, in 1983, monumented with an iron pipe, 1 in. diam., loosely set, projecting 6 ins. above the ground.

Not remonumented.

- 78.684** The cor. of secs. 8, 9, 16, and 17.

From the cor. of secs. 29, 30, 31, and 32., monumented with a decayed wood post, 4 x 4 ins. sq., loosely set, projecting 12 ins. above the ground, as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin., alongside of which, a decayed cedar fence post, 8 ins. diam, firmly set, projecting 18 ins. above ground, with barbed wire wrapped around it, and dilapidated fences, with decayed wood posts and downed wire extending N. and E.

Not remonumented.

N. 0°39' E., bet. secs. 29 and 30.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

- 35.333** Point for the meander cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
- From this point, the meander cor. of secs. 29 and 30, mistakenly established in the 1978 dependent resurvey, bears N. $87^{\circ}13'$ E., 1.9 lks. dist., not monumented
- 37.400** Enter Bishop Lake, edge bears SE and NW.
- 38.362** Point for the meander cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
- From this point, the meander cor. of secs. 29 and 30, mistakenly established in the 1978 dependent resurvey, bears N. $82^{\circ}37'$ E., 2.1 lks. dist., not monumented.
- 38.500** Leave Bishop Lake, edge bears SE and NW.
- 40.381** Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
- From this point, the 1/4 sec. cor. of secs. 29 and 30, mistakenly established in the 1978 dependent resurvey, bears N. $79^{\circ}58'$ E., 2.3 lks. dist., not monumented.
- 80.762** Point for the cor. of secs. 19, 20, 29, and 30, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
- From this point, the cor. of secs. 19, 20, 29, and 30, mistakenly established in the 1978 dependent resurvey, bears N. $79^{\circ}58'$ E., 4.5 lks. dist., not monumented.
-
- From the cor. of secs. 20, 21, 28, and 29.
- S. $89^{\circ}16'$ W., bet. secs. 20 and 29.
- 19.050** Creek, 85 lks. wide, course S.
- 32.150** Leave swamp, edge bears N. and S.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

*CHAINS***39.468**

The 1/4 sec. cor. of secs. 20 and 29, monumented with an aluminum post, 2 ½ ins. diam., firmly set, projecting 5 ins. above the ground, with an aluminum cap mkd. as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin.

from which the remains of original bearing trees

An uprooted stump hole, bears N. 85° E., 15.0 lks. dist.

An uprooted stump hole, bears S. 33° E., 40.0 lks. dist.

from which the 1978 bearing trees

A spruce stump, 14 ins. diam., bears N. 25° E., 39.0 lks. dist.

A spruce, 18 ins. diam., bears S. 83° E., 15.0 lks. dist., mkd. with a healed blaze at the base.

and a new bearing tree

A spruce, 14 ins. diam., bears S. 56° W., 40.7 lks. dist., mkd.
1/4 S29 BT.

Not remonumented.

S. 88° 51' W., beginning new measurement.

19.770

Point for the W. 1/16 sec. cor. of secs. 20 and 29.

From this point, the W. 1/16 sec. cor. of secs. 20 and 29, mistakenly established in the 1978 dependent resurvey, bears N. 79° 58' E., 2.3 lks. dist., set, mkd., and witnessed as described in the official record.

Removed the 1978 aluminum post.

At the cor. point.

Reset the aluminum post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", with an aluminum cap mkd.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

<i>CHAINS</i>	T35N R12E S 20 W 1/16 ————— S 29 BLM 1978 2007
	<p>from which the 1978 bearing trees</p> <p style="padding-left: 40px;">An ash, 8 ins. diam., bears S. 52° E., 12.1 lks. dist., mkd. with a healed blaze at the base.</p> <p style="padding-left: 40px;">An ash, 14 ins. diam., bears N. 2° W., 41.0 lks. dist., mkd. with a healed blaze at the base .</p>
39.540	<p>The cor. of secs. 19, 20, 29, and 30.</p> <hr/> <p>N. 89°55' W., bet. secs. 19 and 30.</p>
39.581	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p> <p>From this point, the 1/4 sec. cor. of secs. 19 and 30, mistakenly established in the 1978 dependent resurvey, bears N. 87°09' E., 8.2 lks. dist., not monumented.</p>
81.240	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 2°19' E., bet. secs. 19 and 20.</p>
40.411	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p> <p>From this point, the 1/4 sec. cor. of secs. 19 and 30, mistakenly established in the 1978 dependent resurvey, bears N. 82°51' E., 2.1 lks. dist., not monumented.</p>

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS**80.822**

Point for the cor. of secs. 17, 18, 19, and 20, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.

From this point, the cor. of secs. 17, 18, 19, and 20, mistakenly established in the 1978 dependent resurvey, bears S. 46°44' W., 0.4 lks. dist., not monumented.

From the cor. of secs. 16, 17, 20, and 21.

S. 88°22' W., bet. secs. 17 and 20.

10.750

Enter swamp, edge bears NE and SW.

20.209

Point for the E. 1/16 sec. cor. of secs. 17 and 20, not monumented.

22.900

Creek, 10 lks. wide, course SW.

30.150

Leave swamp, edge bears N. and S.

36.900

Enter swamp, edge bears N. and S.

40.418

Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.

From this point, the 1/4 sec. cor. of secs. 17 and 20, mistakenly established in the 1978 dependent resurvey, bears S. 46°46' E., 0.2 lks. dist., not monumented.

At the cor. point.

Set an aluminum rod, 32 ins. long, 1 in. diam., driven 24 ins. in the ground, with a "DEEP-1" alongside, with an aluminum cap mkd.

T 35 N R 12 E
S 17
1/4 —————
S 20
2007

from which

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A tamarack, 4 ins. diam., bears S. 86° W., 221.0 lks. dist., mkd. BT at the base and X at breast height.

A tamarack, 10 ins. diam., bears N. 65° W., 217.5 lks. dist., mkd. 1/4 S17 BT.

44.700 Leave swamp, edge bears N. and S.

80.836 The cor. of secs. 17, 18, 19, and 20.

S. 89°09' W., bet. secs. 18 and 19.

40.031 The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, 7 ins. below the gravel surface of Johnson Road, as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin.

from which the accessories not of record in the 1978 survey

A pine stump, 21 ins. diam., bears S. 82° W., 56.0 lks. dist., mkd. 19 BT in an open blaze at the base.

An iron pipe, 1 1/4 ins. diam., loosely set, projecting 7 ins. above the ground, bears W., 38.0 lks. dist.

A cedar, 7 ins. diam., bears N. 51° W., 64.0 lks. dist., mkd. with a healed blaze at the base.

from which new bearing trees not of record

A hemlock, 9 ins. diam., bears N. 65° E., 76.5 lks. dist., mkd. with open blazes at base and breast height.

A balsam, 5 ins. diam., bears S. 86° E., 60.5 lks. dist., mkd. with open blazes at base and breast height.

An aspen snag, 9 ins. diam., bears S. 69° W., 47.0 lks. dist., mkd. with an open blaze at the base.

Not remonumented.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

From the cor. of secs. 17, 18, 19, and 20.

N. 0°16' W., bet. secs. 17 and 18.

40.378 Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor, not monumented.

From this point, an iron pipe, 1 in. diam., firmly set, 2 ins. below the gravel surface of Logan Creek Lane, bears N. 38°36' E., 86.4 lks. dist.

From this same point, an iron pipe, 1 3/4 ins. diam., loosely set, projecting 48 ins. above ground, bears N. 18°42' W., 61.0 lks. dist.

80.756 The cor. of secs. 7, 8, 17, and 18, reestablished and recorded by Philip T. Hansen, Registered Land Surveyor No. 498, in 1977, and accepted as a careful and faithful reestablishment of the original cor. position, as described in the official record of the 1978 dependent resurvey, executed under Group No. 109, Wisconsin, and further perpetuated by Jeffrey Kip Inman, Registered Land Surveyor No. 1676, in 2001.

Note: The railroad spike and accessories established by Mr. Hansen and described in the 1978 survey have been obliterated, presumably by road construction. This position was reestablished from found monuments of Inman's 2001 survey.

From this cor., an iron rod, 3/4 ins. diam., firmly set, flush with the ground, with a 1 in. diam. plastic cap mkd. AYRES, bears N. 17°25' E., 238.8 lks. dist.

From this same cor., an iron rod, 3/4 ins. diam., firmly set, flush with the ground, with a 1 in. diam. plastic cap mkd. AYRES, bears N. 23°09' E., 184.6 lks. dist.

Also from this same cor., a concrete post, 14 in. diam., firmly set, flush with the ground, with an aluminum disc mkd. WIS. DEPT OF TRANSPORTATION UNLAWFUL TO DISTURB, bears N. 43°35' E., 178.7 lks. dist.

Also from this same cor., a concrete post, 14 in. diam., firmly set, flush with the ground, with an aluminum disc mkd. WIS. DEPT OF TRANSPORTATION UNLAWFUL TO DISTURB, bears S. 38°23' E., 149.7 lks. dist.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

Also from this same cor., an iron rod, 3/4 ins. diam., firmly set, projecting 1 in. above the ground, with a 1 in. diam. plastic cap mkd. AYRES, bears S. 25°28' E., 188.5 lks. dist.

Also from this same cor., an iron rod, 3/4 ins. diam., firmly set, flush with the ground, with a 1 in. diam. plastic cap mkd. AYRES, bears S. 27°56' E., 183.5 lks. dist.

Also from this same cor., a concrete post, 14 in. diam., firmly set, flush with the ground, with an aluminum disc mkd. WIS. DEPT OF TRANSPORTATION UNLAWFUL TO DISTURB, bears S. 52°53' E., 131.1 lks. dist.

Also from this same cor., a concrete post, 14 in. diam., firmly set, flush with the ground, with an aluminum disc mkd. WIS. DEPT OF TRANSPORTATION UNLAWFUL TO DISTURB, bears N. 46°21' W., 142.6 lks. dist.

Also from this same cor., an iron rod, 3/4 ins. diam., firmly set, flush with the ground, with a 1 in. diam. plastic cap mkd. AYRES, bears N. 22°56' W., 244.2 lks. dist.

Also from this same cor., an iron rod, 3/4 ins. diam., loosely set, flush with the ground, bears N. 15°33' W., 126.3 lks. dist.

Not monumented.

From the cor. of secs. 8, 9, 16, and 17.

S. 85°36' W., bet. secs. 8 and 17.

21.186 Point for the E. 1/16 sec. cor. of secs. 8 and 17, not monumented.

42.372 The 1/4 sec. cor. of secs. 8 and 17, reestablished and recorded by Philip T. Hansen, Registered Land Surveyor No. 498, in 1977. There is no remaining evidence of the original monument, however, this position is accepted as a careful and faithful reestablishment of the original cor. position.

DEPENDENT RESURVEY OF A
PORTION OF THE SUBDIVISIONAL LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

Note: The railroad spike established by Mr. Hansen has been obliterated, presumably by road construction. This position was determined from accessories established by Mr. Hansen.

from which Hansen's accessories

A maple, 13 ins. diam., bears S. 10° E., 116.3 lks. dist., mkd. with healed blazes at base and breast height.

An iron post, 2 ½ ins. diam., firmly set, projecting 8 ins. above the ground, with an aluminum cap mkd. T35N R12E 1/4 S8 S17 WC 1977 N. 60 LKS TO COR.. bears S., 60.0 lks. dist.

A maple, 10 ins. diam., bears S. 46° W., 112.1 lks. dist., mkd. BT in an open blaze at the base, and with a healed breast height blaze.

N. 86° 17' W., beginning new measurement.

39.420 The cor. of secs. 7, 8, 17, and 18.

Reestablishment of a Portion of the
Record Meander Lines
T. 35 N., R. 12 E., 4th Prin. Mer., Wisconsin

(Restoring the survey executed by
James L. Nowlin and Hardin Nowlin,
Deputy Surveyors, in 1864)

The record measurements of a portion of the original meander lines were retraced and the residual or closing error was ascertained. Thereupon, the record measurements were adjusted to a closing by means of the broken boundary method, adopting new courses to the nearest minute, and distances to the nearest one-tenth of a link.

Rice Lake

REESTABLISHMENT OF A PORTION OF THE
RECORD MEANDER LINES
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

<i>CHAINS</i>	<p>From the meander cor. and the cor. of secs. 22, 23, 26, and 27, on the E. side of Rice Lake.</p> <p>Thence in sec. 22</p> <p>N. 16°38' W., 13.110 chs.</p> <p>N. 8°07' E., 3.031 chs.</p> <p>N. 17°38' W., 9.075 chs.</p> <p>N. 72°24' W., 26.988 chs.</p> <p>S. 59°23' W., 2.976 chs.</p> <p>S. 44°15' W., 15.847 chs. At 5.974 chs. on this course, the special meander cor. on the N. and S. center line of sec. 22.</p> <p>S. 17°59' W., 19.790 chs. The meander cor. of secs. 22 and 27, on the W. side of Rice Lake.</p> <hr/> <p style="text-align: center;">Subdivision of Section 15, T. 35 N., R. 12 E., 4th Prin. Mer., Wisconsin</p> <hr/> <p>From the 1/4 sec. cor. of secs. 15 and 22.</p> <p>N. 0°33' W., on the N. and S. center line of sec. 15.</p> <p>39.054 Point for the center 1/4 sec. cor. of sec. 15, at the intersection with the E. and W. center line, not monumented.</p> <p>From this cor., an iron pipe, 1 1/2 ins. diam., firmly set, projecting 22 ins. above the ground, bears N. 40°47' E., 37.8 lks. dist.</p> <p>58.887 Point for the center N. 1/16 sec. cor. of sec. 15, not monumented.</p> <p>From this cor., an iron pipe, 2 ins. diam., firmly set, projecting 13 ins. above the ground, bears N. 67°49' E., 75.0 lks. dist.</p>
---------------	--

SUBDIVISION OF SECTION 15,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

78.720 The 1/4 sec. cor. of secs. 10 and 15.

From the 1/4 sec. cor. of secs. 14 and 15.

S. 89°30' W., on the E. and W. center line of sec. 15.

39.297 The center 1/4 sec. cor. of sec. 15.

59.070 Point for the center W. 1/16 sec. cor. of sec. 15.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a "DEEP-1", with a brass cap mkd.

W 1/16
C ——— C
S 15
2007

from which

An aspen, 7 ins. diam., bears S. 38° E., 23.5 lks. dist., mkd. BT at the base and X at breast height.

An aspen, 4 ins. diam., bears S. 84° W., 31.7 lks. dist., mkd. BT at the base and X at breast height.

From this cor., an iron pipe, 1 1/2 ins. diam., firmly set, projecting 22 ins. above the ground, bears N. 5°20' W., 32.9 lks. dist.

78.843 The 1/4 sec. cor. of secs. 15 and 16.

From the W. 1/16 sec. cor. of secs. 15 and 22.

N. 0°16' W., on the N. and S. center line of the SW 1/4 of sec. 15.

39.209 The center W. 1/16 sec. cor. of sec. 15.

SUBDIVISION OF SECTION 15,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

From the center W. 1/16 sec. cor. of sec. 15.

N. 0°16' W., on the N. and S. center line of the NW 1/4 of sec. 15.

19.757 Point for the NW 1/16 sec. cor. of sec. 15, at the intersection with the E. and W. center line of the NW 1/4 of sec. 15.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", with a brass cap mkd.

NW 1/16 S 15
2007

from which

A cedar, 13 ins. diam., bears N. 63° E., 24.7 lks. dist., mkd.
NW 1/16 S15 BT.

A spruce, 17 ins. diam., bears S. 2° W., 40.7 lks. dist., mkd. NW
1/16 S15 BT.

From this cor., an iron pipe, 1 1/2 ins. diam., firmly set, projecting 17 ins. above the ground, bears N. 4°37' E., 55.0 lks. dist.

39.513 The W. 1/16 sec. cor. of secs. 10 and 15.

From the center N. 1/16 sec. cor. of sec. 15.

S. 89°16' W., on the E. and W. center line of the NW 1/4 of sec. 15.

19.671 The NW 1/16 sec. cor. of sec. 15.

39.342 The N. 1/16 sec. cor. of secs. 15 and 16.

Subdivision of Section 16,
T. 35 N., R. 12 E., 4th Prin. Mer., Wisconsin

SUBDIVISION OF SECTION 16,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

From the 1/4 sec. cor. of secs. 16 and 21.

N. 0° 10' E., on the N. and S. center line of sec. 16.

39.846 Point for the center 1/4 sec. cor. of sec. 16, at the intersection with the E. and W. center line.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 26 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

T 35 N R 12 E
C 1/4 S 16
2007

from which

A maple, 8 ins. diam., bears S. 49° E., 36.0 lks. dist., mkd. C1/4 S16 BT.

A cedar, 12 ins. diam., bears S. 37° W., 31.7 lks. dist., mkd. C1/4 S16 BT.

From this cor., an iron pipe, 1 in. diam., firmly set, flush with the ground, bears S. 8° 27' W., 37.5 lks. dist.

59.391 Point for the center N. 1/16 sec. cor. of sec. 16.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., flush with the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

C
N 1/16 | S 16
C
2007

from which

An elm, 13 ins. diam., bears N. 33° E., 178.9 lks. dist., mkd. CN 1/16 S16 BT.

SUBDIVISION OF SECTION 16,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A maple, 5 ins. diam., bears N. 73° E., 122.0 lks. dist., mkd. BT at the base and X at breast height.

This cor. is located 27 lks. West of the center line of Kramar Lane, bearing N. and S.

78.936 The 1/4 sec. cor. of secs. 9 and 16.

From the 1/4 sec. cor. of secs. 15 and 16.

S. 89°37' W., on the E. and W. center line of sec. 16.

19.719 Point for the center E. 1/16 sec. cor. of sec. 16.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 26 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

T35N R12E
E 1/16
C ——— C
S 16
2007

from which

A maple, 6 ins. diam., bears S. 26° E., 18.3 lks. dist., mkd.
CE 1/16 S16 BT.

A maple, 15 ins. diam., bears N. 1° W., 8.5 lks. dist., mkd.
CE 1/16 S16 BT.

From this cor., an iron pipe, 1 1/2 ins. diam., firmly set, 3 ins. below the ground, bears S. 9°19' E., 49.5 lks. dist.

From this same cor., an iron pipe, 1 in. diam., firmly set, flush with the ground, bears S. 7°05' W., 16.8 lks. dist.

39.438 The center 1/4 sec. cor. of sec. 16.

58.988 Point for the center W. 1/16 sec. cor. of sec. 16.

SUBDIVISION OF SECTION 16,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

W 1/16
C ——— C
S 16
2007

from which

A maple, 9 ins. diam., bears N. 27° E., 52.5 lks. dist., mkd.
CW 1/16 S16 BT.

A maple, 11 ins. diam., bears S. 87° E., 33.5 lks. dist., mkd.
CW 1/16 S16 BT.

From this cor., an iron pipe, 1 in. diam., firmly set, flush with the ground, bears S. 9° 49' W., 58.2 lks. dist.

78.538 The 1/4 sec. cor. of secs. 16 and 17.

From the center E. 1/16 sec. cor. of sec. 16.

N. 0° 06' E., on the N. and S. center line of the NE 1/4 of sec. 16.

19.613 Point for the NE 1/16 sec. cor. of sec. 16, at the intersection with the E. and W. center line of the NE 1/4 of sec. 16.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

NE 1/16 S 16
2007

from which

A maple, 10 ins. diam., bears N. 81° E., 31.2 lks. dist., mkd. NE
1/16 S16 BT.

SUBDIVISION OF SECTION 16,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A hemlock, 5 ins. diam., bears S. 49° W., 47.5 lks. dist., mkd. BT at the base and X at breast height.

From this cor., an iron pipe, 1 1/2 ins. diam., firmly set, flush with the ground, bears S. 19°57' E., 11.3 lks. dist.

39.226 The E. 1/16 sec. cor. of secs. 9 and 16.

From the N. 1/16 sec. cor. of secs. 15 and 16.

S. 89°25' W., on the E. and W. center line of the NE 1/4 of sec. 16.

19.695 The NE 1/16 sec. cor. of sec. 16.

39.390 The center N. 1/16 sec. cor. of sec. 16.

From the center W. 1/16 sec. cor. of sec. 16.

North, on the N. and S. center line of the NW 1/4 of sec. 16.

19.476 Point for the NW 1/16 sec. cor. of sec. 16, at the intersection with the E. and W. center line of the NW 1/4 of sec. 16.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

NW 1/16 S 16

2007

from which

A maple, 12 ins. diam., bears N. 71° E., 41.0 lks. dist., mkd.
NW 1/16 S16 BT.

A basswood, 8 ins. diam., bears S. 17° W., 39.0 lks. dist., mkd.
NW 1/16 S16 BT.

From this cor., an angle iron, 1 1/4 x 1 1/4 ins., loosely set, projecting 48 ins. above the ground, bears S. 86°39' E., 147.1 lks. dist.

SUBDIVISION OF SECTION 16,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

From this same cor., an iron pipe, 1 in. diam., firmly set, flush with the ground, bears S. 0°37' W., 33.0 lks. dist., alongside of which is an iron pipe, 1 1/2 ins. diam., firmly set, projecting 42 ins. above the ground.

38.952 The W. 1/16 sec. cor. of secs. 9 and 16.

From the center N. 1/16 sec. cor. of sec. 16.

S. 89°24' W., on the E. and W. center line of the NW 1/4 of sec. 16.

19.610 The NW 1/16 sec. cor. of sec. 16.

39.220 The N. 1/16 sec. cor. of secs. 16 and 17.

Subdivision of Section 17,
T. 35 N., R. 12 E., 4th Prin. Mer., Wisconsin

From the 1/4 sec. cor. of secs. 17 and 20.

N. 1°04' W., on the N. and S. center line of sec. 17

20.168 Point for the center S. 1/16 sec. cor. of sec. 17, not monumented.

40.336 Point for the center 1/4 sec. cor. of sec. 17, at the intersection with the E. and W. center line, not monumented.

From this cor., a steel fence post, 1/2 x 1 1/2 ins., firmly set, projecting 24 ins. above the ground, in an embedded collar of stone, bears N. 2°28' E., 29.4 lks. dist.

58.699 Point for the center N. 1/16 sec. cor. of sec. 17, not monumented.

77.062 The 1/4 sec. cor. of secs. 8 and 17.

From the 1/4 sec. cor. of secs. 16 and 17.

S. 88°25' W., on the E. and W. center line of sec. 17.

SUBDIVISION OF SECTION 17,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

20.857 Point for the center E. 1/16 sec. cor. of sec. 17.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

E 1/16
C ——— C
S 17
2007

from which

A spruce, 4 ins. diam., bears N. 73° E., 100.0 lks. dist., mkd. BT at the base and X at breast height.

A spruce, 6 ins. diam., bears S. 76° E., 114.0 lks. dist., mkd. CE 1/16 S17 BT.

41.714 The center 1/4 sec. cor. of sec. 17.

81.566 The 1/4 sec. cor. of secs. 17 and 18.

From the center E. 1/16 sec. cor. of sec. 17.

N. 0°37' W., on the N. and S. center line of the NE 1/4 of sec. 17.

18.885 Point for the NE 1/16 sec. cor. of sec. 17, at the intersection with the E. and W. center line of the NE 1/4 of sec. 17.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

NE 1/16 S 17
2007

from which

A maple, 13 ins. diam., bears N. 31° E., 64.7 lks. dist., mkd. NE 1/16 S17 BT.

SUBDIVISION OF SECTION 17,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A maple, 8 ins. diam., bears S. 42° E., 52.5 lks. dist., mkd.
NE 1/16 S17 BT.

37.769 The E. 1/16 sec. cor. of secs. 8 and 17.

From the N. 1/16 sec. cor. of secs. 16 and 17.

S. 87°00' W., on the E. and W. center line of the NE 1/4 of sec. 17.

21.015 The NE 1/16 sec. cor. of sec. 17.

42.030 The center N. 1/16 sec. cor. of sec. 17.

From the E. 1/16 sec. cor. of secs. 17 and 20.

N. 0°08' W., on the N. and S. center line of the SE 1/4 of sec. 17.

20.164 Point for the SE 1/16 sec. cor. of sec. 17, at the intersection with the E. and W. center line of the SE 1/4 of sec. 17.

Set a stainless steel post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", with a brass cap mkd.

SE 1/16 S 17
2007

from which

A maple, 8 ins. diam., bears N. 71° E., 75.4 lks. dist., mkd.
SE 1/16 S17 BT.

A maple, 6 ins. diam., bears S. 44° E., 30.5 lks. dist., mkd. SE
1/16 S17 BT.

40.328 The center E. 1/16 sec. cor. of sec. 17.

From the S. 1/16 sec. cor. of secs. 16 and 17.

SUBDIVISION OF SECTION 17,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS S. 88°24' W., on the E. and W. center line of the SE 1/4 of sec. 17.

20.533 The SE 1/16 sec. cor. of sec. 17.

41.066 The center S. 1/16 sec. cor. of sec. 17.

Corrective Subdivision of Section 20,
T. 35 N., R. 12 E., 4th Prin. Mer., Wisconsin

From the 1/4 sec. cor. of secs. 20 and 29.

N. 2°56' E., on the N. and S. center line of sec. 20.

40.331 Point for the center 1/4 sec. cor. of sec. 20, at the intersection with the E. and W. center line.

From this point, the center 1/4 sec. cor. of sec. 20, mistakenly established in the 1978 dependent resurvey, bears N. 28°33' W., 0.1 lks. dist., set, mkd., and witnessed as described in the official record.

Removed the 1978 aluminum post, and destroyed the marks on the 1978 NE bearing tree.

At the cor. point.

Reset the aluminum post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the ground, over a "DEEP-1", with an aluminum cap mkd.

T 35 N R 12 E
C 1/4
S 20
BLM
1978
2007

from which

A cedar, 9 ins. diam., bears S. 51° E., 31.6 lks. dist., mkd. C1/4
S20 BT.

CORRECTIVE SUBDIVISION OF SECTION 20,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A cedar, 11 ins. diam., bears S. 59° W., 24.7 lks. dist., mkd.
C1/4 S20 BT. Note: this is the SW bearing tree from the 1978
survey.

81.220 The 1/4 sec. cor. of secs. 17 and 20.

From the 1/4 sec. cor. of secs. 20 and 21.

S. 89°00' W., on the E. and W. center line of sec. 20.

39.968 The center 1/4 sec. cor. of sec. 20.

59.947 Point for the center W. 1/16 sec. cor. of sec. 20.

From this point, the center W. 1/16 sec. cor. of sec. 20, mistakenly
established in the 1978 dependent resurvey, bears N. 79°33' E., 1.0 lks.
dist., set, mkd., and witnessed as described in the official record.

Removed the 1978 aluminum post, and destroyed the marks on the 1978
NW bearing tree.

At the cor. point.

Reset the aluminum post, 30 ins. long, 2 ½ ins. diam., 25 ins. in the
ground, over a "DEEP-1", in a collar of stone, with an aluminum cap
mkd.

T35N R12E
CW 1/16
S 20
BLM
1978
2007

from which

An ash, 8 ins. diam., bears N. 42° E., 22.6 lks. dist., mkd.
CW 1/16 S20 BT.

CORRECTIVE SUBDIVISION OF SECTION 20,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

A maple, 9 ins. diam., bears S. 41° E., 40.0 lks. dist., mkd. with a healed blaze at the base. Note: this is the SE bearing tree from the 1978 survey.

79.926 The 1/4 sec. cor. of secs. 19 and 20.

From the W. 1/16 sec. cor. of secs. 20 and 29.

N. 2°38' E., on the N. and S. center line of the SW 1/4 of sec. 20.

40.371 The center W. 1/16 sec. cor. of sec. 20.

Subdivision of Section 21,
T. 35 N., R. 12 E., 4th Prin. Mer., Wisconsin

From the 1/4 sec. cor. of secs. 21 and 28.

N. 3°29' E., on the N. and S. center line of sec. 21.

40.220 Point for the center 1/4 sec. cor. of sec. 21, at the intersection with the E. and W. center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a "DEEP-1", in a collar of stone, with a brass cap mkd.

T 35 N R 12 E
C 1/4 S 21
2007

from which

A maple, 9 ins. diam., bears S. 15° W., 80.0 lks. dist., mkd.
C1/4 S21 BT.

A maple, 8 ins. diam., bears N. 52° W., 53.3 lks. dist., mkd. C1/4
S21 BT.

SUBDIVISION OF SECTION 21,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

CHAINS

81.657 The 1/4 sec. cor. of secs. 16 and 21.

From the 1/4 sec. cor. of secs. 21 and 22.

S. 89°01' W., on the E. and W. center line of sec. 21.

38.924 The center 1/4 sec. cor. of sec. 21.

78.491 The 1/4 sec. cor. of secs. 20 and 21.

Subdivision of Section 22,
T. 35 N., R. 12 E., 4th Prin. Mer., Wisconsin

From the 1/4 sec. cor. of secs. 15 and 22.

S. 2°46' W., on a weighted mean bearing on the N. and S. center line of sec. 22.

20.303 Point for the center N. 1/16 sec. cor. of sec. 22.

Set an aluminum rod, 32 ins. long, 1 in. diam., driven 26 ins. in the ground, with a "DEEP-1" alongside, with an aluminum cap mkd.

C
N 1/16 | S 22
C
2007

from which

A cedar, 10 ins. diam., bears N. 62° E., 20.5 lks. dist., mkd.
CN 1/16 S22 BT.

A tamarack, 10 ins. diam., bears N. 59° W., 29.3 lks. dist., mkd.
CN 1/16 S22 BT.

SUBDIVISION OF SECTION 22,
T. 35 N., R. 12 E., 4TH PRIN. MER., WISCONSIN

<i>CHAINS</i>	<p>From this cor., a wood post, 4 ins. diam., loosely set, projecting 12 ins. above the ground, bears N. 41°33' E., 47.2 lks. dist.</p>
40.606	<p>Point for the center 1/4 sec. cor. of sec. 22, at the intersection with the E. and W. center line.</p> <p>Set an aluminum rod, 32 ins. long, 1 in. diam., driven 27 ins. in the ground, with a "DEEP-1" alongside, with an aluminum cap mkd.</p> <p style="text-align: center;">T 35 N R 12 E C 1/4 S 22 2007</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears N. 65° W., 107.2 lks. dist., mkd. C1/4 S22 BT.</p> <p style="padding-left: 40px;">A tamarack, 10 ins. diam., bears N. 41° W., 55.8 lks. dist., mkd. C1/4 S22 BT.</p>
56.447	<p>Point for the special meander cor. of sec. 22, at intersection with the adjusted record meander line of Rice Lake; not monumented.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23.</p> <p>S. 87°52' W., on the E. and W. center line of sec. 22.</p>
35.916	<p>The center 1/4 sec. cor. of sec. 22.</p>
77.084	<p>The 1/4 sec. cor. of secs. 21 and 22.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 22 and 23.</p> <p>S. 89°25' W., on the E. and W. center line of the NE 1/4 of sec. 22.</p>
37.681	<p>The center N. 1/16 sec. cor. of sec. 22.</p>

TOWNSHIP 35 NORTH, RANGE 12 EAST
FOURTH PRINCIPAL MERIDIAN, WISCONSIN

CHAINS

General Description

The land encompassed in this survey is located approximately 1 mile north of the city of Mole Lake, and 5 miles southwest of the city of Crandon. The topography is gently rolling and the elevation ranges from approximately 1550 to 1750 feet above sea level. The township is mostly upland in character with some low swampland areas. Most of the area is timbered with the predominant species being pine, maple, aspen, spruce, birch, cedar, balsam, and tamarack.

Vehicle access is by State Highway 55, County highways B and M, township roads, and numerous logging roads. The area is predominantly used for logging and recreational activities which include hiking, hunting, and ATV riding.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
David G. Ritter	Survey Technician
Ronald L. Blair	Survey Technician
C. Eric Wright	Survey Technician
Chad Buescher	Survey Technician

CERTIFICATE OF SURVEY

I, *Travis M. Hand*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *4th day of April, 2007*, I have performed a *dependent resurvey of a portion of the west boundary, and a portion of the subdivisional lines; a corrective dependent resurvey of a portion of the west boundary, and a portion of the subdivisional lines; a corrective resurvey of the subdivision of section 20; and the survey of the subdivision of sections 15, 16, 17, 21, and 22, Township 35 North, Range 12 East*, of the *4th Principal Meridian*, in the State of *Wisconsin*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

SEPT. 2, 2008
(Date)

Travis M. Hand
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Springfield, Virginia

The foregoing field notes of the *dependent resurvey of a portion of the west boundary, and a portion of the subdivisional lines; a corrective dependent resurvey of a portion of the west boundary, and a portion of the subdivisional lines; a corrective resurvey of the subdivision of section 20; and the survey of the subdivision of sections 15, 16, 17, 21, and 22, Township 35 North, Range 12 East*, of the *4th Principal Meridian, Wisconsin*, executed by *Travis M. Hand* having been critically examined and found correct, are hereby approved.

SEPT 5, 2008
(Date)

Ronald S. Fiber
(Chief Cadastral Surveyor, Eastern States)