

952742

4-878
(April 1933)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

DUPLICATE

FIELD NOTES

RECEIVED & FILED # **L3681**
Oneida County Surveyor's Office
Date **FEB. 14 1988**
By **M J H**
OCS Area #.....

OF THE

DEPENDENT RESURVEY

OF THE

SOUTH BOUNDARY OF SECTIONS

35 AND 36

AND

A PORTION OF THE SUBDIVISIONAL LINES

TOWNSHIP NO. 38 NORTH, RANGE NO. 11 EAST

Of the **FOURTH PRINCIPAL** Meridian,

In the State of **WISCONSIN**

EXECUTED BY

Hugh B. Crawford, Assistant Cadastral Engineer.

Supplemental

Under/special instructions dated **August 25**, 19**41**, which provided
for the surveys included under Group No. **51**, bearing the approval of the
Commissioner of the General Land Office under date of **August 29, 1941**
and assignment instructions dated **September 2, 1941**, 19**41**

Survey commenced **August 21**, 19**41**

Survey completed **October 25**, 19**41**

8981

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin

Chains

N. 1°15' W., bet. secs. 26 and 27.

Descend N. slope to Crooked Lake, through timber and undergrowth.

0.72

Intersect the S. shore of Crooked Lake; there has been no change in the shore line, and the actual shore is accepted as the best available evidence of the position of the original cor.

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, for meander cor. of frac. secs. 26 and 27, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

M C	
S 27	S 26
T 38 N	R 11 E
1941	

from which

A white birch, 5 ins. diam., bears S. 43½° E.,
21 lks. dist., mkd. T 38 N R 11 E S 26 M C B T.

A white birch, 6 ins. diam., bears S. 76° W.,
27 lks. dist., mkd. T 38 N R 11 E S 27 M C B T.

Thence over Crooked Lake by carefully checked triangulation.

47.51

The meander cor. on the NW. shore of Crooked Lake, as determined from the remains of the original bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for meander cor. of frac. secs. 26 and 27, with brass cap mkd.

T 38 N	R 11 E
S 27	S 26
M C	
1941	

from which

The remains of the original bearing trees,

A rotted balsam stump, 16 ins. diam., bears N. 43° E., 27 lks. dist.

A stump hole, bears N. 50° W., 24 lks. dist.

And new bearing trees,

A maple, 6 ins. diam., bears N. 55° E., 58½ lks. dist., mkd. T 38 N R 11 E S 26 M C B T.

A maple, 7 ins. diam., bears N. 52½° W., 17½ lks. dist., mkd. T 38 N R 11 E S 27 M C B T.

A local stake, 3 ins. sq., 30 ins. above ground, bears N. 20° E., 3 lks. dist.

N. 0°35' E., bet. secs. 26 and 27 (N. portion).

INDEX DIAGRAM.

Township 38 North, Range 11 East

6	5	4	3	3 6	2 0	1
7	8	9	10	3 3	36 11	19 17 12
18	17	16	15	3 0	31 14	15 13
19	20	21	22	2 7	29 28	12 11 10
30	29	28	27	2 5	26 25	10 9 8
31	32	33	34	2 2	23 22	8 7 6
				6	4	3

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin

Chains	Over rolling land, through timber and undergrowth.						
3.00	Enter swamp, near W. edge, bears E.						
7.90	Leave swamp, bears E.						
13.89	A local 1/16 cor., which is a wooden post, 4 ins. sq., 30 ins. long, rotted off at ground. This cor. was established by Adolph Kloes, local surveyor, Three Lakes, Wisconsin, on line bet. the original meander cor. and original sec. cor. of secs. 22, 23, 26, and 27, both cors. being in existence at the time. The sec. cor. has since been destroyed by road work. I determined the position of the sec. cor. by running the line through this 1/16 cor. to the center line of the road; the line thus determined falls on old blazed line.						
35.44	The point for the cor. of secs. 22, 23, 26, and 27 falls in center of a road, bearing E. and W.						
	Set a concrete monument, 24 ins. long, 6 ins. diam., 30 ins. in the ground, for cor. of secs. 22, 23, 26, and 27, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.						
	<table border="1"> <tr> <td>T 38 N</td><td>R 11 E</td></tr> <tr> <td>S 22</td><td>S 23</td></tr> <tr> <td>S 27</td><td>S 26</td></tr> </table>	T 38 N	R 11 E	S 22	S 23	S 27	S 26
T 38 N	R 11 E						
S 22	S 23						
S 27	S 26						
	1941						
	from which						
	A poplar, 12 ins. diam., bears N. $52\frac{1}{2}^{\circ}$ E., 72 lks. dist., mkd. T 38 N R 11 E S 23 B T.						
	A hemlock, 10 ins. diam., bears S. $13\frac{1}{2}^{\circ}$ E., 90 lks. dist., mkd. T 38 N R 11 E S 26 B T.						
	A hemlock, 6 ins. diam., bears S. 31° W., $111\frac{1}{2}$ lks. dist., mkd. T 38 N R 11 E S 27 B T.						
	A maple, 16 ins. diam., bears N. $24\frac{5}{4}^{\circ}$ W., 49 lks. dist., mkd. T 38 N R 11 E S 22 B T.						
	Land, rolling.						
	Soil, sandy clay, 2nd and 3rd rate.						
	Timber, hemlock, birch, maple, spruce, and poplar; undergrowth, young timber.						
	From the cor. of secs. 23, 24, 25, and 26.						
	N. $86^{\circ} 17'$ W., bet. secs. 23 and 26.						
	Over level swamp land, through timber and undergrowth.						
11.65	Scott Creek, 20 lks. wide, course S. from NE.						
17.25	Leave swamp, bears N. and S.						
23.70	Enter swamp, bears N. and S.						
28.60	Right bank of Eagle River, averaging nearly 1.00 ch. in width, course W. from SE.						
36.00	Leave river, course N. from E., very winding.						
40.89 $\frac{1}{2}$	Proportionate distance; there is no remaining evidence of the original cor.						

Dependent Resurvey of a Portion of T. 38 N., R. 11 E.,
Fourth Prin. Mer., Wisconsin.

Sections 1, 12, 13, 24, 25, and 36; and the east one-half of sections 2, 11, 14, 23, 26, and 35, Township 38 North, Range 11 East, of the Fourth Principal Meridian, Wisconsin, are located within the Nicolet National Forest. The subdivisional survey of the township was executed by William E. Daugherty, Deputy Surveyor, in 1859; the official survey is represented on the township plat approved December 20, 1859.

The east boundary of the township was resurveyed under the direction of the General Land Office in connection with the dependent resurvey of T. 38 N., R. 12 E., in 1937; the plat of the resurvey was approved December 12, 1941. The north boundary of sections 1, 2, and 3 was resurveyed in connection with the dependent resurvey of the east half of T. 39 N., R. 11 E., which was executed concurrently with the present resurvey. The following field notes are those of the dependent resurvey of the remaining lines necessary to complete the resurvey of the boundaries of sections 1, 2, 11, 12, 13, 14, 23, 24, 25, 26, 35, and 36 of the township.

The resurvey is a complete restoration of the original boundary and subdivisional lines in their true, original positions, in accordance with the identified evidence of the original survey.

Before restoring the corners, the lines of the original survey were retraced and diligent search made for any evidence of the original corner posts, bearing trees, and other calls of the original field note record. When duly identified, the corner positions were remonumented and new bearing trees marked.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations, but not until exhausting every reasonable possibility of finding direct evidence for the control of each particular corner. The true lines, thus adjusted to the identified original evidence, were then duly run and marked through the timber.

The retracement data were submitted for office examination and verification prior to the conclusion of the field work. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed resurvey.

Survey commenced August 21, 1941, and executed with a light mountain solar transit made by Buff and Buff, Serial No. 19424, constructed in accordance with the standard specifications of the General Land Office. The horizontal circle has a diameter of 4½ ins., with two double opposite verniers reading to single minutes; the vertical circle has a diameter of 4 inches, with one double vernier reading to single minutes. The instrument is equipped with the improved Smith solar attachment, radius of latitude arc 3 inches, and of declination arc 3½ inches, each with verniers reading to single minutes. The instrument was in good condition and was placed in satisfactory adjustment prior to the beginning of the survey.

The directions of the random and true lines were determined by the solar transit method. The measurements were made with a Lallie steel tape, 5 chains in length, graduated every link for the first 100 links, and thereafter at intervals of ten links. The tape was tested by comparison with a Keuffel and Esser Standard tape and found correct. The measurements were made on the slope, and the vertical angle of each interval was ascertained by a clinometer in good adjustment; the horizontal equivalents only are entered in this field note record.

For description of camp meridian, and for test of instrument, see field notes of the Dependent Resurvey of T. 39 N., R. 12 E., Wisconsin, which was executed concurrently with the present resurvey.

27

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

$$\begin{array}{r} S\ 23 \\ \frac{1}{4} \\ S\ 26 \\ \hline 19\frac{1}{4} \end{array}$$

from which

A dead cedar, 6 ins. diam., bears N. $73\frac{1}{2}^{\circ}$ E., 69 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.

A white pine, 10 ins. diam., bears S. $0\frac{1}{4}^{\circ}$ W., 293 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.

- 45.90 Leave swamp, bears N. and S.
- 51.70 Enter swamp, bears N. 20° W. and S. 20° E.
- 53.90 Leave swamp, bears N. 20° E. and S. 20° W.; thence over rolling land.
- 60.95 Road, bears S. and N., 1.25 chs. dist. turns W.
- 65.50 Enter swamp, bears N. and S.
- 67.15 Creek, 10 lks. wide, course N.
- 69.10 Leave swamp, bears N. and S.
- 76.00 Gradually enter road, bearing E. and W.
- 81.32 SE. cor. of a fence, bears N., $40\frac{1}{2}$ lks. dist.
- 81.79 The cor. of secs. 22, 23, 26 and 27.
- Land, level and rolling.
Soil, sandy clay, 2nd and 3rd rate.
Timber, spruce, tamarack, pine, maple, birch and poplar; undergrowth, young timber, alder and willow.
-
- N. $0^{\circ} 07'$ W., bet. secs. 22 and 23.
- Over rolling land, in a road, bearing E. and W.
- 0.37 $\frac{1}{2}$ SE. cor. of a fence, bears E., 47 lks. dist.; leave road, enter timber and undergrowth.
- 4.00 Enter pot hole, bears E. and W.
- 7.10 Leave pot hole, bears E. and W.; thence near E. edge of clearing.
- 13.60 Enter swamp, bears NW. and SE.
- 18.10 Enter creek, 15 lks. wide, winding N. along line from SE.
- 23.00 Leave creek, course NW. from S.
- 28.50 Leave swamp to island of high land between swamps.
- 30.30 Enter swamp, bears NW. and SE.

Dependent Resurvey of a Portion of T. 38 N., R. 11 E.,
Fourth Prin. Mer., Wisconsin.

I repeat the tests of the area daily, when conditions are favorable, by noon observation, and verify the meridional indications of the solar attachment at frequent intervals throughout the survey.

The magnetic declination was found to be approximately $2^{\circ} 45'$ E.

The geographic position of the southeast corner of the township was determined from the data furnished to be as follows: latitude $45^{\circ}43'25''$ N., and longitude $89^{\circ}02'50''$ W.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

37.80

Right bank of creek, 1.50 chs. wide, source E.; creek affected here by flowage from Eagle River.

40.78

The $\frac{1}{4}$ sec. cor., as determined from the remains of an original bearing tree.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 22 | S 23
 1941

from which

The remains of an original bearing tree,

A tamarack stump, 6 ins. diam., bears S. 61° W., 11 lks. dist., mkd. $\frac{1}{4}$ S B T.

And new bearing trees,

A Norway pine, 20 ins. diam., bears N. $88\frac{1}{2}^{\circ}$ E., 105 lks. dist., mkd. $\frac{1}{4}$ S 23 B T.

A tamarack, 5 ins. diam., bears N. $61\frac{3}{4}^{\circ}$ W., 297 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S 22 B T.

N. 2° 16' W., bet. secs. 22 and 23 (N. half mile).

34.50

Leave swamp, bears E. and W.

38.54

The cor. of secs. 14, 15, 22 and 23, which is an iron pipe, 1 in. diam., 14 ins. above ground, set at NE. cor. of timber cutting.

In place of pipe,

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, (with pipe set W. and alongside) for cor. of secs. 14, 15, 22 and 23, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

T 38 N R 11 E
 S 15 | S 14
 S 22 | S 23
 1941

from which

A stump hole, bears N. 57° E., 6 lks. dist.

A stump hole, bears S. 65° E., 25 lks. dist.

These stump holes agree in position with the record of the position of the original bearing trees, and the iron pipe is accepted as having been set from the trees.

And new bearing trees,

A white pine, 14 ins. diam., bears N. $65\frac{1}{2}^{\circ}$ E., 117 lks. dist., mkd. T 38 N R 11 E S 14 B T.

3

Dependent Resurvey of the S. Bdy., Secs. 35 and 36,
T. 38 N., R. 11 E., Wisconsin.

Chains

Dependent Resurvey of the South Boundary of Sections 35
and 36, Township 38 North, Range 11 East, Fourth Principal
Meridian, Wisconsin.

Reestablishment of Surveys Executed by Hiram
C. Fellows, Deputy Surveyor, in July, 1859.

From the cor. of Tps. 37 and 38 N., Rs. 11 and 12 E., which is a
concrete monument, 6 ins. diam., 5 ins. above ground, firmly set,
with brass tablet, 3½ ins. diam., embedded in top, marked and wit-
nessed as described in the official record.

N. 81° 35' W., bet. secs. 1 and 36, marking and blazing the true
line.

Over rolling land, through timber and undergrowth.

- 1.00 Enter swamp, bears NW. and SE.
 - 14.70 Leave swamp, bears N. and S.
 - 24.80 Enter swamp, bears N. and S.
 - 31.90 Leave swamp, bears NE. and SW.
 - 39.19 The ¼ sec. cor., as determined from the remains of the original
bearing trees.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground,
for ¼ sec. cor., with brass cap mkd.

S 36
¼ —————
S 1

1941

from which

The remains of the original bearing trees,

A stump hole, bears N. 40° E., 18 lks. dist.

A hemlock, 16 ins. diam., bears S. 40° W., 20 lks. dist.,
mkd. ¼ S.

And new bearing trees,

A hemlock, 14 ins. diam., bears N. 25½° W., 51 lks. dist.,
mkd. ¼ S 36 B T.

A maple, 18 ins. diam., bears S. 74° E., 23 lks. dist., mkd.
¼ S 1 B T.

N. 88° 38' W., bet. secs. 1 and 36 (W. half mile).

- 4.30 Enter swamp, bears NE. and SW.
- 8.80 Leave swamp, bears N. and S., turning SW.
- 27.65 Blazed foot trail, bears N. and S.
- 31.50 Enter swamp, bears N. and S.

29
Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

A Norway pine, 12 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ E., 126 $\frac{1}{2}$ lks. dist.,
mkd. T 38 N R 11 E S 23 B T.

A white pine, 6 ins. diam., bears S. $81\frac{1}{4}^{\circ}$ W., 110 lks. dist.,
mkd. T 38 N R 11 E S 22 B T.

A Norway pine, 12 ins. diam., bears W. $20\frac{1}{4}^{\circ}$ W., 45 lks. dist.,
mkd. T 38 N R 11 E S 15 B T.

Land, rolling and level.

Soil, sandy clay, 2nd and 3rd rate.

Timber, spruce, tamarack, pine, maple, birch and poplar; under-
growth, young timber, hazel and alder.

From the cor. of secs. 13, 14, 23 and 24.

N. 88° 14' W., bet. secs. 14 and 23.

Over level swamp land, through timber and undergrowth. The creek
from Elm Lake enters this swamp in sec. 24 and spreads throughout
the swamp; no attempt was made to determine the channel on any of
the lines in the swamp.

6.50 Leave swamp, bears N. and S.; thence over ridge from S.

11.70 Enter swamp, bears NE. and SW.

16.00 Leave timber, enter open swamp, bears NE. and SW.

26.70 Left bank of The Thoroughfare, bears NE. and SW., course SW. from
Whitefish Lake to Eagle River; affected here by flowage from Eagle
River.

31.50 Right bank of The Thoroughfare, bears S. and N., turning NE.

34.00 S. end of a point of timber and undergrowth from N.

40.98 The $\frac{1}{4}$ sec. cor., as determined from the remains of the original
bearing trees.

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with an iron post, 23 ins. long, 1 in.
diam., embedded in center, with brass cap mkd.

$$\begin{array}{r} S\ 14 \\ \frac{1}{4} \text{---} \\ S\ 23 \\ 1941 \end{array}$$

from which

The remains of the original bearing trees,

A tamarack stump, 9 ins. diam., bears N. 70° W., 9 lks. dist.

A tamarack stub, 8 ins. diam., bears S. 5° E., 17 lks. dist.,
mkd. $\frac{1}{4}$ S (Record bearing S. 5° W.).

And new bearing trees,

A cedar, 8 ins. diam., bears N. 71° E., 448 lks. dist., mkd.
 $\frac{1}{4}$ S 14 B T.

A spruce, 8 ins. diam., bears N. $88\frac{1}{2}^{\circ}$ W., 481 $\frac{1}{2}$ lks. dist.,
mkd. $\frac{1}{4}$ S 23 B T.

4

Dependent Resurvey of the S. Bdy., Secs. 35 and 36,
T. 38 N., R. 11 E., Wisconsin.

Chains

42.50

The preserved original cor. of secs. 1, 2, 35 and 36, which is marked by an iron pipe, 2 $\frac{1}{2}$ ins. diam., 24 ins. above ground, firmly set at intersection of old blazed lines from N., S., E. and W., with cap mkd.

T 38	
S 35	S 36
—	
S 2	S 1
T 37	

This cor. was established from the original bearing trees, as stated by Roger Smith, cruiser, Rhinelander, Wisconsin, who has known the cor. for 35 years and remembers seeing the original bearing trees.

In place of pipe,

Set a concrete monument, 3 ft. long, 4 ins. diam., 28 ins. in the ground, (and set the pipe S. and alongside) for cor. of secs. 1, 2, 35 and 36, with an iron post, 3 ft. long, 1 in. diam., embedded in center, with brass cap mkd.

T 38 N R 11 E	
S 35	S 36
—	
S 2	S 1
T 37 N	

1941

from which

A cedar, 6 ins. diam., bears N. 59 $\frac{1}{2}$ ° E., 53 $\frac{1}{2}$ lks. dist., mkd.
T 38 N R 11 E S 36 B T.

A cedar, 6 ins. diam., bears S. 21 $\frac{1}{2}$ ° E., 34 lks. dist., mkd.
T 37 N R 11 E S 1 B T.

A cedar, 10 ins. diam., bears S. 48 $\frac{3}{4}$ ° W., 51 lks. dist., mkd.
T 37 N R 11 E S 2 B T.

A maple, 7 ins. diam., bears N. 45° W., 56 lks. dist., mkd.
T 38 N R 11 E S 35 B T.

Land, rolling and level.

Soil, sandy and stony clay, 2nd and 3rd rate.

Timber, cedar, balsam, spruce, hemlock, maple and poplar; undergrowth, young timber and alder.

N. 88° 51' W., bet. secs. 2 and 35.

Over level swamp land, through timber and undergrowth.

4.00

Leave swamp, bears NE. and SW.

28.50

Enter Eagle River swamp, bears NW. and S.

29.15

Right bank of Eagle River, 85 lks. wide, course NW. from S.

32.00

Leave swamp, bears NW. and S.

30

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

- N. 86° 18' W., bet. secs. 14 and 23 (W. half mile).
- 4.60 Leave swamp, bears N. 20° E. and S. 20° W.; thence over rolling land, through timber and undergrowth.
- 29.56 Right bank of Eagle River, 5.00 chs. wide, course NW. from S.; river affected here by flowage from Big Lake.
- 34.56 Left bank of river, bears NW. and SE.
- 42.16 The cor. of secs. 14, 15, 22 and 23.
Land, level and rolling.
Soil, sandy clay, 2nd and 3rd rate.
Timber, spruce, cedar, pine, birch and poplar; undergrowth, young timber and alder.
-
- N. 2° 19' W., bet. secs. 14 and 15.
Over rolling land, through timber and undergrowth.
- 3.30 Left bank of Eagle River, bears E. and W., course W.
- 9.15 Right bank of river, bears E. and W.; river affected here by flowage from Big Lake; thence line follows near a fence.
- 14.00 Enter pot hole, 1.00 ch. wide.
- 14.90 Leave pot hole.
- 27.30 Woods road, bears N. 23° W. and S. 23° E.
- 29.32 Fence, bears E. and W.
- 38.01 Woods road, bears NW., turning W., and S. 15° E.; old railroad grade, bears N. 80½° E. and S. 80½° W.
- 38.56 The preserved original ¼ sec. cor., which is marked by an iron pipe, 1 in. diam., 4 ins. above ground. This cor. was established from the original bearing trees, as stated by Adolph Kloes, local surveyor, Three Lakes, Wisconsin.
In place of pipe,
Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, (with pipe set alongside) for ¼ sec. cor., with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.
- $$\begin{array}{c} \frac{1}{4} \\ \hline S\ 15 \quad | \quad S\ 14 \\ \hline 1941 \end{array}$$
- from which
- A Norway pine, 12 ins. diam., bears N. 33½° E., 90 lks. dist., mkd. ¼ S 14 B T.
- A Norway pine, 10 ins. diam., bears N. 48½° W., 140½ lks. dist., mkd. ¼ S 15 B T.

Dependent Resurvey of the S. Ely., Secs. 35 and 36,
T. 38 N., R. 11 E., Wisconsin.

Chains

40.98

The $\frac{1}{4}$ sec. cor., as determined from the remains of an original bearing tree.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} 8 \ 35 \\ \frac{1}{4} \\ \hline 8 \ 2 \\ 1941 \end{array}$$

from which

The remains of an original bearing tree,

A fallen hemlock, 10 ins. diam., bears N. 40° W., 7 lks. dist., mkd. $\frac{1}{4}$ S.

And new bearing trees,

A spruce, 10 ins. diam., bears N. $24\frac{1}{4}^{\circ}$ E., 72 lks. dist., mkd. $\frac{1}{4}$ S 35 B T.

A balsam, 8 ins. diam., bears S. $53\frac{1}{4}^{\circ}$ E., 64 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.

S. $88^{\circ} 57'$ W., bet. secs. 2 and 35 (W. half mile).

9.00 Enter swamp, bears N. and S.

20.00 Leave swamp, bears N. and S.

30.80 Logging road, bears NE. and SW.

38.57 Proportionate distance; there is no remaining evidence of the original cor. Point for cor. falls at local post, 4 ins. sq., 36 ins. above ground, set by Melendy, local surveyor, about 1910, cor. falls on semi-swampy land.

Set a concrete monument, 3 ft. long, 4 ins. diam., 27 ins. in the ground, for cor. of secs. 2, 3, $3\frac{1}{4}$ and 35, with an iron post, 3 ft. long, 1 in. diam., embedded in center, with brass cap mkd.

$$\begin{array}{r} T \ 38 \ N \ R \ 11 \ E \\ S \ 3\frac{1}{4} \ | \ S \ 35 \\ \hline S \ 3 \ | \ S \ 2 \\ T \ 37 \ N \end{array}$$

1941

from which

A spruce, 4 ins. diam., bears N. $32\frac{1}{2}^{\circ}$ E., $35\frac{1}{2}$ lks. dist., mkd. T 38 N R 11 E S 35 B T.

A cedar, 12 ins. diam., bears S. $8\frac{1}{2}^{\circ}$ E., $162\frac{1}{2}$ lks. dist., mkd. T 37 N R 11 E S 2 B T.

A yellow birch, 7 ins. diam., bears S. 71° W., $53\frac{1}{2}$ lks. dist., mkd. T 37 N R 11 E S 3 B T.

31
Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 38 N., R. 11 E., Wisconsin.

Chains

N. 2° 43' W., bet. secs. 14 and 15 (N. half mile).

2.14 Enter swamp, bears E. and W.

2.44 The meander cor. of frac. secs. 14 and 15, on the S. shore of Virgin Lake, as determined from the remains of the original bearing trees.

Set a concrete monument, 3 ft. long, 4 ins. diam., 27 ins. in the ground, for meander cor. of frac. secs. 14 and 15, with an iron post, 3 ft. long, 1 in. diam., embedded in center, with brass cap mkd.

M C	
8 15	8 14
T 38 N	R 11 E
1941	

from which

The remains of the original bearing trees,

A stump hole, bears S. 6° E., 45 lks. dist. (Record bearing, S. 2° E).

A dead Norway pine, 12 ins. diam., bears S. 12° W., 41 lks. dist., with scribe marks 38 N R 11 E legible. (Record bearing, S. 9° W.).

And new bearing trees,

A Norway pine, 12 ins. diam., bears S. 7 $\frac{1}{2}$ ° E., 98 lks. dist., mkd. T 38 N R 11 E S 14 MC B T.

A Norway pine, 12 ins. diam., bears S. 45° W., 139 $\frac{1}{2}$ lks. dist., mkd. T 38 N R 11 E S 15 MC B T.

The meander cor. of frac. secs. 10 and 11, on the NW. shore of Virgin Lake, hereinafter described, bears N. 8° 52' W., 51.85 chs. dist.

Land, rolling.

Soil, sandy clay, 2nd rate.

Timber, pine, hemlock, birch, maple, and poplar; undergrowth, young timber.

From the point for the cor. of secs. 11, 12, 13, and 14, in Whitefish Lake, as determined by proportionate measurement.

N. 88° 06' W., bet. secs. 11 and 14.

Over Whitefish Lake.

8.58

The local meander cor. of frac. secs. 11 and 14, on the NW. shore of Whitefish Lake, which is an iron pipe, 1 in. diam., projecting 12 ins. above ground, accepted as marking the direction of the line bet. secs. 11 and 14.

In place of the iron pipe,

Dependent Resurvey of the S. Bdy., Secs. 35 and 36,
T. 38 N., R. 11 E., Wisconsin.

Chains

A hemlock, 14 ins. diam., bears N. 49° W., 95 lks. dist.,
mkd. T 38 N R 11 E S 34 B T.

A local cor., bears S. 70° W., 226½ lks. dist., an iron pipe,
2½ ins. diam., 24 ins. above ground, firmly set, with cap
mkd.

	T 38	
S 34		S 35
S 3		S 2
	T 37	

This cor. is set by a very old wooden post rotted off at
ground, and there is a local cedar bearing tree with 25
year ring count.

Land, rolling and level.

Soil, sandy and stony clay, 2nd and 3rd rate.

Timber, cedar, balsam, spruce, hemlock, birch, maple, poplar and
scattering pine; undergrowth, young timber and alder.

S. 88° 57' W., bet. secs. 3 and 34, on a connecting line, searching
for original evidence.

Over level semi-swamp land, through timber and undergrowth.

0.90 Enter swamp, bears N. and S.

8.45 Leave swamp, bears N. and S.

18.60 Enter swamp, bears NE. and SW.

21.00 Leave swamp, bears N. and S.

23.90 Enter swamp, bears N. and S.

35.60 Leave swamp, bears NE. and SW.

38.57 The ¼ sec. cor., as determined from the remains of the original
bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground,
for ¼ sec. cor., with brass cap mkd.

	S 34
¼	—
	S 3
	1941

from which

The remains of the original bearing trees,

A stump hole, bears N. 30° W., 18 lks. dist.

A rotted balsam stump, bears S. 45° E., 10 lks. dist., with
slab of tree with old blaze lying by stump.

And new bearing trees,

A balsam, 4 ins. diam., bears N. 57° E., 111 lks. dist., mkd.
¼ S 34 B T.

A poplar, 8 ins. diam., bears S. 64½° W., 36 lks. dist., mkd.
¼ S 3 B T.

32
Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for witness point on the line bet. secs. 11 and 14, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

T 38 N
S 11

S 14
R 11 E W P

1941

from which

A hemlock, 20 ins. diam., bears S. $44\frac{1}{2}^{\circ}$ W., 29 lks. dist., mkd. W P T 38 N R 11 E S 14 B T.

A hemlock, 12 ins. diam., bears N. $28\frac{3}{4}^{\circ}$ W., 38 lks. dist., mkd. W P T 38 N R 11 E S 11 B T.

The iron pipe was reset W. and alongside of the concrete monument.

N. $88^{\circ} 34'$ W., bet. secs. 11 and 14.

Over rolling land, through timber and undergrowth.

- 2.00 Enter Patrick Sullivan's yard.
- 4.60 Leave yard.
- 6.80 Road, bears N. $57\frac{1}{2}^{\circ}$ E. and S. $57\frac{1}{2}^{\circ}$ W.
- 7.05 Fence, parallel to road.
- 13.50 House, bears N., 90 lks. dist.
- 16.13 State Highway No. 32, bears N. 47° W., and S. 47° E.
- 23.92 Old railroad grade, bears N. 33° W. and S. 33° E.
- 34.24 Road, bears N. $3\frac{1}{2}^{\circ}$ W. and S. 26° W.
- 34.41 The point for the $1/4$ sec. cor., as established by local surveyor, according to the testimony of Adolph Kloes, a surveyor, of Three Lakes, Wisconsin, as determined in longitudinal position by a fence line which bears N.; the testimony of Mr. Kloes is accepted as the best evidence now available of the position of the original cor.

Deposit a granite stone, 7 x 8 x 12 ins., 30 ins. in the ground, with a cross (X) marked on top, in ditch on W. side of road.
- N. $87^{\circ} 53'$ W., bet. secs. 11 and 14 (W. half mile).
- 0.16 Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, for witness $1/4$ sec. cor., with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

W C
S 11

S 14
1941

from which

7
Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

Dependent Resurvey of a Portion of the Subdivisional
Lines of Township 38 North, Range 11 East, Fourth
Principal Meridian, Wisconsin.

Reestablishment of Surveys Executed by William
E. Daugherty, Deputy Surveyor, in August and
September, 1859.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.

N. $0^{\circ} 31'$ W., bet. secs. 35 and 36, marking and blasing the true line.

Over level swamp land, through timber and undergrowth.

8.20 Leave swamp, bears NW. and SE.; thence over gently rolling land and low level land.

36.70 Enter swamp, bears NE. and SW.

40.39 Proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 35 \quad | \quad S\ 36 \\ 1941 \end{array}$$

from which

A cedar, 7 ins. diam., bears N. 62° E., 63 lks. dist., mkd.
 $\frac{1}{4}$ S 36 B T.

A spruce, 7 ins. diam., bears N. 25° W., $57\frac{1}{2}$ lks. dist., mkd.
 $\frac{1}{4}$ S 35 B T.

66.55 Right bank of Eagle River, 70 lks. wide, course E.

80.78 Proportionate distance; there is no remaining evidence of the original cor.

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

$$\begin{array}{c} T\ 38\ N \quad R\ 11\ E \\ S\ 26 \quad | \quad S\ 25 \\ \hline S\ 35 \quad | \quad S\ 36 \\ 1941 \end{array}$$

from which

A balsam, 6 ins. diam., bears N. $42\frac{1}{2}^{\circ}$ E., 80 lks. dist., mkd.
T 38 N R 11 E S 25 B T.

A cedar, 9 ins. diam., bears S. $11\frac{1}{2}^{\circ}$ E., 301 lks. dist., mkd.
T 38 N R 11 E S 36 B T.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin

Chains

A hemlock, 14 ins. diam., bears N. $5\frac{1}{2}^{\circ}$ W., 118 $\frac{1}{2}$
lks. dist., mkd. W C $\frac{1}{4}$ S 11 B T.

A maple, 5 ins. diam., bears S. $3\frac{1}{2}^{\circ}$ W., 19 $\frac{1}{2}$ lks.
dist., mkd. W C $\frac{1}{4}$ S 14 B T.

5.45

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the
ground, for witness meander cor. of frac. secs. 11 and 14, on the E.
shore of Virgin Lake, with an iron post, 23 ins. long, 1 in. diam.,
embedded in center, with brass cap mkd.

W C
T 38 N
S 11
M C / S 14
R 11 E

1941

from which

A norway pine, 10 ins. diam., bears N. $18\frac{1}{4}^{\circ}$ E.,
34 lks. dist., mkd. W C T 38 N R 11 E S 11 M C B T.

A hemlock, 9 ins. diam., bears S. $45\frac{1}{2}^{\circ}$ E., 55
lks. dist., mkd. W C T 38 N R 11 E S 14 M C B T.

5.55

A meander cor. of frac. secs. 11 and 14, on the E. shore of Virgin
Lake, and the NW. cor. of a lot subdivision, which is a wooden post,
12 ins. high, 2 ins. square, set by a local surveyor. The post has
long been recognized by all interested persons as marking the
meander cor., and is accepted as the best evidence now available
of the position of the section line. The point falls on a bank $1\frac{1}{2}$
ft. high, too near the water for permanent monumentation.

From this point, the meander cor. of frac. secs. 14 and 15, on the
S. shore of Virgin Lake, bears S. $45^{\circ}22'$ W., 45.14 chs. dist.

19.17

Record distance to meander cor., falls in lake.

Land, rolling.

Soil, sandy and stony claim, 2nd and 3rd rate.

Timber, pine, hemlock, birch, maple, and poplar;
undergrowth, young timber.

The meander cor. of frac. secs. 10 and 11, on the NW. shore of
Virgin Lake, is marked by an iron pipe, 1 in. diam., projecting
14 ins. above ground, set by a local surveyor, from original
bearing trees.

In place of the iron pipe,

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the
ground, for meander cor. of frac. secs. 10 and 11, with an iron
post, 23 ins. long, 1 in. diam., embedded in center, with brass
cap mkd.

T 38 N | R 11 E
S 10 | S 11
M C
1941

from which

The remains of the original bearing trees,

L 3 6 8

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

A balsam, 5 ins. diam., bears S. $89\frac{1}{2}^{\circ}$ W., 61 lks. dist., mkd.
T 38 N R 11 E S 35 B T.

A cedar, 11 ins. diam., bears N. $57\frac{1}{2}^{\circ}$ W., 196 lks. dist., mkd.
T 38 N R 11 E S 26 B T.

Land, level and gently rolling.

Soil, sandy clay, 3rd rate.

Timber, cedar, balsam, spruce, tamarack, maple, birch and poplar;
undergrowth, young timber and alder.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.,
which is a concrete monument, 6 ins. diam., 2 ins. above ground,
firmly set, with brass tablet, $3\frac{1}{2}$ ins. diam., embedded in top, mkd.
and witnessed as described in the official record.

N. 84° 23' W., bet. secs. 25 and 36.

Over level swamp land, through timber and undergrowth.

22.20 Leave swamp, bears N. and S.; thence over rolling land.

40.97 Proportionate distance; there is no remaining evidence of the
original cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground,
for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} S 25 \\ \frac{1}{4} \hline S 36 \\ 1941 \end{array}$$

from which

A hemlock, 12 ins. diam., bears N. 64° E., 7 lks. dist., mkd.
 $\frac{1}{4}$ S 25 B T.

A cedar, 10 ins. diam., bears S. 68° E., 16 lks. dist., mkd.
 $\frac{1}{4}$ S 36 B T.

43.55 Enter swamp, bears N. and S.

46.25 Leave swamp, bears N. and S.

58.00 Enter swamp, bears N. and S.

65.95 Low ridge, bears N. and S., extending N. about 2.00 chs. in swamp.

72.65 Right bank of Eagle River, 100 lks. wide, course N.

81.94 The cor. of secs. 25, 26, 35 and 36.

Land, level and rolling.

Soil, sandy and stony clay, 2nd and 3rd rate.

Timber, cedar, spruce, hemlock, pine, birch and poplar; undergrowth,
young timber and alder.

Dependant Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin

Chains	<p>A pine stump, 20 ins. diam., bears N. 44° E., 18 lks. dist. (Record bearing, N. 40° E.).</p> <p>A pine stump, 22 ins. diam., bears N. 55° W., 33 lks. dist. (Record bearing, N. 57° W.).</p> <p>And new bearing trees,</p> <p>A red oak, 5 ins. diam., bears N. 16½° E., 14 lks. dist., mkd. T 38 N R 11 E S 11 M C B T.</p> <p>A Norway pine, 24 ins. diam., bears N. 45½° W., 40 lks. dist., mkd. T 38 N R 11 E S 10 M C B T.</p> <p>The meander cor. of frac. secs. 11 and 14, on the E. shore of Virgin Lake, bears S. 64° 03' E., 44.60 chs. dist.</p> <p>The iron pipe was reset W. and alongside of the monument. N. 1°10' W., bet. secs. 10 and 11.</p> <p>Over rolling land, through timber and undergrowth.</p>
8.40	Road, bears S. 35° W., and N. 35° E., turning N.; line follows near W. side of road.
17.76	Junction of roads bears E., 50 lks. dist.; roads bear N. 80° E., S. 80° W., and S.
19.16	The 1/4 sec. cor., as determined from the remains of the original bearing trees.
	Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for 1/4 sec. cor., with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ \text{S 10} \mid \text{S 11} \\ 1941 \end{array}$
	from which
	The remains of the original bearing trees,
	A pine stump, 20 ins. diam., bears N. 50° E., 30 lks. dist., mkd. ¼ B T. (Record bearing, N. 15° E.).
	A Norway pine, 18 ins. diam., bears S. 43½° W., 49 lks. dist., mkd. ¼ S B T. (Record bearing, S. 36° W.). I remark this tree ¼ S. 10 B T.
	And a new bearing tree,
	A white pine, 14 ins. diam., bears S. 75¼° E., 113 lks. dist., mkd. ¼ S 11 B T.
	A local cor., which is a well casing pipe, 6 ins. diam., projecting 24 ins. above ground, filled with concrete, bears N. 80° W., 2½ lks. dist.
	N. 2°48' W., bet. secs. 10 and 11 (N. half mile).
0.30	Enter swamp, bears N. 80° E. and S. 80° W.
2.10	Leave swamp, bears NW. and SE.

9
Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains	N. 0° 35' W., bet. secs. 25 and 26. Over level swamp land, through timber and undergrowth.
5.80	Leave swamp, bears E. and W., thence over rolling land.
15.70	Enter swamp, bears N. 60° E. and S. 60° W.
17.00	Leave swamp, bears N. 60° E. and S. 60° W.
18.80	Enter swamp, bears E. and W.
26.80	Leave swamp, bears E. and W.
31.70	Enter swamp, bears E. and W.
34.30	Left bank of Eagle River, 80 lks. wide, course N. 80° W.
40.39	Proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;">$\frac{1}{4}$ S 26 S 25 1941</div> from which A poplar, 6 ins. diam., bears N. 60° E., 11 lks. dist., mkd. $\frac{1}{4}$ S 25 B T. A white birch, 5 ins. diam., bears S. 75 $\frac{1}{2}$ ° W., 21 lks. dist., mkd. $\frac{1}{4}$ S 26 B T. At $\frac{1}{4}$ sec. cor., leave swamp, bears NW. and SE.; thence over rolling land.
47.75	Enter semi-swamp, bears E. and W.
52.75	Enter swamp, bears E. and W.
62.80	Leave swamp, bears E. and W.
80.48	Enter swamp, bears NE. and SW.
80.78	The cor. of secs. 23, 24, 25 and 26, which is a cedar post, 4 ins. sq., 4 ft. above ground, marked S 23 on NW., S 24 on NE., S 25 on SE. and S 26 on SW. face. This cor. was established by a local surveyor several years ago and was found to be acceptably located by the proper methods as evidenced by the retracements. In place of post, Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, and set the marked post S. and alongside, for cor. of secs. 23, 24, 25 and 26, with brass cap mkd. <div style="text-align: center;">T 38 N R 11 E S 23 S 24 S 26 S 25 1941</div> L 3 6 8 from which

35
Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

- 5.50 Enter same swamp, bears NE. and SW.
- 6.30 Leave swamp, bears N. 60° E. and S. 60° W.
- 8.00 Woods road, bears E. and W.
- 12.35 Enter swamp, bears N. 70° E. and W.
- 21.85 Leave swamp, bears S. 80° E. and N. 80° W.
- 27.20 State highway No. 32, bears N. 77° W. and S. 77° E.
- 29.76 Junction of woods roads, bearing W., NE. and SE.
- 37.40 Intersect the S. shore of a bay of Big Stone Lake. This bay covers a former swamp area, which is submerged because the water level of the lake has been raised by the construction of a dam.
- Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for witness cor. of secs. 2, 3, 10 and 11, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.
- | | |
|--------|--------|
| W | C |
| T 38 N | R 11 E |
| S 3 | S 2 |
| S 10 | S 11 |
- 1941
- from which
- A cedar, 10 ins. diam., bears N. 69½° E., 74 lks. dist., mkd.
W C T 38 N R 11 E S 11 B T.
- A hemlock, 16 ins. diam., bears S. 35½° E., 59 lks. dist.,
mkd. W C T 38 N R 11 E S 11 B T.
- A white birch, 10 ins. diam., bears S. 39° W., 34 lks. dist.,
mkd. W C T 38 N R 11 E S 10 B T.
- A white pine, 16 ins. diam., bears N. 80½° W., 164 lks. dist.,
mkd. W C T 38 N R 11 E S 10 B T.
- Thence over bay of lake.
- 41.37 The point for the original cor. of secs. 2, 3, 10 and 11, as determined from a tie to the cor. as shown on Big Stone Plat, which is a plat of a subdivision, on the E. shore of Big Stone lake, sec. 2, T. 38 N., R. 11 E., executed by G.A. Kloes, local surveyor, Three Lakes, Wisconsin, subscribed and sworn to July 7, 1931. Mr. Kloes states this cor. was in existence prior to the raising of the water level of the lake, and that the meander cor. bet. secs. 3 and 10 was also in place, with the original bearing trees at both cors., and he further states that he had never seen the S. meander cor. bet. secs. 2 and 3.
- Land, rolling and level.
Soil, sandy clay, 2nd and 3rd rate.
Timber, pine, spruce, cedar, hemlock, birch, oak and poplar; undergrowth, young timber and alder.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

A spruce, 5 ins. diam., bears N. 44° E.; 69 lks. dist., mkd.
T 38 N R 11 E S 24 B T.

A spruce, 6 ins. diam., bears S. $53\frac{1}{2}^{\circ}$ E., 21 $\frac{1}{2}$ lks. dist., mkd.
T 38 N R 11 E S 25 B T.

A spruce, 6 ins. diam., bears S. 21° W., 21 lks. dist., mkd.
T 38 N R 11 E S 26 B T.

A spruce, 4 ins. diam., bears N. $64\frac{3}{4}^{\circ}$ W., 57 lks. dist., mkd.
T 38 N R 11 E S 23 B T.

Land, level and rolling.

Soil, sandy and stony clay, 2nd and 3rd rate.

Timber, pine, spruce, birch, and poplar; undergrowth, young timber
and alder.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.,
which is an iron post, 2 ins. diam., 8 ins. above ground, firmly
set, with brass cap mkd. and witnessed as described in the official
record.

N. 83° 24' W., bet. secs. 24 and 25.

Over gently rolling land, through timber and undergrowth.

41.18

Proportionate distance; there is no remaining evidence of the
original cor.

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with an iron post, 23 ins. long, 1 in.
diam., embedded in center, with brass cap mkd.

$$\begin{array}{r} \text{S } 24 \\ \frac{1}{4} \text{ ————— } \\ \text{S } 25 \\ \hline 1941 \end{array}$$

from which

A white birch, 6 ins. diam., bears N. $37\frac{3}{4}^{\circ}$ W., 53 lks. dist.,
mkd. $\frac{1}{4}$ S 24 B T.

A white birch, 5 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ W., 18 lks. dist.,
mkd. $\frac{1}{4}$ S 25 B T.

A local post, 6 ins. sq., 30 ins. above ground, bears
S. $55\frac{1}{2}^{\circ}$ E., 43 $\frac{1}{2}$ lks. dist.

47.36

State highway No. 32, bears N. and S., curving SE.

75.55

Enter swamp, bears N. and S.

80.55

Leave swamp, bears N. and S.

82.06

Enter swamp, bears NE. and SW.

82.36

The cor. of secs. 23, 24, 25 and 26.

Land, gently rolling.

Soil, sandy and stony clay, 2nd and 3rd rate.

Timber, spruce, birch, and poplar; undergrowth, young timber.

36

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains	From the cor. of secs. 1, 2, 11 and 12.
	N. 87° 17' W., bet. secs. 2 and 11.
	Over level swamp land, through timber and undergrowth.
8.00	Leave swamp, bears NE. and S.; thence over rolling land.
10.30	Road, bears S. 60° W. and N. 50° E., curving N. 20° E.
32.30	Enter swamp, bears NW. and SE.
36.10	Leave swamp, bears NE. and SW.
43.74	The local $\frac{1}{4}$ sec. cor., which is a concrete monument, 6 ins. sq., 18 ins. above ground. This cor. was established by Russell, local surveyor, in 1896, has long been recognized by adjoining property owners and is accepted as marking the $\frac{1}{4}$ sec. cor. In place of monument, Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with concrete monument set N. and alongside, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \text{S } 2 \\ \frac{1}{4} \text{ ---} \\ \text{S } 11 \\ \hline 19\frac{1}{4} \end{array}$
	from which
	A white pine, 6 ins. diam., bears N. 60 $\frac{1}{2}$ ° E., 12 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S 2 B T.
	A white pine, 5 ins. diam., bears S. 10 $\frac{1}{2}$ ° E., 91 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.
	N. 86° 56' W., bet. secs. 2 and 11 (W. half mile).
31.50	Road, bears NE. and SW.
37.58	The SW. cor. of the Big Stone Lake subdivision, which is a concrete monument, 6 ins. sq., 12 ins. above ground. This cor. was established on the line bet. secs. 2 and 11, 537 ft. from the cor. of secs. 2, 3, 10 and 11, as shown on the Big Stone Plat, and on the SE. shore of a bay of Big Stone Lake. This bay covers a former swamp area, which is submerged because the water level of the lake has been raised by the construction of a dam.
	Thence over bay of lake.
45.72	The point for the cor. of secs. 2, 3, 10 and 11 falls in lake. Land, level and rolling. Soil, sandy clay, 2nd and 3rd rate. Timber, spruce, pine, birch and poplar; undergrowth, young timber and alder.
	N. 3° 20' E., bet. secs. 2 and 3.
	Over Big Stone Lake by carefully checked triangulation.
12.27	Proportionate distance for the meander cor. of frac. secs. 2 and 3, on the SE. shore of Big Stone Lake, falls in lake.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

N. 0° 09' W., bet. secs. 23 and 24.

Over level swamp land, through timber and undergrowth.

6.05 Scott Creek, 25 lks. wide, course S. 80° W.; enter open swamp N. of creek.


24.80 Leave swamp, bears E. and NW.

28.40 Enter E. edge of swamp, bears N. and SW.

31.60 Leave edge of swamp, bears NW. and S.; thence over rolling land.

40.30½ Proportionate distance; there is no remaining evidence of the original cor. Point for cor. falls by a poplar tree, 10 ins. diam.

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, for ¼ sec. cor., with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.



from which

A poplar, 6 ins. diam., bears N. 60½° E., 12½ lks. dist., mkd. ¼ S 24 B T.

A jack pine, 8 ins. diam., bears S. 17° W., 70 lks. dist., mkd. ¼ S 23 B T.

43.40 Enter swamp, bears E. and W.

45.70 Leave swamp, bears E. and W.

48.30 Enter swamp, bears E. and W.


53.30 Leave swamp, bears E. and W.

74.60 Enter swamp, bears NE. and SW.

80.61 The cor. of secs. 13, 14, 23 and 24, which is a wooden post, 4 ins. sq., 12 ins. above ground.

In place of post,

Set a concrete monument, 3 ft. long, 4 ins. diam., 30 ins. in the ground, (and set the wooden post alongside) for cor. of secs. 13, 14, 23 and 24, with an iron post, 3 ft. long, 1 in. diam., embedded in center, with brass cap mkd.



from which

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

72.20

The point for the original meander cor. of frac. secs. 2 and 3, as determined from the remains of an original bearing tree, on the N. shore of Big Stone Lake, falls in lake due to raising of the water level by the construction of a dam.

from which

The remains of an original bearing tree,

A dead white pine, 20 ins. diam., bears N. 28° W., 50 lks. dist., mkd. T 38 N R 11 E S 3 M C B T.

N. 32° 28' E., bet. secs. 2 and 3 (N. portion).

Over Big Stone Lake.

0.33

Intersect the N. shore of Big Stone Lake.

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for witness meander cor. of frac. secs. 2 and 3, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

W	C
T 38 N	R 11 E
S 3	S 2

M C

1941

from which

A cedar, 6 ins. diam., bears N. 59½° E., 119½ lks. dist., mkd. W C T 38 N R 11 E S 2 M C B T.

A Norway pine, 7 ins. diam., bears N. 64° W., 50½ lks. dist., mkd. W C T 38 N R 11 E S 3 M C B T.

A concrete monument, 6 ins. sq., 8 ins. above ground, bears N. 50½° W., 24 lks. dist.

Thence over level swamp land, through timber and undergrowth.

11.75

Road, bears NW. and SE.

16.80

Leave swamp, bears E. and W.

19.22

The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., which is a concrete monument, 6 ins. diam., 6 ins. above ground, firmly set, with brass cap embedded in top, marked and witnessed as described in the official record.

Land, level and rolling.

Soil, sandy clay, 2nd and 3rd rate.

Timber, cedar, spruce, hemlock, pine, birch and poplar; undergrowth, young timber.

Final Test of Instrument.

October 25, 1941, in camp, at 8 a.m. and 4 p.m., I make proper settings on the arcs of the solar attachment and ascertain that the resulting orientation of the instrument when compared with the meridian as established by observation of Polaris has a maximum error of less than 1' 30".

L368

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

The remains of the original bearing trees,

A tamarack stump, bears S. $32\frac{1}{2}^{\circ}$ E., 51 lks. dist. (Record bearing S. 34° E.).

A dead tamarack, 18 ins. diam., bears N. $72\frac{1}{2}^{\circ}$ W., 29 lks. dist., scribe marks R E S 14 legible. (Record bearing N. 75° W.).

And new bearing trees,

A tamarack, 14 ins. diam., bears N. $87\frac{1}{4}^{\circ}$ E., 48 lks. dist., mkd. T 38 N R 11 E S 13 B T. This is a local bearing tree and the marks S 13 B T are about 10 years old.

A tamarack, 16 ins. diam., bears S. 35° E., $57\frac{1}{2}$ lks. dist., mkd. T 38 N R 11 E S 24 B T.

A white pine, 8 ins. diam., bears S. $79\frac{1}{4}^{\circ}$ W., $233\frac{1}{2}$ lks. dist., mkd. T 38 N R 11 E S 23 B T.

A white pine, 15 ins. diam., bears N. $36\frac{1}{2}^{\circ}$ W., 109 lks. dist., mkd. T 38 N R 11 E S 14 B T.

Land, level and rolling.

Soil, sandy clay, 2nd and 3rd rate.

Timber, spruce, tamarack, pine, birch and poplar; undergrowth, young timber and alder.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., which is an iron post, 2 ins. diam., 10 ins. above ground, firmly set, with brass cap mkd. and witnessed as described in the official record.

N. $77^{\circ} 56'$ W., bet. secs. 13 and 24.

Over gently rolling land, through timber and undergrowth.

25.30 Enter swamp, bears N. 30° E. and S. 30° W.

37.04 The meander cor. of frac. secs. 13 and 24, on the E. shore of a small bay of Elm Lake, as determined from the remains of the original bearing trees.

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for meander cor. of frac. secs. 13 and 24, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

	T 38 N
	S 13
M C	-----
	S 24
	R 11 E

1941

from which

The remains of the original bearing trees,

A fallen, dead tamarack, 6 ins. diam., bears N. $79\frac{3}{4}^{\circ}$ E., 114 lks. dist., with old blaze. (Record bearing N. 81° E.).

38

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

General Description.

At the time of this resurvey the N. and S. center lines of secs. 2, 11, 14, 23, 26 and 35 formed the W. bdy. of the Nicolet National Forest. The surface of the two E. ranges of sections in T. 38 N., R. 11 E. is gently rolling to rolling. Eagle River enters sec. 35 from the S. and flows northerly through secs. 35, 36, 25, 26, 23 and 14, leaving sec. 14 near the SW. cor. Scott Creek enters sec. 24 from the E. and flows westerly joining Eagle River in sec. 26. Lake Julia invades secs. 1 and 12, Virgin Lake lies in secs. 11 and 14 and Whitefish Lake lies in secs. 11, 12, 13 and 14; a creek flows from Lake Julia to Virgin Lake, and one flows from Virgin Lake easterly to Whitefish Lake, and what is known as The Thoroughfare flows southwesterly from Whitefish Lake to Eagle River, joining the river in sec. 23. Elm Lake lies in secs. 13 and 24 and a small creek flows westerly from the lake through secs. 13, 24, 23 and 14 to The Thoroughfare. A small creek drains S. from a swamp in secs. 1, 2, 11 and 12 and empties into Julia Creek in sec. 11. Crooked Lake lies in secs. 26 and 35 and a creek flows northerly through secs. 26 and 23 leaving sec. 23 into sec. 22, then joins Eagle River in sec. 23. Big Stone Lake lies in secs. 2, 11 and 14 and is one of the Eagle River Chain of Lakes. Several swamps are found throughout the area.

The soil is a sandy clay loam, with some stone, varying from 2nd to 3rd rate.

There is a fair growth of young timber from 4 to 12 ins. in size, over most of the area. There is very little virgin timber standing due either to fires or timber cutting in recent years. Norway and white pine, hemlock, birch, maple and poplar are the predominating species of timber with scattering growths of ash, oak and jack pine. Spruce, tamarack and cedar are found in the swamps. The undergrowth is alder and willow with some cherry and hazel.

Some farming is carried on in secs. 1 and 2 and a good farm is located in sec. 35, potatoes being the principal crop. With the exception of Elm Lake there are several cottages on the shores of the lakes.

The area is well supplied with roads. State highway No. 32 traverses through secs. 11, 14, 13, 24 and 25. Roads constructed and maintained by the town of Three Lakes, and roads constructed and maintained by the Forest Service pass through the area. Other trails lead into the woods making all the sections accessible by motor vehicle, excepting sec. 36, which had no road at the time of this resurvey.

Survey Completed October 25, 1941.

13
Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

A fallen, dead tamarack, 6 ins. diam., bears S. $60\frac{1}{2}^{\circ}$ E.,
47 lks. dist., with old blaze. (Record bearing S. 58° E.).

And new bearing trees,

A tamarack, 5 ins. diam., bears N. $81\frac{1}{2}^{\circ}$ E., lks. dist.,
mkd. T 38 N R 11 E S 13 M C B T.

A tamarack, 5 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ W., lks. dist.,
mkd. T 38 N R 11 E S 24 M C B T.

N. $80^{\circ} 07'$ W., bet. secs. 13 and 24.

Over small bay of Elm Lake.

4.25

The $\frac{1}{4}$ sec. cor. and meander cor. of frac. secs. 13 and 24, on W.
shore of a small bay of Elm Lake, as determined from the remains
of an original bearing tree.

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the
ground, for $\frac{1}{4}$ sec. cor. and meander cor. of frac. secs. 13 and 24,
with an iron post, 23 ins. long, 1 in. diam., embedded in center,
with brass cap mkd.

$$\begin{array}{r|l} S\ 13 & \\ \hline \frac{1}{4} & \\ S\ 24 & \\ \hline & MC \\ & 1941 \end{array}$$

from which

The remains of an original bearing tree,

A tamarack stub, 6 ins. diam., bears S. 84° W., 120 lks. dist.,
mkd. $\frac{1}{4}$ S B T. (Record bearing S. 84° E.).

And new bearing trees,

A white pine, 8 ins. diam., bears S. $36\frac{1}{2}^{\circ}$ W., 223 lks. dist.,
mkd. $\frac{1}{4}$ S 24 M C B T.

A white pine, 28 ins. diam., bears N. $75\frac{1}{2}^{\circ}$ W., 383 lks. dist.,
mkd. $\frac{1}{4}$ S 13 M C B T.

A local tamarack post, 4 ins. sq., 36 ins. above ground,
bears S. $27\frac{1}{2}^{\circ}$ E., 22 lks. dist.

N. $85^{\circ} 02'$ W., bet. secs. 13 and 24 (W. half mile).

3.30

Leave swamp, bears N. and S.

9.00

Enter swamp, bears N. and S.

10.23

The meander cor. of frac. secs. 13 and 24, on the SE. shore of Elm
Lake, as determined from the remains of an original bearing tree.

Set a concrete monument, 3 ft. long, 4 ins. diam., 26 ins. in the
ground, for meander cor. of frac. secs. 13 and 24, with an iron
post, 3 ft. long, 1 in. diam., embedded in center, with brass cap
mkd.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

[illegible]

0-8412

14
Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains	
	<div><div><div>T 38 N S 13 M C S 24 R 11 E</div><div>1941</div></div><div>from which</div><div>The remains of an original bearing tree, A fallen, dead tamarack, 6 ins. diam., bears N. 54° E., 70 lks. dist., with old blaze on SW. face. And new bearing trees, A white pine, 28 ins. diam., bears N. 66½° E., 330 lks. dist., mkd. T 38 N R 11 E S 13 M C B T. A spruce, 5 ins. diam., bears S. 63° E., 121½ lks. dist., mkd. T 38 N R 11 E S 24 M C B T.</div></div>
	N. 87° 54' W., bet. secs. 13 and 24. Over Elm Lake.
5.65	Proportionate distance for meander cor. of frac. secs. 13 and 24, on W. shore of Elm Lake, falls on old bank, near mouth of old out- let, which has been closed by a beaver dam; point for cor. falls in about 3 ft. of water; there is no remaining evidence of the original cor.
6.51	Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, for witness meander cor. of frac. secs. 13 and 24, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd. <div><div><div>W C T 38 N S 13 S 24 R 11 E</div><div>M C 1941</div></div><div>from which</div><div>A maple, 8 ins. diam., bears S. 31½° W., 169 lks. dist., mkd. W C T 38 N R 11 E S 24 M C B T. A white pine, 22 ins. diam., bears N. 36½° W., 165 lks. dist., mkd. W C T 38 N R 11 E S 13 M C B T.</div></div>
16.50	Creek, 10 lks. wide, course SW.
19.50	Leave swamp, bears N. and S.
24.64	State highway No. 32, bears N. 37° E. and S. 37° W.
27.40	Enter swamp, bears NE. and SW.
30.83	The cor. of secs. 13, 14, 23 and 24. Land, gently rolling and level. Soil, sandy and stony clay, 2nd and 3rd rate. Timber, pine, hemlock, spruce, tamarack, birch, maple and poplar; undergrowth, young timber and alder.

CERTIFICATE OF SURVEYOR

I, Hugh B. Crawford, Asst. Cadastral Engineer, HEREBY CERTIFY upon honor that, in pursuance of supplemental special instructions bearing date of the 25th day of August, 1941 received from the district cadastral engineer for Eastern District, with assignment instructions dated September 2, 1941, I have ~~surveyed~~ made the Dependent Resurvey of the South Boundary of Sections 35 and 36 and of a Portion of the Subdivisional Lines of T. 38 N., R. 11 E.

of the Fourth Principal Meridian, in the State of Wisconsin, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Washington, D.C.

Hugh B. Crawford

April 22, 1942

Assistant Cadastral Engineer.

CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,

Denver, Colorado, Oct. 1, 1943.

The foregoing field notes of the ~~survey~~ Dependent Resurvey of the South Boundary of Sections 35 and 36 and of a Portion of the Subdivisional Lines of T. 38 N., R. 11 E., Fourth Principal Meridian, Wisconsin

executed by Hugh B. Crawford, Assistant Cadastral Engineer, supplemental under/special instructions dated August 25, 1941, and assignment instructions dated September 2, 1941, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.



Supervisor of Surveys.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in Wisconsin, is a true copy of the original field notes filed in the General Land Office. for file in the public survey office.



Supervisor of Surveys.

L3 6 8

15
Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains					
	<p>Whitefish Lake, a deep, permanent body of water, lying in sections 11, 12, 13, and 14, is not shown on the plat of the original survey of the township. The field notes of the original survey of the lines between secs. 11 and 12, secs. 13 and 14, secs. 11 and 14, and the west half of the line between secs. 12 and 13 are, in part, at least, fictitious. Most of the land in sections 11, 12, 13, and 14 is in private ownership, and part of it, especially near the lake shores, has long been settled and developed. The boundaries of sections 11, 12, 13, and 14 were resurveyed by local surveyors many years ago, and retracements indicate that correct surveying methods were employed. The local surveyors established meander corners on the shores of Whitefish Lake; these corners have been found acceptable in position, and in the present resurvey were remonumented as witness points.</p> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 2° 33' W., bet. secs. 13 and 14.</p> <p>Over level swampy land, through timber and undergrowth.</p>				
6.40	Leave swamp, bears E. and W.; thence over gently rolling land.				
8.00	Enter swamp, bears E. and W.				
13.40	Leave swamp, bears N. 50° W., and S. 50° E.; thence over gently rolling land.				
15.43	State Highway No. 32, bears N. 53° W. and S. 53° E.				
16.05	SE. cor. of woven wire fence; this fence was established about 1928 after resurvey of the section line as agreed upon by the interested property owners; and is accepted as marking the direction of the section line.				
20.00	<p>The S. shore of Whitefish Lake, bears N. 70° E. and S. 80° W., and point for the local meander cor., which was destroyed in the construction of fence.</p> <p>Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, for witness point on line bet. secs. 13 and 14, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.</p> <div style="text-align: center;"> <p>W P</p> <table> <tr> <td>S 14</td><td>S 13</td></tr> <tr> <td>T 38 N</td><td>R 11 E</td></tr> </table> <p>1941</p> </div> <p>from which</p> <p>A tamarack, 7 ins. diam., bears S. 85½° E., 82 lks. dist., mkd. W P T 38 N R 11 E S 13 B T.</p> <p>A white pine, 16 ins. diam., bears S. 4½° W., 49 lks. dist., mkd. W P T 38 N R 11 E S 14 B T.</p>	S 14	S 13	T 38 N	R 11 E
S 14	S 13				
T 38 N	R 11 E				
17.76½	N. 3° 27' W., bet. secs. 13 and 14.				
55.55	<p>Over Whitefish Lake by carefully checked triangulation. Proportionate point for ¼ sec. cor. falls in lake.</p> <p>Proportionate distance; the point for the cor. of secs. 11, 12, 13, and 14 falls in Whitefish Lake.</p>				

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the tp., which is a concrete monument, 6 ins. diam., projecting 6 ins. above ground, firmly set, with brass tablet, $\frac{3}{8}$ ins. diam., embedded in top, mkd. and witnessed as described in the official record.

N. 86° 44' W., bet. secs. 12 and 13.

Over rolling land, through scattering timber and undergrowth.

26.00 Enter pot hole, bears N. and S.

28.30 Leave pot hole, bears N. and S.

41.80 Scott Lake Road, bears N. 29° W. and S. 29° E.

42.52 The $\frac{1}{4}$ sec. cor., as determined from the remains of the original bearing trees.

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \quad \begin{array}{r} 8 \ 12 \\ \hline 8 \ 13 \\ \hline 1941 \end{array} \end{array}$$

from which

The remains of the original bearing trees,

A stump hole, bears N. 28° W., 16 lks. dist.

A rotted hemlock stump, bears S. 11° E., 17 lks. dist., with scar on NW. face.

And new bearing trees,

A maple, 4 ins. diam., bears N. 66 $\frac{3}{4}$ ° W., 37 lks. dist., mkd. $\frac{1}{4}$ S 12 B T.

A white birch, 6 ins. diam., bears S. 27 $\frac{1}{2}$ ° W., 86 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S 13 B T.

A local cor., which is a sand point, 2 ins. diam., 24 ins. above ground, bears S., 4 lks. dist.

N. 86° 45' W., bet. secs. 12 and 13 (W. half mile).

16.50 Road, bears N. 35° E. and S. 35° W.; enter improved yard W. of road.

17.98 SE. cor. of a cabin, bears N., 22 lks. dist.

21.48 The local meander cor., on the E. shore of Whitefish Lake, which is an iron pipe, 2 ins. diam., 24 ins. above ground, set in a mound of stone, accepted as marking the direction of the line bet. secs. 12 and 13.

In place of iron pipe,

Set a concrete monument, 24 ins. long, 5 ins. diam., 18 ins. in the ground, and in a mound of stone, for witness point on line bet. secs. 12 and 13, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

$$\begin{array}{r} \text{W P} \quad \begin{array}{r} \text{T 38 N} \\ \text{S 12} \\ \hline \text{S 13} \\ \text{R 11 E} \\ \hline 1941 \end{array} \end{array}$$

17

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

from which

A Norway pine, 12 ins. diam., bears N. 35° E., 12 lks. dist.,
mkd. W P T 38 N R 11 E S 12 B T.

A Norway pine, 9 ins. diam., bears S. 14° W., 61 lks. dist.,
mkd. W P T 38 N R 11 E S 13 B T.

The iron pipe was replaced alongside the concrete monument.

N. 82° 51' W., bet. secs. 12 and 13.

Over Whitefish Lake by carefully checked triangulation.

21.77

The proportionate point for the cor. of secs. 11, 12, 13 and 14
falls in lake.

Land, rolling.

Soil, sandy clay, 2nd rate.

Timber, pine along lake with scattering birch and poplar back from
lake; undergrowth, young timber and cherry.

N. 0° 47' W., bet. secs. 11 and 12.

Over Whitefish Lake.

6.60

The local cor. bet. secs. 11 and 12, on the N. shore of Whitefish
Lake, which is an iron pipe, 1 in. diam., 12 ins. above ground.

In place of pipe,

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the
ground, (with the pipe set alongside) for witness point, with an iron
post, 23 ins. long, 1 in. diam., embedded in center, with brass cap
mkd.

T 38 N	R 11 E
S 11	S 12

W P

1941

from which

A hemlock, 8 ins. diam., bears N. 34° E., 88 lks. dist., mkd.
W P T 38 N R 11 E S 12 B T.

A hemlock, 6 ins. diam., bears N. 75° W., 24½ lks. dist., mkd.
W P T 38 N R 11 E S 11 B T.

N. 1° 03' W., bet. secs. 11 and 12.

Over rolling land, through timber and undergrowth.

5.62

SE. cor. of a cabin, bears W., 47 lks. dist.

11.42

An iron pipe, 1½ ins. diam., 8 ins. above ground, bears E., 3 lks.
dist.

11.62

An iron pipe, 1 in. diam., 4 ins. above ground, bears E., 7 lks.
dist.; this pipe is set by fence cor., fence bears W.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

11.74

Old railroad grade, bears NE. and SW.

12.22

SW. cor. of a wire fence.

30.36

NW. cor. of same fence.

30.60

Scott Lake road, bears N. 80° E. and S. 80° W.

31.12

The local $\frac{1}{4}$ sec. cor., as determined from the intersection of a road from S. 86° 30' E. and fence line from S. 1° 03' E. This is the position of the cor. as established by the local surveys according to the testimony of Adolph Kloes, local surveyor, Three Lakes, Wisconsin.

At point for cor.,

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

S 11	S 12
------	------

1941

from which

A hemlock, 10 ins. diam., bears N. 51° E., 151 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S 12 B T.

A white birch, 8 ins. diam., bears N. 52 $\frac{30}{4}$ ° W., 78 lks. dist., mkd. $\frac{1}{4}$ S 11 B T.

N. 1° 23' W., bet. secs. 11 and 12 (N. half mile).

11.10

Old railroad grade, bears N. 33° 10' E. and S. 33° 10' W.

11.60

Enter swamp, bears with old railroad grade.

21.65

Left bank of Julia Creek, 50 lks. wide, course W., turning N.

24.00

Leave creek, course W. from S.

29.20

Creek, 8 lks. wide, course S. 20° W.

39.05

The cor. of secs. 1, 2, 11 and 12, which is a wooden post, 4 ins. sq., 24 ins. above ground. This cor. was established by Russell, local surveyor, in 1896.

In place of post,

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, (and set local post N. and alongside) for cor. of secs. 1, 2, 11 and 12, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

T 38 N	R 11 E
--------	--------

S 2	S 1
-----	-----

S 11	S 12
------	------

1941

from which

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin

Chains	<p>A spruce, 10 ins. diam., bears N. $64\frac{1}{2}^{\circ}$ E., $47\frac{1}{2}$ lks. dist., mkd. T 38 N R 11 E S 1 B T.</p> <p>A spruce, 6 ins. diam., bears S. $70\frac{1}{2}^{\circ}$ E., 39 lks. dist., mkd. T 38 N R 11 E S 12 B T.</p> <p>A white birch, 6 ins. diam., bears S. 81° W., $118\frac{1}{2}$ lks. dist., mkd. T 38 N R 11 E S 11 B T.</p> <p>A yellow birch, 7 ins. diam., bears N. 80° W., $65\frac{1}{2}$ lks. dist., mkd. T 38 N R 11 E S 2 B T.</p> <p>Land, rolling and level. Soil, sandy clay, 2nd and 3rd rate. Timber, pine, hemlock, birch, poplar, spruce and tamarack; undergrowth, young timber, alder and cherry.</p>
	<p>S. $87^{\circ}55'$ E., bet. secs. 1 and 12.</p> <p>Over level swamp land, through timber and undergrowth.</p>
2.90	Fork of creek, 5 lks. wide, course S. from NW. and NE.
12.00	Leave swamp, bears N. and S.
17.00	Old railroad grade, curving from S. $33^{\circ}10'$ W. to N.
21.80	Enter swamp, bears N. 15° W. and S. 15° E.
28.90	Ridge, 4 ft. high, 50 lks. wide, bears NE. and SW.
35.00	Leave swamp, bears NE. and SW.; thence over rolling land.
43.58	<p>The $\frac{1}{4}$ sec. cor., which is a wooden post, 4 ins. sq., 24 ins. long, rotted off at ground. This cor. was established by Russell, local surveyor, in 1896.</p> <p>In place of post,</p> <p>Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the ground, (and set local post alongside), for $\frac{1}{4}$ sec. cor., with an iron post, 23 ins. long, 1 in. diam., embedded in center with brass cap mkd.</p> <div><div><div>S</div><div>1</div></div><div><div><div>$\frac{1}{4}$</div><div>S 12</div></div><div>1941</div></div></div> <p>from which</p> <p>A balsam, 9 ins. diam., bears N. $26\frac{1}{2}^{\circ}$ W., 73 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.</p> <p>A white pine, 5 ins. diam., bears S. 80° W., 175 lks. dist., mkd. $\frac{1}{4}$ S 12 B T.</p>
	<p>S. $87^{\circ}45'$ E., bet. secs. 1 and 12 (E. half mile)</p>
3.35	Enter swamp, bears N. and S.
19.90	Julia Creek, 60 lks. wide, general course SW.
21.60	Leave swamp, bears N. and S.; thence over rolling land.
22.74	Record distance for the meander cor. of frac. secs. 1 and 12, on the W. shore of Lake Julia, falls on high land; there is no evidence of the original cor. at this point.
	L 3 6 8

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin

Chains

34.30 Enter pine grove, bears N. and S.

35.60 Road, bears NE. and S., curving SW.

38.52 Intersect the W. shore of Lake Julia in a position facing local bearing trees. This point is recognised by adjoining property owners as being the true meander cor., and is accepted by me as being the best available evidence of the position of the original cor.; there has been no change in the lake shore.

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for meander cor. of frac. secs. 1 and 12, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

T 38 N
S 1
----- M C
S 12
R 11 E

1941

from which

A white pine, 18 ins. diam., bears N. 23° E.,
30 lks. dist., mkd. T 38 N R 11 E S 1 M C B T.

And a local bearing tree,

A Norway pine, 16 ins. diam., bears S. 70° W.,
33½ lks. dist., mkd. M C B T.

Thence continue over lake, on a connecting line to the E. bdy.

43.30 Intersect the E. bdy. of the Tp. at the true point for the cor. of secs. 1, 6, 7, and 12, which falls in the lake.

Land, level and rolling.

Soil, sandy clay, 2nd and 3rd rate.

Timber, spruce, tamarack, pine, birch and poplar;
undergrowth, young timber and alder.

From the cor. of secs. 1, 2, 11, and 12.

N. 4°02' E., bet. secs. 1 and 2.

Over level swamp land, through timber and undergrowth.

10.00 Creek, 10 lks. wide, course SE.

11.40 Same creek, 5 lks. wide, course SW.

12.65 Leave swamp, bears E. and S. 10° W.; thence over rolling land.

16.29 Log cabin, bears E., 82 lks. dist.

16.80 Log cabin, bears W., 1.40 chs. dist.

18.45 Road, bears N. 40° E. and S. 20° W.

21.60 Wire fence, bears N. 12° E. and S. 12° W.

22.06 Log cabin, bears E., 1.00 ch. dist.

22.45 Enter swamp, bears NE. and SW.

28.75 Leave swamp, bears E. and W.

21
Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

- 35.86 Wire fence, bears NW. and SE.
36.30 Road, bears NW. and SE.
37.05 Enter swamp, bears NW. and E.
42.06 The $\frac{1}{4}$ sec. cor., which is a wooden post, 4 ins. sq., 30 ins. above ground, marked $\frac{1}{4}$ S on S., 1 on E. and 2 on W. face. This cor. was established by Russell, local surveyor, in 1896. Point for cor. falls at E. edge of swamp.

In place of post,

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, (and set local post N. and alongside) for $\frac{1}{4}$ sec. cor., with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

$\frac{1}{4}$
S 2 | S 1
1941

from which

A white pine, 7 ins. diam., bears N. $47\frac{1}{2}^{\circ}$ E., 71 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.

A white pine, 10 ins. diam., bears N. $7\frac{1}{4}^{\circ}$ W., 61 lks. dist., mkd. $\frac{1}{4}$ S 2 B T.

N. 4° 00' E., bet. secs. 1 and 2 (N. half mile).

Over rolling land, through timber and undergrowth.

- 2.67 Woods road, bears N. 65° W. and S. 65° E.
22.85 Enter pot hole, 2.00 chs. wide.
24.45 Leave pot hole.
32.55 Road, bears N. 40° E. and S. 40° W.
35.20 Thence along E. side of clearing.
39.56 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., which is a concrete monument, 6 ins. diam., 5 ins. above ground, firmly set, with brass cap embedded in top, marked and witnessed as described in the official record.

Land, rolling and level.

Soil, sandy clay, 2nd and 3rd rate.

Timber, spruce, pine, hemlock, birch and poplar; undergrowth, young timber and alder.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin.

Chains

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.
N. 3° 54' W., bet. secs. 34 and 35.

Over level semi-swamp land, through timber and undergrowth.

2.40 Enter swamp, bears NE. and SW.

42.05 Leave swamp, bears E. and W.; thence over rolling land.

43.54 The $\frac{1}{4}$ sec. cor., which is a cedar stake, 2 $\frac{1}{2}$ ins. sq., 24 ins. long,
set at SE. cor. of timber cutting.

In place of stake,

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the
ground, (with stake set alongside) for $\frac{1}{4}$ sec. cor., with an iron
post, 23 ins. long, 1 in. diam., embedded in center, with brass cap
mkd.

$\frac{1}{4}$
 S 34 | S 35
 1941

from which

A stump hole, bears N. 47° E., 6 lks. dist.

A stump hole, bears S. 63° W., 17 lks. dist.

These stump holes agree in position with the record of the
original bearing trees, and the cedar stake is accepted as
having been set from the trees.

And now bearing trees,

A yellow birch, 9 ins. diam., bears S. 70 $\frac{1}{2}$ ° E., 64 lks. dist.,
mkd. $\frac{1}{4}$ S 35 B T.

A yellow birch, 11 ins. diam., bears S. 63° W., 46 $\frac{1}{2}$ lks. dist.,
mkd. $\frac{1}{4}$ S 34 B T.

N. 0° 05' W., bet. secs. 34 and 35. (N. half mile).

11.60 Leave timber and undergrowth, enter SE. cor. of field at S. end of
a wire fence; timber about 30 lks. E. of line.

16.10 Enter field E. of line.

18.66 Fence, bears E. and W. from the N. and S. fence.

30.10 Farm road, bears E. and W.

40.46 The cor. of secs. 26, 27, 34 and 35, which is an iron pin, $\frac{1}{4}$ in.
diam., 8 ins. above ground, set in line with fence to S. and at N.
edge of field. I did not obtain any testimony of the history of
this pin, but did find it had been in use for several years and its
relation to the shores of Crooked Lake, E., W. and N., checks close-
ly with these recorded distances.

In place of pin,

Set a concrete monument, 24 ins. long, 6 ins. diam., 18 ins. in the
ground, (with the pin set N. and alongside) for cor. of secs. 26,
27, 34 and 35, with an iron post, 23 ins. long, 1 in. diam., embed-
ded in center, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin

Chains

T 38 N	R 11 E
S 27	S 26
S 34	S 35

1941

from which

A white birch, 6 ins. diam., bears N. $56\frac{1}{2}^{\circ}$ E.,
27 $\frac{1}{2}$ lks. dist., mkd. T 38 N R 11 E S 26 B T.

A poplar, 10 ins. diam., bears S. 43° E.,
8 lks. dist., mkd. T 38 N R 11 E S 35 B T.

No tree available in sec. 34.

A white birch, 5 ins. diam., bears N. $33\frac{3}{4}^{\circ}$ W.,
22 lks. dist., mkd. T 38 N R 11 E S 27 B T.

Land, level and rolling.

Soil, sandy clay, 2nd and 3rd rate.

Timber, cedar, balsam, spruce, pine, hemlock, birch, maple and poplar;
undergrowth, young timber, cherry, hazel, and alder.

From the cor. of secs. 25, 26, 35, and 36.

N. $89^{\circ}57'$ W., bet. secs. 26 and 35.

Over level swamp land, through timber and undergrowth.

8.60 Leave swamp, bears NE. and SW.; thence over rolling land.

40.90 The $\frac{1}{4}$ sec. cor., as determined from the remains of the original
bearing trees.

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with an iron post, 23 ins. long,
1 in. diam., embedded in center, with brass cap mkd.

$\frac{1}{4}$	S 26
	S 35

1941

from which

The remains of the original bearing trees,

A birch stump hole, bears N. 73° W., 12 lks. dist.

A hemlock stump hole, bears S. 57° E., 27 lks. dist.

And new bearing trees,

A hemlock, 10 ins. diam., bears N. 52° E., 91 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S 26 B T.

A maple, 9 ins. diam., bears S. 40° E., 116 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S 35 B T.

N. $85^{\circ}35'$ W., bet. secs. 26 and 35 (W. half mile).

0.05 SE. cor. of a wire fence, fences bear N. and N. $83^{\circ}41'$ W.

20.36 Wire fence, bears S. 24° E. and N. 24° W., 78 $\frac{1}{2}$ lks. dist., to

L368

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 38 N., R. 11 E., Wisconsin

Chains

E. and W. fence; leave timber and undergrowth, enter field.

29.25 Leave field, enter timber and undergrowth, bears N. 67° E., and S. 55° W.; descent steep NW. slope to Crooked Lake.

30.46 Intersect the SE. shore of Crooked Lake; there has been no change in the shore line, and the actual shore is accepted as the best available evidence of the position of the original cor.

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for meander cor. of frac. secs. 26 and 35, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

	T 38 N
	S 26
M C	—
	S 35
	R 11 E

1941

from which

A white birch, 5 ins. diam., bears N. 55° E., 62 lks. dist., mkd. T 38 N R 11 E S 26 M C B T.

A white birch, 6 ins. diam., bears S. 30° W., 29 lks. dist., mkd. T 38 N R 11 E S 35 M C B T.

Thence over lake.

38.11 Intersect the SW. shore of Crooked Lake; there has been no change in the shore line and the actual shore is accepted as the best available evidence of the position of the original cor.

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for meander cor. of frac. secs. 26 and 35, with an iron post, 23 ins. long, 1 in. diam., embedded in center, with brass cap mkd.

T 38 N	
S 26	
—	M C
S 35	
R 11 E	

1941

from which

A white birch, 5 ins. diam., bears S. 88° W., 20½ lks. dist., mkd. T 38 N R 11 E S 35 M C B T.

A white birch, 5 ins. diam., bears N. 76¼° W., 65½ lks. dist., mkd. T 38 N R 11 E S 26 M C B T..

Thence ascend NE. slope to cor.

41.06 The cor. of secs. 26, 27, 34, and 35.

Land, level and rolling.

Soil, sandy clay, 2nd and 3rd rate.

Timber, ash, cedar, spruce, tamarack, pine, hemlock, maple, birch, and poplar; undergrowth, young timber, alder, cherry, and hazel.