



United States Department of the Interior

BUREAU OF LAND MANAGEMENT
EASTERN STATES OFFICE
350 South Pickett Street
ALEXANDRIA, VIRGINIA 22304

IN REPLY REFER TO:

2000(962)VRE
WIES 31866

AUG - 5 1988

RECEIVED & FILED #	1844
Oneida County Surveyor's Office	
Date	AUG. 17 1988
By	<i>mgk</i>
OCS Area #	

Vivian Levkneht
Real Property Lister
Real Property Tax Listing Office
Box 400
Oneida County Courthouse
Rhinelander, Wisconsin 54501

Dear Ms. Levkneht:

Enclosed is a copy of the survey plat and field notes for Sections 5 and 6 in T. 37 N., R. 9 E., as requested in your April 25, 1988 letter (copy enclosed). Thank you for advising us of the prior existence of Lot 5 in the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of Section 5. We will notify your office when a correction has been made as to the designation of Lot numbers. In the meantime, please note your records as to the proper location of Lot 3 since Oneida County now claims ownership virtue of a 1985 tax deed.

Should you have any questions, contact me at (703) 461-1430.

Sincerely,

Vanessa Stuebing Engle

Vanessa Stuebing Engle
Land Law Examiner

Enclosures

1-6

1844

REAL PROPERTY TAX LISTING OFFICE

BOX 400

ONEIDA COUNTY COURTHOUSE
RHINELANDER, WISCONSIN 54501

April 25, 1988

P.L.

Ms Vanessa R Steubing
Land Law Examiner
Bureau of Land Management
350 South Picket Street
Alexandria, VA 22304


Dear Ms. Steubing:

In reference to 2000(962)VRS, ES 31866, Wisconsin. The owner in Gov Lot 1 (you have it indicated as Gov Lot 5 on your map) is B B Hoffman, 3215 N 8th St., Wausau, WI 54401. He also owns Gov Lot 2 Section 5. Gov Lot 3 is owned by Oneida County, the tax deed was taken in 1985, it was formerly owned by Michael Cahill Etal.

The original town plat indicates that Gov Lot 5 already exists in the SE SE of Section 5. Are all the Government Lots going to be re-numbered, if so could you please send us copies of the notes and plats of the Government re-surveys at no cost to us?

We do not have tax parcel mapping at the present time. Enclosed are some copies of old maps to show that Gov Lot 5 is already in the SE SE of Section 5.

Sincerely,


Vivian Levknecht
Real Property Lister

Enc.

1844

Form 100-1
December 1, 1979
Revised 10-1-80

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

03180 ORIGINAL

FIELD NOTES

OF THE
DEPENDENT RESURVEY
OF A PORTION OF THE
SOUTH AND NORTH BOUNDARIES,
A PORTION OF THE
SUBDIVISIONAL LINES
AND THE
REESTABLISHMENT
OF A PORTION OF THE
RECORD MEANDER LINES
TO INCLUDE LANDS OMITTED FROM
THE ORIGINAL SURVEY IN
SECTIONS 5 AND 6,
TOWNSHIP 37 NORTH, RANGE 9 EAST,
of the 100th Principal Meridian,
of the State of Missouri

EXECUTED BY

Michael J. Avery

Cadastral Surveyor

Under special instructions dated April 14, 19 80, approved April 25, 1980

which provided for the surveys included under U.S. Survey Group
Number 111 and assignment instructions dated April 25, 19 80

Survey commenced May 1, 19 80

Survey completed June 27, 19 80

1844

INDEX DIAGRAM

Township 37 North Range 9 East

4	3					
6	5	5	4	3	2	1
6	5					
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Portion of Record Meander Lines, Sec. 5	Pgs. 7 - 9
Portion of Record Meander Lines, Sec. 6	Pgs. 9 - 12
Portion of Meanders of Netties Lake, Sec. 5	Pg. 12
Portion of Meanders of Netties Lake, Sec. 6	Pgs. 12 - 13

1844

Township 37 North, Range 9 East,
Fourth Principal Meridian, Wisconsin 031866

CHAINS

The history of surveys of Township 37 North, Range 9 East, Fourth Principal Meridian, Wisconsin, pertinent to this resurvey and survey is as follows:

The west and north boundaries were surveyed by H. C. Fellows, Deputy Surveyor, in 1859; the subdivisional and meander lines were surveyed by Wm. E. Daugherty, Deputy Surveyor, in 1863, as shown on the plat of survey approved March 18, 1864.

The following field notes describe the dependent resurvey of a portion of the west and north boundaries, a portion of the subdivisional lines, and the reestablishment of a portion of the record meander lines to include lands omitted from the original survey in sections 5 and 6, of the township.

The surveys were executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. III, Wisconsin, dated April 14, 1980.

Preliminary to the resurvey the necessary lines of the original survey were retraced and search was made for all corners and other calls of record. Lost corners were restored and monumented at proportionate positions based upon the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by altitude observations of the sun. The lines were carried forward by sustained angulation being supplemented by other altitude observations on the sun taken throughout the progress of the survey.

All distances were determined by the use of an electronic distance measuring device (Trade name - Hewlett-Packard 3805).

The geographic position of the northeast corner of sec. 5, as scaled from the U.S. Geological Survey quadrangle map, "RHINELANDER, WIS.," prepared in 1966, is as follows:

Latitude: 45°43.9' N., Longitude: 89°23.0' W.

The mean magnetic declination is 2° East.

Dependent Resurvey, Portion of the W. Bdy.,
T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

(Restoring the 1859 survey by H. C. Fellows)

Beginning at the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., perpetuated by Norman Loftus in 1960, and recorded in the Oneida County Courthouse, by Philip T. Hansen in 1977, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap, 4x4 ins. sq., mkd.

	S1	S6	
T37N	R8E	T37N	R9E
	S12	S7	
RIPCO			

from which the remains of an orig. bearing tree:

78441

Dependent Resurvey, Portion of the W. Bdy.,
T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS

The charred remains of a stump, size indeterminate, bears N. 24° E., 193 lks. dist., no mks. visible.

and local bearing trees:

A white pine, 24 ins. diam., bears S. 1° E., 105 lks. dist., with a healed blaze.

A white pine, 30 ins. diam., bears S. 52° W., 112 lks. dist., with a healed blaze.

Not remonumented.

A wooden post, 3x3 ins. sq., projecting 2 ins. above ground, is set alongside iron post.

N. 1°26' E., bet. secs. 1 and 6.

40.03 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with the remains of a decayed wooden post, 3 ins. diam., loosely set, 3 ins. below the ground

from which the remains of an orig. bearing tree:

A decayed pine, 16 ins. diam., bears N. 64° E., 191 lks. dist., mkd. $\frac{1}{4}$ S on a charred face.
(Record, N. 46° E.)

and local bearing trees:

A white pine, 30 ins. diam., bears N. 84° E., 320 lks. dist., mkd. $\frac{1}{4}$ BT on a partially healed blaze.

A Norway pine, 18 ins. diam., bears S. 70° W., 235 lks. dist., mkd. with a healed blaze.

Not remonumented.

N. 0°56' E., beginning new measurement.

37.38 The cor. of Tps. 37 and 38 N., Rs. 8 and 9 E., monumented by Norman Loftus, with an iron post, 2 ins. diam., firmly set, projecting 30 ins. above the ground, with brass cap, 4x4 ins. sq., mkd.

T38N R8E	T38N R9E
S36	S31
T37N R8E	T37N R9E
S1	S6

RIPCO

This position is harmoniously related to existing orig. cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the orig. cor. position. There is no remaining evidence of the orig. cor. or accessories

from which local bearing trees:

A spruce, 4 ins. diam., bears N. 21° E., 28 lks. dist., mkd. SC BT on a partially healed blaze.

L844

021266

Dependent Resurvey, Portion of the W. Bdy.,
T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS

A tamarack, 4 ins. diam., bears S. 20° E.,
27 lks. dist., with a healed blaze.

A tamarack, 4 ins. diam., bears N. 40° W.,
41 lks. dist., mkd. S36 on a partially
healed blaze.

A tamarack, 4 ins. diam., bears N. 32° W.,
40 lks. dist., with a healed blaze.

Not remonumented.

A wooden post, 3x3 ins. sq., projecting 6 ins. above
ground, is set alongside iron post.

Dependent Resurvey, Portion of the N. Bdy.,
T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

(Restoring the 1859 survey by H. C. Fellows)

From the cor. of secs. 4, 5, 32 and 33, on the N. bdy.
of the Tp., perpetuated by Norman Loftus, monumented
with an iron post, 2 ins. diam., firmly set, projecting
36 ins. above the ground, with brass cap, 4x4 ins.
sq., mkd.

S32	S33
	T38N R9E
	T37N R9E
S5	S4
RIPCO	

from which the remains of the orig. bearing trees:

A stump hole, bears N. 57° E.,
15 lks. dist.

A decayed pine stump, 18 ins. diam.,
bears S. 31° E., 15 lks. dist., no
mks. visible.

A decayed pine stump, 24 ins. diam.,
bears S. 24° W., 19 lks. dist., no
mks. visible. (Record, S. 24° E.)

A decayed pine stump, 12 ins. diam.,
bears N. 48° W., 13 lks. dist., no
mks. visible.

and local bearing trees:

A white birch, 6 ins. diam., bears S. 14° W.,
17 lks. dist., mkd. SC BT on a partially
healed blaze.

A sugar maple, 6 ins. diam., bears N. 38° W.,
35 lks. dist., mkd. SC BT on a partially
healed blaze.

Not remonumented.

N. 88°52' W., bet. secs. 5 and 32.

40.39

The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, perpetuated by Norman
Loftus, monumented with an iron post, 2 ins. diam.,
firmly set, projecting 30 ins. above ground, with brass
cap, 4x4 ins. sq., mkd.

1844

Dependent Resurvey, Portion of the N. Bdy.,
T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS

$\frac{1}{2}$ S32 T38N R9E
S5 T37N R9E

from which the remains of an orig. bearing tree:

A stump hole, bears S. 45° E.,
17 lks dist.

and local bearing trees:

An aspen, 10 ins. diam., bears N. 72° E.,
27 lks. dist., with a healed blaze.

An aspen, 10 ins. diam., bears S. 12° W.,
20 lks. dist., with a healed blaze.

Not remonumented.

N. 88°52' W., beginning new measurement.

40.33 The cor. of secs. 5, 6, 31 and 32, monumented by Norman Loftus, with an iron post, 2 ins. diam., loosely set, projecting 24 ins. above ground, with brass cap, 4x4 in. sq., mkd.

S31	S32
	T38N R9E
	T37N R9E
S6	S5

This position is harmoniously related to existing orig. cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the orig. cor. position. There is no remaining evidence of the orig. cor. or accessories

from which local bearing trees:

A balsam fir, 6 ins. diam., bears N. 54° E.,
15 lks. dist., with a healed blaze.

A balsam fir, 8 ins. diam., bears S. 22° W.,
29 lks. dist., with a healed blaze.

Not remonumented.

Cor. falls in center of old, unimproved logging road,
bears N. and S.

N. 88°01' W., bet. secs. 6 and 31.

17.60 East shore of Silver Lake, bears N. 57° E. and S. 52½° W.

18.26 Point for the E. meander cor. of secs. 6 and 31, at proportionate dist., falls in Silver Lake; there is no remaining evidence of the orig. cor. Not monumented.

40.25 West shore of Silver Lake, bears N. and S.

40.32 The $\frac{1}{2}$ sec. cor. of secs. 6 and 31, monumented with a wooden post, 4x4 ins. sq., loosely set, projecting 12 ins. above ground, mkd. $\frac{1}{2}$ on N. and S. faces. The wooden post is not believed to be the orig. monument; however, this position is harmoniously related to existing orig. cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the orig. cor. position.

Not remonumented.

NO 34866

Dependent Resurvey, Portion of the
T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS

N. 89°11' W., beginning new measurement.

43.24 The cor. of Tps. 37 and 38 N., Rs. 8 and 9 E.

Dependent Resurvey, Portion of Subdivisional Lines,
T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

(Restoring the 1863 survey by Wm. E. Daugherty)

From the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, perpetuated by James D. Rein, Registered Land Surveyor, S-1234, in 1979, from orig. evidence no longer in existence, monumented with an aluminum post, 2 ins. diam., loosely set, projecting 6 ins. above ground, with cap mkd.

ONEIDA COUNTY	
T37N	R9E
S5	S4
S1234	1979
SURVEY MARKER	

from which local bearing trees:

A tamarack, 4 ins. diam., bears N. 3° E.,
71 lks. dist., mkd. $\frac{1}{4}$ S4 BT on a partially
healed blaze.

A tamarack, 8 ins. diam., bears S. 18° W.,
92 lks. dist., mkd. $\frac{1}{4}$ S5 BT on a partially
healed blaze.

Not remonumented.

N. 5°46' W., bet. secs. 4 and 5.

35.75 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of
the Tp.

From the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with
an iron pipe, 1 $\frac{1}{2}$ ins. diam., firmly set, projecting 2
ins. above ground. This position is harmoniously re-
lated to existing orig. cors., has long been recognized
as the cor. by adjacent landowners, and is accepted as
the best available evidence of the orig. cor. position.

from which local bearing trees:

A Norway pine, 12 ins. diam., bears S. 42° E.,
39 lks. dist., with a healed blaze.

A white birch, 8 ins. diam., bears N. 2° W.,
45 lks. dist., mkd. BT / S $\frac{1}{4}$ on a
partially healed blaze.

Not remonumented.

Cor. falls on S. edge of logging road, bears E. and W.

S. 89°25' W., bet. secs. 5 and 8.

40.16 The cor. of secs. 5, 6, 7, and 8, monumented with an iron
pipe, 2 ins. diam., firmly set, projecting 48 ins. above
ground, in center of mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft.
high. This position is harmoniously related to existing

Dependent Resurvey, Portion of Subdivisional Lines,
T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS

orig. cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the orig. cor. position.

Not remonumented.

S. 89°47' W., bet. secs. 6 and 7.

39.51 The $\frac{1}{2}$ sec. cor. of secs. 6 and 7, monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., loosely set, projecting 12 ins. above ground. This position is harmoniously related to existing orig. cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the orig. cor. position.

Not remonumented.

A wooden post, 4x4 ins. sq., projecting 36 ins. above ground, with the E. face mkd. $\frac{1}{4}$ S, S. face mkd. WILCOX, and W. face mkd. $\frac{1}{4}$ S, is set alongside iron pipe.

Cor. falls at intersection of old fences extending N., E., and W.

N. 87°16' W., beginning new measurement.


44.23 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.

From the cor. of secs. 5, 6, 7 and 8.

N. 1°00' E., bet. secs. 5 and 6.

35.48 Point for the meander cor. of secs. 5 and 6, for the S. side of lake, at proportionate dist.; there is no remaining evidence of the orig cor.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with cap mkd.



from which

A white pine, 10 ins. diam., bears N. 46° E., 65 lks. dist., mkd. T37N R9E S5 MC BT.

A Norway pine, 12 ins. diam., bears West, 96 lks. dist., mkd. T37N R9E S6 MC BT.

37.36 Actual S. shore of Netties Lake, bears N. 57°30' E. and S. 55°45' W.

45.08 Point for the new meander cor. of secs. 5 and 6, on the actual N. shore of Netties Lake, bears S. 58°46' E. and N. 81°30' W.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with cap mkd.

RECORD

Dependent Resurvey, Portion of Subdivisional Lines,
T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS		
	<p style="text-align: center;"> T37N R9E S6 S5 ----- MC 1980 </p> <p>from which</p> <p>A Norway pine, 12 ins. diam., bears N. 46° E., 92 lks. dist., mkd. T37N R9E S5 MC BT.</p> <p>A Norway pine, 20 ins. diam., bears N. 9° W., 150 lks. dist., mkd. T37N R9E S6 MC BT.</p> <p>59.27 Point for the meander cor. of secs. 5 and 6, for the N. side of lake, at proportionate dist.; there is no re- maining evidence of the orig. cor.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;"> T37N R9E S6 S5 ----- MC 1980 </p> <p>from which</p> <p>A spruce, 6 ins. diam., bears S. 88° E., 111 lks. dist., mkd. T37N R9E S5 MC BT.</p> <p>A spruce, 8 ins. diam., bears N. 46° W., 27 lks. dist., mkd. T37N R9E S6 MC BT.</p> <p>77.35 The cor. of secs. 5, 6, 31 and 32.</p>	
	<p style="text-align: center;">Reestablishment Portion of Record Meander Lines, Sec. 5, T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin</p> <hr/> <p style="text-align: center;">(Restoring the 1863 survey by Wm. E. Daughtery)</p> <p>The record measurements of the orig. meander lines were retraced, the residual or closing error was ascertained and the record measurements were adjusted to a closing by the broken boundary method (adopting new courses to the nearest minute and lengths to the nearest link). A portion of these meander lines are now established as a fixed and limiting boundary.</p> <p>From the meander cor. of secs. 5 and 6, for S. side of lake, heretofore described.</p> <p>N. 72°42' E., along adjusted orig. meander lines in sec. 5 held not to be grossly erroneous, and not estab- lished as a fixed and limiting boundary.</p> <p>6.55 Adjusted position for AP1.</p> <p>Not monumented.</p> <p>Thence, S. 40°30' E.</p> <p>4.49 Adjusted position for AP2.</p> <p>Not monumented.</p>	

1844

Reestablishment
 Portion of Record Meander Lines, Sec. 5,
 T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS

Thence, S. 81°27' E.

12.05 Adjusted position for AP3, on the actual SE shore of
 Netties Lake, bears N. 26°45' E. and N. 83°45' W.

Set a Copperweld, 24 ins. in the ground, with cap mkd.

AP3

T37N R9E
 S5
 BLM 1980

from which

A white pine, 5 ins. diam., bears N. 35° E.,
 31 lks. dist., mkd. X BT

The SW cor. of a frame shed, 20.3x12.1 ft.,
 bears N. 42°28' E., 700 lks. dist., the
 long side bears N. 35° E.

The SW cor. of a frame cabin, 25.8x23.9 ft.,
 bears N. 47°31' E., 658 lks. dist., the
 long side bears N. 24° E.

A tamarack, 6 ins. diam., bears S. 32° E.,
 65 lks. dist., mkd. AP3 S5 BT.

Up to this point, the adjusted orig. meander lines do
 not depart sufficiently from the actual lake shore to
 constitute a material error and are not marked as a
 fixed and limiting boundary.

Thence with the adjusted orig. meander lines, beginning
 a fixed and limiting boundary.

N. 63°46' E.

14.11 Adjusted position for AP4.

Set a Copperweld, 24 ins. in the ground, with cap mkd.

T37N
 R9E
 AP4
 S5
 BLM 1980

from which

A tamarack, 8 ins. diam., bears S. 40° E.,
 72 lks. dist., mkd. AP4 S5 BT.

A white birch, 12 ins. diam., bears N. 88° W.,
 155 lks. dist., mkd. AP4 S5 BT.

Thence, N. 5°40' W.

13.08 Adjusted position for AP5.

Set a Copperweld, 24 ins. in the ground, with cap mkd.

T37N R9E
 S5
 AP5
 BLM
 1980

L844

Reestablishment
 Portion of Record Meander Lines, Sec 3, 866
 T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS

from which

A spruce, 8 ins. diam., bears S. 76° W.,
 37 lks. dist., mkd. AP5 S5 BT.

A white birch, 8 ins. diam., bears N. 11° W.,
 17 lks. dist., mkd. AP5 S5 BT.

Thence, N. 58°30' W.

20.98 Adjusted position for AP6.

Set a Copperweld, 24 ins. in the ground, with cap mkd.

T37N R9E

S5

BLM 1980

AP6

from which

A tamarack, 10 ins. diam., bears S. 24° W.,
 266 lks. dist., mkd. AP6 S5 BT.

A tamarack, 6 ins. diam., bears N. 30° W.,
 494 lks. dist., mkd. AP6 S5 BT.

Thence, S. 77°20' W.

14.46 Remains of an old barbed wire fence line, bears N. and S.

14.49 The orig. meander cor. of secs. 5 and 6, for the N. side of lake, heretofore described.

Reestablishment

Portion of Record Meander Lines, Sec. 6,
 T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

(Restoring the 1863 survey by Wm. E. Daugherty)

From the meander cor. of secs. 5 and 6, for the N. side
 of lake, heretofore described.

S. 80°31' W., in sec. 6, along the fixed and limiting
 boundary.

3.89 Barbed wire fence line, bears N. and S.; enter uncultivated field.

6.07 Adjusted position for AP1.

Set a Copperweld, 12 ins. below the ground, with cap mkd.

T37N R9E

S6 1980

BLM

AP1

from which

A Norway pine, 7 ins. diam., bears N. 62° E.,
 231 lks. dist., mkd. AP1 S6 BT.

A spruce, 10 ins. diam., bears S. 66° E.,
 387 lks. dist., mkd. AP1 S6 BT.

1844


Reestablishment
 Portion of Record Meander Lines, Sec. 6,
 T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS

Thence, S. 64°14' W., across uncultivated field.

12.37 Adjusted position for AP2.

Set a Copperweld, 12 ins. below the ground, with cap mkd.



from which

A Norway pine, 8 ins. diam., bears S. 30° W.,
 339 lks. dist., mkd. AP2 S6 BT.


An aspen, 12 ins. diam., bears S. 83° W.,
 1035 lks. dist., mkd. AP2 S6 BT.

Thence, S. 37°36' W., across uncultivated field.

3.65 Dirt road, 20 lks. wide, bears N. 3° E. and S. 3° W.

8.62 Adjusted position for AP3.

Set a Copperweld, 12 ins. below the ground, with cap mkd.



from which

A jack pine, 12 ins. diam., bears N. 64° E.,
 360 lks. dist., mkd. AP3 S6 BT.

An aspen, 14 ins. diam., bears N. 60° W.,
 568 lks. dist., mkd. AP3 S6 BT.

Thence, S. 18°16' E., across uncultivated field.


4.06 Spider Lake Road, improved, 30 lks. wide, bears E. and W.

8.07 Dirt driveway, 15 lks. wide, bears N. 3° E. and S. 3° W.

8.60 Leave uncultivated field, edge bears N. and S.

11.07 Adjusted position for AP4.

Set a Copperweld, 24 ins. in the ground, with cap mkd.



from which

A jack pine, 14 ins. diam., bears N. 27° E.,
 45 lks. dist., mkd. AP4 S6 BT.

A white birch, 12 ins. diam., bears S. 28° E.,
 132 lks. dist., mkd. AP4 S6 BT.


Thence, S. 63°43' E.

8.46 Adjusted position for AP5.

Reestablishment
 Portion of Record Meander Lines, Sec. 6031866
 T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS

Set a Copperweld, 24 ins. in the ground, with cap mkd.



from which

The SW cor. of a frame garage, 20.2 x 19.9 ft.,
 bears N. 2°06' E., 317 lks. dist., long side
 bears N. 20° E.

The NW cor. of a frame cabin, 30.2 x 20.3 ft.,
 bears N. 19°02' E., 259 lks. dist., long side
 bears S. 16° W.

The NW cor. of a frame outhouse, 4.4 x 6.2 ft.,
 bears N. 34°03' E., 335 lks. dist., long side
 bears S. 28° W.

A white birch, 10 ins. diam., bears S. 52° W.,
 33 lks. dist., mkd. AP5 S6 BT.

A white birch, 10 ins. diam., bears N. 32° W.,
 97 lks. dist., mkd. AP5 S6 BT.

The SE cor. of a mobile home, 32.2 x 7.8 ft.,
 bears N. 25°35' W., 274 lks. dist., long side
 bears N. 30° E.

The SE cor. of a frame shed, 15.4 x 8.7 ft.,
 bears N. 24°34' W., 423 lks. dist., the long
 side bears N. 62° W.

The SE cor. of a frame garage, 26.2 x 22.1 ft.,
 bears N. 2°25' W., 408 lks. dist., long side
 bears N.


This point marks the termination of the adjusted orig.
 meander line as a fixed and limiting boundary, since the
 remainder of the lines do not depart sufficiently from
 the actual lake shore to constitute a material error.
 In order to properly define the fixed and limiting
 boundary of the omitted land at a point on the actual
 lake shore, I run on a radial line from the adjusted
 position for angle point 5.

N. 45°01' E.

1.94 Spider Lake Road, asphalt surfaced, 30 lks. wide, bears
 E. and W.

4.94 Point for the auxiliary meander cor.

Set an aluminum post, 30 ins. long, 2½ ins. diam.,
 24 ins. in the ground, with cap mkd.



from which

A white pine, 8 ins. diam., bears S. 18° W.,
 80 lks. dist., mkd. S6 AMC BT.

A spruce, 5 ins. diam., bears West, 31 lks.
 dist., mkd. X BT.

Reestablishment
 Portion of Record Meander Lines, Sec. 6,
 T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS

Thence with the calculated adjusted courses to complete the traverse from AP5.

N. 71°22' E., 11.52 chs.

11.52

The meander cor. of secs. 5 and 6, for the S. side of lake, heretofore described.

Portion of Meanders of Netties Lake, Sec. 5,
 T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

From AP3 of sec. 5, on the actual SE shore of Netties Lake.

N. 26°45' E., 5.90 chs.

N. 1°00' E., 3.10 chs.

N. 33°15' W., 4.40 chs.

S. 88°00' W., 3.20 chs.

S. 69°30' W., 3.00 chs.

S. 66°00' W., 2.30 chs.

N. 66°00' W., 3.20 chs.

N. 80°45' W., 2.60 chs.

S. 54°45' W., 3.50 chs.

N. 73°00' W., 1.70 chs.

N. 43°45' W., 2.80 chs.

N. 58°46' W., 1.38 chs. The new meander cor. of secs. 5 and 6, on the actual N. shore of Netties Lake.

Portion of Meanders of Netties Lake, Sec. 6,
 T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

From the new meander cor. of secs. 5 and 6, on the actual N. shore of Netties Lake.

N. 81°30' W., 1.00 ch.

S. 59°15' W., 6.70 chs.

S. 28°30' W., 2.80 chs.

S. 0°15' E., 2.90 chs.

S. 22°45' E., 1.25 chs. The auxiliary meander cor. of sec. 6, on the actual lake shore of Netties Lake.

General Description

Netties Lake is a permanent body of fresh water of moderate size and depth. The shore is well defined and heavily timbered.

031866

T. 37 N., R. 9 E., 4th Prin. Mer., Wisconsin

CHAINS

The greater portion of land in the omitted area is of a rolling nature, rising approximately 20 ft. above the ordinary high water mark of Netties Lake.

The area was extensively logged in the early 1900's. There are many large pine stumps which are well over 120 years of age, proving that the area was land in place at the date of the original subdivision survey. Timber consists of maple, birch, aspen, basswood, ash, balsam fir, pine, hemlock, spruce and tamarack.

The soil in the omitted area consists mainly of a well drained loamy sand on the upland areas and poorly drained organic material in the swampy areas.

The original meander lines around Netties Lake in secs. 5 and 6 are grossly erroneous; they do not follow any contour, and in some instances cross ridges at right angles.

There are a number of improvements within the omitted area, belonging to various owners.

The following list is a classification of the omitted lands in secs. 5 and 6 within the purview of the Act of September 28, 1850:

Over 50% Upland

Section 5 Lot 5

Section 5 Lot 6

Section 6 Lot 5

Over 50% Swamp and Overflowed Land

None

1844

CERTIFICATE OF SURVEY

I, ~~do~~ Michael J. Avery

HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 14th day of April, 1980, (I) ~~do~~ have dependently resurveyed a portion of the west and north boundaries, a portion of the subdivisional lines, and the re-establishment of a portion of the record meander lines to include lands omitted from the original survey in sections 5 and 6, Township 37 North, Range 9 East,

of the Fourth Principal Meridian, in the State of Wisconsin, which are represented in the foregoing field notes as having been executed by (me), ~~us~~ and under (my) ~~own~~ direction, and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 30, 1981

Date

Michael J. Avery
(Cadastral Surveyor)

Date

Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado
Alexandria, Virginia

The foregoing field notes of the dependent resurvey of a portion of the west and north boundaries, a portion of the subdivisional lines, and the reestablishment of a portion of the record meander lines to include lands omitted from the original survey in sections 5 and 6, T. 37 N., R. 9 E., Fourth Principal Meridian, Wisconsin,

executed by Michael J. Avery, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved

[Signature]
Date

[Signature]
(Chief Cadastral Survey Examination and Approval Staff)
(Chief Cadastral Surveyor, Eastern States Office)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes

Date (Chief Cadastral Survey Examination and Approval Staff)

1844