

T. 40 N 39 N 4 E 3 E 4th Mer. N.F. Chequamegon County Price State Wisconsin
 Section 6 Corner common to sections 1 6 31 and 36
 SW COR. OF TOWNSHIP BOOK 9 B.S., PAGE 25

EXISTING SURVEYS

Original Government Survey
 Year surveyed 1864
 Original monument Wood post
 Bearing Trees
 Species W. Pine Hemlock Birch Birch
 Diameter 25" 12" 9" 12"
 Bearing N 64 W N 15 E S 34 E S 51 W
 Distance 28 links 14 links 40 links 10 links


Original Evidence Found
 Year of search 1960 By ELC & BJE
 Monument found _____
 Original Bearing Trees Found
 Species None found
 Diameter _____
 Bearing _____
 Distance _____

Subsequent Corner Restoration
 Year surveyed 1936 By GLO
 Where filed or recorded U.S. Forest Service
 Monument 6" cylindrical concrete with 3/4" bronze tablet

Evidence of Subsequent Corner Restoration Found
 Year of search 1960 By ELC & BJE
 Monument found 6" concrete monument with bronze tablet 5' x 10" U.S. GENERAL LAND OFFICE SURVEY THOM T39N, R3E, R4E, S1, S2, S31, S36 1936. EXTENDS 2" ABOVE GROUND. A SQUARED POST WITH FOREST SERVICE LOC. TAG IS NEXT TO MONUMENT.
 Species W. Birch W. Pine N. Pine Pine Stump
 Diameter 6" 6" 12" 38"
 Bearing N 21 W S 10 E S 24 30' W N 70 W
 Distance 20.7' 55.6' 68.4' 19.8'
 "THOM R3E R4E"

Bearing Trees, Reference Objects
 Species ~~W. Pine~~ ~~Hemlock~~ ~~Birch~~ ~~Birch~~
 Diameter ~~6"~~ ~~6"~~ ~~12"~~ ~~38"~~
 Bearing ~~N 21 W~~ ~~S 10 E~~ ~~S 24 30' W~~ ~~N 70 W~~
 Distance ~~20.7'~~ ~~55.6'~~ ~~68.4'~~ ~~19.8'~~

1866



Relation of Evidence to Record Features Along Section Lines

Section line to sections _____
 Object _____
 Record distance _____
 Measured distance _____

Other Evidence

Describe evidence of use and occupation such as roads, fences, clearings, timber cutting lines, plantations, etc.. Cite source of testimony if any.

BRUSHED LINES RUN NORTH, SOUTH, AND EAST.

- At time of search:
 1. Did you have the record description? Yes No
 2. How was search area located? Pacing, chaining, photos, maps, etc. _____
 3. Man hours spent in search _____
 4. Do you think additional search might recover evidence? Yes No
 5. Signature Edward J. Olson

Perpetuation Record

Monument and accessories established. Include brief description of area.
BLAZED AND SCRIBED NEW BEARING TREES AS FOLLOWS:

<u>Maple</u>	<u>N. Pine</u>	<u>W. Pine</u>
<u>6"</u>	<u>11"</u>	<u>4"</u>
<u>N 88 W</u>	<u>51° 30' E</u>	<u>N 76 E</u>
<u>33.0'</u>	<u>85.3'</u>	<u>22.8'</u>

NAILED LOC. TAG ON A 12" W. PINE ON THE SOUTH SIDE OF MAIN ROAD FROM WHICH CORNER BRS SOUTH APPROX

Certified corner restoration certificate prepared: Yes No
 Filed in county records at _____ Date _____ County Document No. 445 ET
 Identified on aerial photo No. _____ Which is filed at _____

RECEIVED & FILED # _____
 Date: FEB 21 1966
 BY: _____
 COS. AREA # _____

1866

Dependent Resurvey and Extension Survey, Secs. 16 and 21,
T. 36 N., R. 8 E., 4th Principal Meridian, Wisconsin.

Chains

T 36 N R 8 E
S 19 | S 20
S 30 | S 29
1939

from which,

Dorr's bearing trees,

A white pine stump, bears N. 79° E., 13 lks. dist., has scribe mks. "B T"

A white pine stump, 16 ins. diam., bears S. 2° W., 32 lks. dist., has part of scribe mks. "B T"

And new bearing trees,

No bearing tree available to the NE.

A norway pine, 6 ins. diam., bears S. 33° E., 42 lks. dist., mkd. T 36 N R 8 E S 29 B T

A white pine, 6 ins. diam., bears S. 45° W., 89 lks. dist., mkd. T 36 N R 8 E S 30 B T

A white pine, 8 ins. diam., bears N. 80¹/₂° W., 165 lks. dist., mkd. T 36 N R 8 E S 19 B T

Land, rolling.

Soil, sandy clay mixed with stone and gravel, 2nd rate.

Timber, none.

N. 2° 43' W., bet. secs. 19 and 20.

Over rolling land, in a partly graded road, cleared field to the E. and timber to the W.

39.60 Road curves to the east, enter timber and undergrowth.

39.78 The point for the ¹/₄ sec. cor., marked by an iron pipe, 1¹/₂ ins. diam., firmly set with 15 ins. of it above ground, has been known and recognized by the adjoining land owner for 20 years; there is no remaining evidence of the original corner post or bearing trees.

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the ¹/₄ sec. cor., with brass tablet, 3¹/₈ ins. diam., 3 in. stem, embedded in top and mkd.,

¹/₄
S 19 | S 20

1939

from which,

A norway pine, 12 ins. diam., bears N. 34¹/₂° E., 54 lks. dist., mkd. ¹/₄ S 20 B T

A white pine, 10 ins. diam., bears N. 76³/₄° W., 48 lks. dist., mkd. ¹/₄ S 19 B T

N. 8° 30' E., bet. secs. 19 and 20. (N¹/₂ mile)

1.70 A winding road, bears E. and W.

3.10 Enter a graded road, bears S. 20° E. and N. along line, cleared field to the E.

22.00 Road curves to the NW., thence through timber and undergrowth.

30.20 End of cleared field to the E.

1863